## Vertical Moisture Profile Effects on the Radar Penetration into Bare Soil Surface

Ying YANG<sup>1</sup> and Kun-Shan  $\rm Chen^2$ 

<sup>1</sup>Nanjing University of Science and Technology <sup>2</sup>Guilin University of Technology

November 26, 2022

#### Abstract

This paper examines the radar penetration into a rough soil surface with a vertical moisture profile. Numerical analysis shows that the penetration depth decreases exponentially with increasing frequency, and the difference between H- and V- polarization reduces. For the incident angle dependence, the variation of penetration depth is somehow complex. For incident angle larger than 20°, the penetration depth decreases at H polarization, but increases first and then decreases at V polarization. As for soil surface dependence, the topsoil moisture content has a greater impact on the penetration depth than the surface roughness. Of the two roughness parameters, the rms height has a more significant influence on the penetration depth than the correlation length. The dependence of penetration depth on the wave polarization moderates when the surface becomes rougher. Results suggest that the penetration depth is sensitive to the inhomogeneity of moisture profiles due to the temporal evaporation process, indicating that the penetration depth is difficult to measure and an equivalent model to estimate it may be inappropriate, or at least it is difficult to establish.

# 1 Vertical Moisture Profile Effects on the Radar Penetration into Bare Soil Surface

## 3 Y. Yang<sup>1</sup>, and K. S. Chen<sup>2</sup>

- <sup>4</sup> <sup>1</sup>Nanjing University of Science and Technology, Nanjing, 210094, China
- <sup>5</sup> <sup>2</sup>Guilin University of Technology, Guilin, 541004 China
- 6 Corresponding author: Ying Yang (yangying@njust.edu.cn)

### 7 Key Points:

- The penetration depth is sensitive to the inhomogeneity of moisture profiles due to the temporal evaporation process.
- As for roughness parameters, the *RMS* height has a more significant influence on the penetration depth than the correlation length.
- For radar parameter dependence, the penetration depth is more sensitive to the radar frequency than the incident angle.

14

15

### 16 Abstract

This paper examines the radar penetration into a rough soil surface with a vertical moisture profile. 17 Numerical analysis shows that the penetration depth decreases exponentially with increasing 18 frequency, and the difference between H- and V- polarization reduces. For the incident angle 19 dependence, the variation of penetration depth is somehow complex. For incident angle larger than 20 21 20°, the penetration depth decreases at H polarization, but increases first and then decreases at V polarization. As for soil surface dependence, the topsoil moisture content has a greater impact on 22 the penetration depth than the surface roughness. Of the two roughness parameters, the rms height 23 has a more significant influence on the penetration depth than the correlation length. The 24 dependence of penetration depth on the wave polarization moderates when the surface becomes 25 rougher. Results suggest that the penetration depth is sensitive to the inhomogeneity of moisture 26 profiles due to the temporal evaporation process, indicating that the penetration depth is difficult 27 to measure and an equivalent model to estimate it may be inappropriate, or at least it is difficult 28 29 to establish.

### 30 1 Introduction

Microwave sensor has the advantage of penetrating capability compared to optical 31 sensors(Farr, 1986 & Ulaby, 2014). A general concurrency is that the penetration depth decreases 32 with increasing radar frequency and moisture content (Bruckler, 1988 & Rao, 1988 & Risman, 33 34 1991 & Boisvert, 1995). However, how deep a radar at a specific wavelength can penetrate a moist soil surface is still vague. For example, the study in (Owe,1988) found that observed "effective 35 penetration depth" exceeded the theoretically defined value, perhaps raised from several aspects. 36 One is the presence of a rough boundary upon which the wave is impinging. Another is the 37 complexity of the moisture profile over depth in which the wave propagates through. Yet, the 38 dielectric model that relates the moisture content to the permittivity as a function of radar 39 wavelength, soil texture, and temperature may also excises some influences in determining the 40 penetration depth (Owe,1988 & Lv, 2018 & Singh, 2018), where the penetration depth may be 41 calculated based on power attenuation via transmissivity (Risman, 1991) or field propagation via 42 43 transmitted coefficient (Bruckler, 1988) through the plane boundary. In this context, the penetration depth is usually confused with the skin depth, although physically they are the same, 44 only differ by 2. By far, the penetration depth is defined at normal incidence upon a plane boundary. 45 This further generates two issues. A plane boundary is rarely found in natural soil surface in 46 microwave regions. A local incidence due to roughness will alter the scattering pattern. Hence the 47 penetration depth must be modified accordingly. Radar observation at normal incidence is not 48 49 common; if not peculiar, it will lose the polarization information and result in the ground range ambiguity. 50

51 For inhomogeneous medium such as soil, an equivalent multilayered model may be applied to calculate the penetration depth (Ulaby, 2014). The influence of inhomogeneity on 52 backscattering detailed in (Zribi, 2013) showed a dependence on the radar frequency, which 53 subsequently altered the penetration depth. The study of (Zribi, 2013) confirmed that the inclusion 54 of moisture inhomogeneity gave a better match between model predictions and SAR observations. 55 The presence of surface inhomogeneity generally leads to features that do not appear in the 56 57 homogeneous surface, including the scattering coefficient is enhanced on the whole scattering plane (Yang, 2019). These features offer significant implications to how we devise the moisture 58 profile inversion effectively. Hence, in this study, it is desirable to re-examine the radar penetration 59

60 depth perturbed by the soil roughness and inhomogeneity. Moreover, the polarization and angle

61 information are taken into account. It is so in line of the radar sensing of soil moisture, and thus an 62 effective retrieval of moisture profile.

### 63 **2** Basic Wave Transmission Through a Rough Boundary with an Inhomogeneous Medium

64 2.1 Reflectivity and transmissivity

Referring to Fig.1, consider an uniform plane wave *p*-polarized  $\mathbf{E}_p^i$  incident onto the boundary, the incident filed, reflected field, and the transmitted field can be expressed by with time-harmonic phase factor  $e^{j\omega t}$  understood.

$$\vec{E}_{p}^{i} = \hat{p}E_{0}e^{-j\vec{k}_{i}\cdot\vec{r}}; \ \vec{E}_{p}^{s} = \hat{p}R_{p}E_{0}e^{j\vec{k}_{s}\cdot\vec{r}}; \ \vec{E}_{p}^{t} = \hat{p}T_{p}E_{0}e^{-j\vec{k}_{t}\cdot\vec{r}}$$
(1)

69 where  $E_0$  is the amplitude of the incident electric field,  $\vec{r} = \hat{x}x + \hat{y}y + \hat{z}z$  is position vector;  $R_p$  and 70  $T_p$  are *p*- polarization reflection and transmission coefficients are determined by imposing the 71 boundary conditions on the tangential and normal fields across the boundary. The propagating 72 vectors, or the wave vectors, appearing in the spatial phase of (1) are given by  $\vec{k_i}, \vec{k_s}, \vec{k_t}$  (Ulaby, 73 2014). Assuming that the wave incidence is in free-space and the transmitted medium (moist soil) 74 is non-magnetic, namely,  $\varepsilon_i = \varepsilon_0; \mu_i = \mu_t = \mu_0$ .



76 77

# Figure 1. Geometry of wave scattering from a rough surface with inhomogeneous dielectric profile.

In what follows, we shall consider the linear polarizations, horizontal, and vertical polarization, since other polarizations can be constructed by combining two linear polarizations. Once permittivity and permeability for the media is given, both the reflection coefficient and transmission coefficient can be determined.

For horizontal polarization, the reflectivity  $\Gamma_{h}$  and the transmissivity  $\Im_{h}$  are

$$\Gamma_{h} = \left| R_{h} \right|^{2} \quad , \Im_{h} = \frac{\mathscr{R}_{e} \{ \cos \theta_{t} / \eta_{t} \}}{\mathscr{R}_{e} \{ \cos \theta_{i} / \eta_{i} \}} \left| T_{h} \right|^{2} \tag{2}$$

85 86

For vertical polarization, the reflectivity  $\Gamma_v$  and transmittivity  $\Im_v$  are

$$\Gamma_{v} = \left| R_{v} \right|^{2} \quad , \Im_{v} = \frac{\mathscr{R}e\{\eta_{i}\cos\theta_{t}\}}{\mathscr{R}e\{\eta_{t}\cos\theta_{i}\}} \left| T_{v} \right|^{2}$$
(3)

The incident angle  $\theta_i$  to refraction angle  $\theta_i$  are related by the Snell's law. Note that the 88 transmissivity is defined at a plane interface between two media. The interface between layers, 89 including top and bottom boundaries, in general, is rough. Hence, modification of the 90 transmissivity to account for the rough boundary is necessary. It is understood that the Fresnel 91 reflection coefficient for a rough boundary is dependent on the local incident angle as long as there 92 93 are local tangent planes that exist. In order to convert global incidence into local incidence, the ppolarized reflection coefficient evaluated at a transition angle is given by (Wu, 2001). It is known 94 that the reflection coefficient is dependent on the surface rms height and the correlation function, 95 or equivalently, the roughness spectrum, to account for the full variation of surface roughness and 96 radar parameters. 97

In the preceding discussion, we assumed the transmitted medium being homogeneous.
However, natural surfaces are generally inhomogeneous, with permittivity being spatially nonuniform. For an inhomogeneous medium with a continuous dielectric profile, the reflectivity and
transmissivity are a function of depth.

102 2.2 Vertical inhomogeneity

87

Following(Njoku,1977), the vertical moisture profile of soil surface in dry up or wet down
 conditions may be modelled by

105 
$$m_v(z) = \begin{cases} m_{v0} + \frac{e^{\beta z} - 1}{e^{-\beta d} - 1} (m_{vb} - m_{v0}), & -d \le z \le 0\\ m_v(-d) & z \le -d \end{cases}$$
(4)

where z is depth, and d is the total layer depth;  $m_{v0}$ ,  $m_{vb}$  are volumetric moisture content at top and bottom boundaries, respectively. The moisture content at bottom is also referred as background moisture content.



## Figure 2. Moisture profile of various soil condition, top soil moisture $m_{v0}=5\%$ , background soil moisture $m_{vb}=40\%$ , $\beta = -0.3, -0.1, 0.001, 0.1, 0.3$ .

In Fig.2, we present several typical monotonic dielectric profiles with moisture content 112 varying in the z-direction by controlling  $\beta$  values. For a minimal amount of  $\beta$ , the moisture 113 content and depth approach to a linear relationship. For unfrozen soil, we employ the generalized 114 refractive mixing dielectric model (GRMDM) (Mironov, 2009 & Mialon, 2015)to relate the 115 moisture content to permittivity. For more about the influence of the dielectric model on the 116 estimating penetration depth, please refer to (Singh, 2018). Once the permittivity profile 117 corresponding to the moisture profile (4) is established, it is possible to derive analytic expressions 118 for the reflection coefficients. However, it is too laborious to do so. Instead, we seek a numerical 119 120 solution by discretizing the continuous profile into multilayers. The number of layers is 500, and the thickness of the layers is 0.1cm. For a multi-layered medium, we used a recursive formula to 121 calculate the reflection coefficients. 122

#### 123 **3 Penetration Depth for Homogeneous and Inhomogeneous Media**

109

125

124 For a homogeneous medium, the power transmission into the medium is

$$P_p(z) = P_p(0) \Im_p e^{-j2k_{tz}z}$$
<sup>(5)</sup>

where  $\Im^p$  is transmissivity at the interface between air and medium, subscript p=h, v indicates polarization;  $k_{tz}$  is the z-component of the wavenumber in the transmitted medium. The penetration depth  $\delta_n$  is defined as

129 
$$e^{-1} = \frac{P_p(z)|_{z=\delta_p}}{P_p(0)\Im_p}$$
(6)

130 
$$\delta_p = \frac{\lambda}{4\pi} \left[ \frac{\varepsilon'}{2} (\sqrt{1 + \tan^2 \delta} - 1) \right]^{1/2}$$
(7)

where the loss tangent is  $\tan \delta = \varepsilon'' / \varepsilon'$ ;  $\varepsilon', \varepsilon''$  are, respectively, real part and imaginary part of the permittivity of the homogeneous medium.

133

136

145

For an inhomogeneous medium with continuous dielectric profile, the power transmission into the medium may be expressed as an integral form:

$$P_p(z) = P_p(0) \int_0^z \Im_p(z') \exp\left[-j2k_{tz}(z')dz'\right] \Box$$
(8)

where  $\Im_p(z')$  is transmissivity at the interface z',  $k_{tz}(z')$  is the z-component of the wavenumber as function of z' in the medium as

139 
$$k_{tz}(z') = k_0 \sqrt{\varepsilon_r(z')\mu_r - \sin^2 \theta_0}$$
(9)

140 It follows that the penetration depth is given by

141 
$$\int_{0}^{\delta_{p}} \Im_{p}\left(z'\right) \exp\left[-j2k_{z}\left(z'\right)dz'\right] = e^{-1} \Box$$
(10)

142 As argued in (Ulaby, 1974), for homogeneous soil surface, we compute the penetration  $\delta_p$ 143 using (7) but replacing moisture profile  $m_v(z)$  with an averaged soil moisture  $\overline{m}_v$  over the depth 144 from top to bottom boundaries:

144 Ifom top to bottom boundaries.

$$\overline{m}_v = \frac{1}{d} \int_{-d}^0 m_v(z) dz \tag{11}$$

It should be noted that in calculating the reflection coefficient of a multilayered medium such as we deal with the profiles in (4), the multiple scattering and the volume scattering are ignored, among other effects. Hence, the penetration depth by the transmittivity varying with depth may be biased compared to real measurement. More discussions about the layering effects on the backscattering and the moisture retrieval can be found in (Konings, 2014). Nevertheless, the penetration depth causes a phase delay, measurable by InSAR, could be an alternative for estimating the soil moisture (Nolan, 2003).

### **4 Effect of Radar and Soil Parameters on Penetration Depth**

154 4.1 Radar parameters dependence

Fig. 3 shows the penetration depth  $\delta_p$  as a function of frequency for homogeneous and inhomogeneous soil surfaces, where, as an example, the top soil moisture  $m_{v0}$  is 5%, and the background soil moisture is 40%. The frequency varies from 1 GHz to 12 GHz. The normalized

correlation length kl is set as 10, and the normalized rms height  $k\sigma$  is 1. The incident angle is 158 40°. Fig. 3 shows the penetration depths from inhomogeneous soil surface are deeper than the 159 homogeneous surfaces. This phenomenon stems from the fact that the averaged moisture of 160 homogeneous soil is wetter than the top layer soil of inhomogeneous soil surface. Hence, the 161 transmissivity is relatively smaller for homogeneous soil. As the frequency increases, the 162 penetration depth decreases exponentially. The differences in penetration depth between 163 homogeneous and inhomogeneous soil surface significantly decrease as the frequency increases. 164 165 Note that the penetration depth is deeper at V-polarized than at H-polarized incidences because the transmissivity is higher at vertical polarization. The difference between H- and V-polarizations 166 reduces with increasing frequency. 167

168 The moisture profile is a function of  $\beta$ , which controls the change rate of the soil moisture 169 content in z-direction. The change rate  $\beta$  affects the penetration depth through the dielectric 170 model corresponding to the vertical moisture profile in (4). Furthermore, the penetration depth for 171 two different soil type (Mironov, 2009) shown in Figure 3(b). As a whole, the difference in 172 penetration depth is about 3-5cm from 1-12 GHz of frequencies.



Figure 3. Penetration depth as a function of frequency. (a) homogeneous ( $\bar{m}_v=22.65\%$ ) and inhomogeneous soil ( $m_{v0}=5\%, m_{vb}=40\%$ )surfaces. (b) inhomogeneous  $\beta = 0.1, 0.001, -0.1$ , (b) inhomogeneous: Sand=88%,Clay=4%, and Sand=2%, Clay=76%.

173

174

To demonstrate how the penetration depth changes due to the moisture profile, in Fig. 3(c) we plot the penetration depth by varying change rates of  $\beta = 0.1, 0.001, -0.1$ . As the absolute value of  $\beta$  increases, the penetration depth decreases correspondingly. The penetration is deeper when  $\beta = -0.1$ . This phenomenon is easily expected for the upper layer with  $\beta = -0.1$  is drier than that with  $\beta = 0.1$ . When the soil is dry, the transmissivity is larger, so is the penetration.



Figure 4. Transmissivity (a) and penetration depth (b) as a function of incident angle at L band. Homogeneous ( $\bar{m}_{w}=22.65\%$ ) and inhomogeneous soil ( $m_{w0}=5\%, m_{wb}=40\%$ )surfaces.

184

185

Similarly, in Fig. 4, the transmissivity's dependence and the penetration depth on the 188 incident angle are presented. For numerical illustration, we fixed the frequency at 1.25GHz. As 189 the incident angle increases, there are two common trends both for homogeneous and 190 inhomogeneous soil surface, including 1) the H-polarized penetration depth decreases, but the V-191 polarized penetration depth increase first and then decreases. The penetration depth is affected by 192 the incident angle because it is a function of transmissivity. For the rough boundary, the V-193 polarized transmissivity along the incident direction increase first and then decreases, and the 194 inflection point appears at the position of Brewster's angle; 2) Penetration depth is deeper in V-195 polarization than in H-polarization, and the difference in penetration depth between the two 196 polarizations gradually increase with increasing incident angle. By comparison with the 197 homogeneous soil surface, the penetration depth of the inhomogeneous soil surface is relatively 198 deeper, and the polarization difference is more pronounced. This phenomenon is given rise by the 199 top layer moisture of inhomogeneous soil being drier than the averaged moisture content over the 200 soil depth. The maximum difference between horizontal and vertical polarizations is about 10cm 201 around  $75^{\circ}$  of incident angle, which is just the Brewster angle in this case. To define an equivalent 202 homogeneous model from an inhomogeneous medium is never straightforward. A large difference 203 of the penetration depths between the two media tells that an equivalent model is difficult, if not 204 impossible, to apply when it comes to estimate the penetration depth at a specific radar wavelength. 205

We now illustrate the coupling effect of frequency and incident angle on the penetration depth by changing one of them while fixing the other. Fig. 5 (a) and Fig. 5 (b) show the contour plots of penetration depth for the inhomogeneous soil surface at H- and V- polarized incidences, respectively. As can be seen from Figs. 5 (a), (b), the tendency of penetration depth in H polarization is quite different from that in V polarization. By comparison, the penetration depth occurs at a larger dynamic range of incident angle in V polarization, but in H polarization, the

- 212 penetration depth is almost zero when  $\theta_i > 75^\circ$ . The dynamic range of penetration depth is about
- 213 24cm when the frequency varies from 1 to 10 GHz, and the incident angle changes from  $0^{\circ}$  to  $85^{\circ}$ .
- The maximum polarization difference occurs at low frequencies (e.g., L band) and at a large
- incident angle, e.g.,  $70^{\circ}$ ~85°, which, however, are rarely used due to low backscattering returns.



Figure 5 Penetration depth as a function of frequency and incident angle for inhomogeneous soil surface  $m_{v0}=5\%, m_{vb}=40\%$ ,  $kl=10, k\sigma = 1$   $\beta = 0.001$ . (a): H polarization, (b): V polarization.

4.2 Soil parameters dependence

We now examine the soil parameters dependence on the penetration depth. Figs. 6 (a), (b) 221 show the overall varying of penetration depth with top and the background soil moisture contents, 222 respectively, with surface roughness as  $kl=10, k\sigma = 1$ , with an incident angle of 40° and 223 frequency of 1.25 GHz. Fig. 6 (a) shows the penetration depth when the backgroud soil 224 moisture is fixed at 40% and the top soil moisture varies from 5% to 40%, and Fig. 6 (b) plots the 225 penetration depth with the background soil moisture varying from the 5% to 40%, and topsoil 226 moisture of 5%. It indicates that the penetration depth decreases as both the top and the background 227 soil moistures increase. When the topsoil moisture varies from 5% to 40%, the dynamic range of 228 penetration depth for inhomogeneous soil surface is about 10cm but that for homogeneous soil 229 surface is only about 2cm. In the above illustration, the penetration depth of an inhomogeneous 230 soil surface is more sensitive to the topsoil moisture. Yet for the homogeneous soil surface, it is 231 dependent on the background soil moisture. It is worth noting that the penetration depth differences 232 between H- and V- polarization is only about 1~2cm. 233



Figure 6 Penetration depth as a function of (a) top soil moisture  $m_{v0}=5\sim40\%$  with  $m_{vb}=40\%$ ; (b) background soil moisture  $m_{vb}=5\sim40\%$  with  $m_{v0}=5\%$ .

240 We now examine the penetration depth dependence of surface roughness at L band. We set the incident angle to  $40^{\circ}$  and the normalized correlation length to 10, while changing the 241 normalized rms heights from 0 to 5. From Fig.7 (a), as the rms height increases, the penetration 242 depth at horizontal polarization increases first and tends to flatten, while diminishes first at vertical 243 polarization. The difference of penetration depth between H- and V- polarization is about 2-3cm 244 for the fairly flat boundary. But when the *rms* height is large enough, say,  $k\sigma > 3$ , the penetration 245 depths are almost the same at H- and V- polarizations; that is, the difference in penetration depth 246 at two polarizations reduces due to the roughness. Fig. 7(b) plots the penetration depth as a 247 function of normalized correlation length. The overall penetration depth dependence on the 248 correlation length is similar to that on the *rms* height. 249



250 251

234 235 236

239

### Figure 7 Penetration depth as a function of (a) normalized *rms* height $k\sigma$ at kl=10 and (b) normalized correlation length kl at $k\sigma=2$ .



Figure 8 Penetration depth as a function of top soil moisture  $m_{v0}$  and normalized *rms* height  $k\sigma$  for inhomogeneous soil surface with parameters similar to Fig.3. (a): H polarization, (b): V polarization.

259 We observe that the topsoil moisture and rms height are two main soil surface parameters to determine the penetration depth. As shown in Fig. 8, physically, the penetration depth is more 260 sensitive to the topsoil moisture than the rms height. We see that the contour plots of the 261 penetration depths are very distinct, especially for a small normalized rms height. The penetration 262 263 depth is a complicated factor that strongly depends on the surface roughness of the top boundary under which the dielectric constant is vertically varying. To define a radar medium, be it a 264 subsurface layer or a volume layer as a half-space, seems problematic. It is worth to examine such 265 effects on the inferring surface parameters, e.g., moisture content, roughness, surface height (Dall, 266 2007), or snow water equivalent content (Yueh, 2017). 267

## 268

254

255

### 269 **5 Conclusions**

This study investigates the penetration depths from an inhomogeneous rough soil surface 270 with a vertical moisture profile. The penetration depth is deeper at V polarization than at H 271 polarization. For radar parameter dependence, the penetration depth is more sensitive to the radar 272 frequency than the incident angle. As the frequency increases from 1 GHz to 10 GHz, the 273 penetration depth decreases exponentially, and the difference between the two polarizations 274 shrinks. With increasing incident angle, the penetration depth decreases in H polarization, but 275 increases first and decreases in V polarization. As for soil conditions dependence, the topsoil 276 moisture has a more significant effect on penetration depth than the surface roughness. As the top 277 soil moisture becomes drier, the difference of penetration depth between two polarizations 278

decreases. When the rms height increases, the penetration depth in horizontal polarization increases first and then tends to flat out, but that in vertical polarization diminishes first. The penetration depth is found more sensitive to polarization at smaller rms heights and correlation lengths.

283

### 284 **References**

Bruckler, L., Witono, H., & Stengel, P. (1988), Near surface soil moisture estimation from
microwave measurements, *Remote Sensing of Environment*, 26 (2), 101-121. doi:10.1016/00344257(88)90091-0.

Boisvert, J. B., Gwyn, Q. H. J., Brisco, B., Major, D. J., & Brown, R. J. (1995), Evaluation of
soil moisture estimation techniques and microwave penetration depth for radar applications, *Canadian Journal of Remote Sensing*, 21(2), 110-123. doi: 10.1080/07038992.1995.10874606.

Dall, J.(2007), InSAR elevation bias caused by penetration into uniform volumes, *IEEE Transactions on Geoscience and Remote Sensing*, 45(7), 2319-2324. doi:
 10.1109/TGRS.2007.896613.

Farr, T. G., Elachi, C., Hartl, P., & Chowdhury, K. (1986), Microwave penetration and
attenuation in desert soil: A field experiment with the shuttle imaging radar, *IEEE Trans. Geosci. Remote Sens.*, GE-24(4), 590–594. doi: 10.1109/TGRS.1986.289675.

Konings, A. G., Entekhabi, D., Moghaddam, M., & Saatchi, S. S.(2014), The effect of variable
soil moisture profiles on P-band backscatter, *IEEE Transactions on Geoscience and Remote Sensing*, 52(10), 6315–6325. doi: 10.1109/TGRS.2013.2296035.

- Lv, S., Zeng, Y., Wen, J., Zhao, H., & Su, Z. (2018), Estimation of penetration depth from soil effective temperature in microwave radiometry, *Remote Sensing*, 10(4), 519. doi: 10.3390/rs10040519.
- Mironov, V. L., Kosolapova, L. G., & Fomin, S. V. (2009), Physically and mineralogically based
   spectroscopic dielectric model for moist soils, *IEEE Transactions on Geoscience and Remote Sensing*, 47(7), 2059–2070. doi: 10.1109/TGRS.2008.2011631.
- Mialon, A., Richaume, P., Leroux, D., Bircher, S., Bitar, A., Pellarin, T., Wigneron, J. P., & Kerr,
  Y. H. (2015), Comparison of Dobson and Mironov dielectric models in the SMOS soil moisture
  retrieval algorithm, *IEEE Transactions on Geoscience and Remote Sensing*, 53(6), 3084–3094.
  doi: 10.1109/TGRS.2014.2368585.
- Njoku, E. G., & Kong, J. A. (1977), Theory for passive microwave remote sensing of near-surface
  soil moisture, *Journal of Geophysical Research*, 82(20), 3108-3118. doi:
  10.1029/JB082i020p03108.

- Nolan, M., & Fatland, D. R. (2003), Penetration depth as a DInSAR observable and proxy for
- soil moisture, IEEE Transactions on Geoscience and Remote Sensing. 41(3), 532-537. doi:
- 315 10.1109/TGRS.2003.809931.
- Owe, M., & Van de Griend, A. A.(1998), Comparison of soil moisture penetration depths for
- 317 several bare soils at two microwave frequencies and implications for remote sensing, Water
- 318 *Resources Research*, 34(9), 2319–2327. doi:10.1029/98WR01469.
- Rao, K. S., Chandra, G., & Rao, P. V. N. (1988), Study on penetration depth and its dependence
- 320 on frequency, soil moisture, texture and temperature in the context of microwave remote sensing,
- Journal of the Indian Society of Remote Sensing, 16(2), 7-19. doi:10.1007/BF03014300.
- Risman, P. (1991), Terminology and notation of microwave power and electromagnetic energy,
- 323 Journal of Microwave Power and Electromagnetic Energy, 26(4), 243-250.
- doi:10.1080/08327823.1991.11688163.
- 325 Singh, A., Meena, G. K., Kumar, S., & Gaurav, K. (2018), Analysis of the effect of incidence
- angle and moisture content on the penetration depth of L- and S-band SAR signals into the ground
- 327 surface, ISPRS Ann. Photogramm. Remote Sens. Spatial Inf. Sci., 5, 197–202. doi: 10.5194/isprs-
- 328 annals-IV-5-197-2018.
- Ulaby, F. T., & Long, D. G. (2014), *Microwave radar and radiometric remote sensing*. Ann
  Arbor, MI, USA: Univ. of Michigan Press.
- Ulaby, F. T., Cihlar, J., & Moore, R. K. (1974), Active microwave measurement of soil water content, *Remote Sensing of Environments*, 3, 185-203. doi:10.1016/0034-4257(74)90004-2
- Wu, T. D., Chen, K. S., Shi, J. C., & Fung, A. K.(2001), A transition model for the reflection
  coefficient in surface scattering," *IEEE Transactions on Geoscience and Remote Sensing*, 39(9),
  2040-2050. doi: 10.1109/36.951094.
- Yueh, S. H., Xu, X., Shah, R., Kim, Y., Garrison, J. L., Komanduru, A., & Elder, K. (2017),
  Remote sensing of snow water equivalent using coherent reflection from satellite signals of
  opportunity: theoretical modeling, *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 10(12), 5529–5540. doi:10.1109/JSTARS.2017.2743172.
- Yang, Y., & Chen, K. S. (2019), Full-polarization bistatic scattering from an inhomogeneous
  rough surface, *IEEE Transactions on Geoscience and Remote Sensing*, 57(9), 6434–6446. doi:
  10.1109/TGRS.2019.2906079.
- Zribi, M., Gorrab, A., Baghdadi, N., Lili-Chabaane, Z., & Mougenot, B.(2013), Influence of radar
  frequency on the relationship between bare surface soil moisture vertical profile and radar
  backscatter, *IEEE Geoscience and Remote Sensing Letters*, 11(4), 848–852. doi:
  10.1109/LGRS.2013.2279893.