Monitoring and Forecasting Injection Induced Fault Reactivation and Seismicity in the Laboratory using Active UltrasonicMethods

Aukje Veltmeijer¹, Milad Naderloo¹, Anne Pluymakers¹, and Auke Barnhoorn¹

¹Delft University of Technology

December 11, 2023

Abstract

Induced earthquakes are still highly unpredictable, and often caused by variations in pore fluid pressure. Monitoring and understanding the mechanisms of fluid-induced fault slip is essential for seismic risk mitigation and seismicity forecasting. Fluid-induced slip experiments were performed on critically stressed faulted sandstone samples, and the evolution of the actively sent ultrasonic waves throughout the experiment was measured. Two different fault types were used: smooth saw-cut fault samples at a 35° angle, and a rough fault created by in-situ faulting of the samples. Variations in the seismic slip velocity and friction along the fault plane were identified by the coda of the ultrasonic waves. Additionally, ultrasonic amplitudes show precursory signals to laboratory fault reactivation. Our results show that small and local variations in stress before fault failure can be inferred using coda wave interferometry for time-lapse monitoring, as coda waves are more sensitive to small perturbations in a medium than direct waves. Hence, these signals can be used as precursors to laboratory fault slip and to give insight into reactivation mechanisms. Our results show that time-lapse monitoring of coda waves can be used to monitor local stress changes associated with fault reactivation in this laboratory setting of fluid-induced fault reactivation. This is a critical first step towards a method for continuous monitoring of natural fault zones, contributing to seismic risk mitigation of induced and natural earthquakes.

Hosted file

981728_0_art_file_11671649_s5ccss.docx available at https://authorea.com/users/549267/ articles/692475-monitoring-and-forecasting-injection-induced-fault-reactivation-andseismicity-in-the-laboratory-using-active-ultrasonicmethods







45

с







ore
1 90
5
ms
uta
ñ
ų.
We
Nie.
-1.e
06.61
n I
06
ot.
SB
ha
t a
Ľ.
rep
a b
.8
nis
Ē
F
33
349
976
00 00
<u>8</u>
231
202
1
SOa
ŝ
ŧ.
225
.01
iop
8
-57
htt
- htt
on. — http
ssion. — http
mission. — http
permission. — http
ut permission. — htt
hout permission. — http
without permission. — http
se without permission. — http
reuse without permission. — http
Vo reuse without permission. — http://www.com/com/com/com/com/com/com/com/com/com/
 No reuse without permission. — http://www.action.
ved. No reuse without permission. — http://www.action.com/
served. No reuse without permission. — http://www.action.com/action/
reserved. No reuse without permission. — http://www.internet.com/
hts reserved. No reuse without permission. — http:// http:/
rights reserved. No reuse without permission. — http://www.action.a
All rights reserved. No reuse without permission. — http://www.all.com/all.com/all/all/all/all/all/all/all/all/all/al
r. All rights reserved. No reuse without permission. — http://www.all.com/al
der. All rights reserved. No reuse without permission. — http://www.all.com/al
funder. All rights reserved. No reuse without permission. — http://www.all.com/a
or/funder. All rights reserved. No reuse without permission. — http://www.com/com/com/com/com/com/com/com/com/com/
ithor/funder. All rights reserved. No reuse without permission. — http://www.all.com/all
author/funder. All rights reserved. No reuse without permission. — http://www.action.
the author/funder. All rights reserved. No reuse without permission. — http://www.action.
is the author/funder. All rights reserved. No reuse without permission. — http://www.author.com/author/funder.auth
ler is the author/funder. All rights reserved. No reuse without permission. — http://www.action.com/action/acti
nolder is the author/funder. All rights reserved. No reuse without permission. — http://www.authout.com/authout/funder.authout/f
it holder is the author/funder. All rights reserved. No reuse without permission. — htt
right holder is the author/funder. All rights reserved. No reuse without permission. — http://www.action.com/action/
pyright holder is the author/funder. All rights reserved. No reuse without permission. — http://www.authout.com/authout/
copyright holder is the author/funder. All rights reserved. No reuse without permission. — http://www.news.org/all/all/all/all/all/all/all/all/all/al
The copyright holder is the author/funder. All rights reserved. No reuse without permission. — http://www.news.com/news/author/funder/
 The copyright holder is the author/funder. All rights reserved. No reuse without permission. — hth
3 - The copyright holder is the author/funder. All rights reserved. No reuse without permission. — http://www.com/defined/com/theta/function/theta/functi
3023 — The copyright holder is the author/funder. All rights reserved. No reuse without permission. — http://www.author.com/authout/permission/authout/authout/permission/authout/autho
sc 2023 — The copyright holder is the author/funder. All rights reserved. No reuse without permission. — http://www.action.com/action/actio
Dec 2023 — The copyright holder is the author/funder. All rights reserved. No reuse without permission. — http://www.new.edu/action.com/action/a
11 Dec 2023 — The copyright holder is the author/funder. All rights reserved. No reuse without permission. — hth
on 11 Dec 2023 — The copyright holder is the author/funder. All rights reserved. No reuse without permission. — hth
ed on 11 Dec 2023 — The copyright holder is the author/funder. All rights reserved. No reuse without permission. — hth



/doi.org/10.22541/essoar.170231638.86764983/v1 — This is a preprint and has









Precursory Signals to Injection Induced Fault Reactivation in the Laboratory using Active Ultrasonic Monitoring Methods

3 A. Veltmeijer¹, M. Naderloo¹, A. Pluymakers¹ and A. Barnhoorn¹

- ¹Delft University of Technology, Faculty of Civil Engineering and Geosciences, Section of
 Applied Geophysics and Petrophysics.
- 6 Corresponding author: Aukje Veltmeijer (<u>a.v.veltmeijer@tudelft.nl)</u>

7 Key Points:

- Time-lapse monitoring of coda waves can be used to monitor injection-induced fault reactivation in the laboratory.
- Different stages of fault reactivation in the laboratory seismic cycle can be identified using ultrasonic monitoring.
- Transmission measurements change prior to injection-induced fault reactivation on smooth and rough fault planes.

14

15 Abstract

- 16 Induced earthquakes are still highly unpredictable, and often caused by variations in pore
- 17 fluid pressure. Monitoring and understanding the mechanisms of fluid-induced fault slip is
- 18 essential for seismic risk mitigation and seismicity forecasting. Fluid-induced slip
- 19 experiments were performed on critically stressed faulted sandstone samples, and the
- 20 evolution of the actively sent ultrasonic waves throughout the experiment was measured.
- 21 Two different fault types were used: smooth saw-cut fault samples at a 35° angle, and a rough
- fault created by in-situ faulting of the samples. Variations in the seismic slip velocity and
- 23 friction along the fault plane were identified by the coda of the ultrasonic waves.
- 24 Additionally, ultrasonic amplitudes show precursory signals to laboratory fault reactivation.
- 25 Our results show that small and local variations in stress before fault failure can be inferred
- using coda wave interferometry for time-lapse monitoring, as coda waves are more sensitive
- to small perturbations in a medium than direct waves. Hence, these signals can be used as
- 28 precursors to laboratory fault slip and to give insight into reactivation mechanisms. Our
- results show that time-lapse monitoring of coda waves can be used to monitor local stress
- 30 changes associated with fault reactivation in this laboratory setting of fluid-induced fault
- reactivation. This is a critical first step towards a method for continuous monitoring of natural
- fault zones, contributing to seismic risk mitigation of induced and natural earthquakes.

33 Plain Language Summary

Activities underground, such as gas extraction or fluid injection, can disturb the natural 34 stresses present and cause human-induced earthquakes along pre-existing faults. Even though 35 they are related to engineering, these earthquakes are currently unpredictable. Monitoring and 36 understanding how these earthquakes occur are essential to progress with mitigation 37 measures and earthquake forecasting. Here, we inject fluid to reactivate faulted sandstone 38 samples in the laboratory, while monitoring what happens with ultrasonic waves that are 39 40 being sent continuously through the faulted sample as we attempt to create a laboratory earthquake. We show that by detecting small changes in these ultrasonic waves we can 41 identify the stages of fault movement, including precursors, in these simplified laboratory 42 43 fault zones. This implies that similar signals can potentially be used as precursors to fault movement in other settings as well, which is a critical first step towards a method for 44 monitoring of the subsurface in real life, contributing towards a method of seismic risk 45 mitigation of induced and natural earthquakes. 46

47 **1 Introduction**

Forecasting earthquakes has received much interest for many years. Increasing human 48 activities in the subsurface have caused substantial earthquakes in more densely populated 49 areas (e.g., M3.4 Basel (2006), Switzerland, M3.6 Groningen, the Netherlands (2012), and 50 M5.4 Pohang, South Korea (2017)), with serious consequences for subsurface use, halting a 51 52 geothermal project in Basel, and onshore gas production in Groningen. Thus, effective subsurface monitoring and seismic forecasting are essential to limit the risk and mitigate 53 seismic hazards. In general, the common mechanisms occurring during the seismic cycle are 54 well known (Figure 1)(Shreedharan et al., 2021a). This involves initial stress build-up during 55 the inter-seismic phase, during which the fault experiences creep, and fault healing. In the 56 pre-seismic phase the first slip instabilities nucleate there where the local stress exceeds the 57 fault strength. This accelerates creep until a seismic event is generated in the co-seismic 58 reactivation phase, during which a large slip event takes place rapidly and stress on the fault 59 is released. In the post-seismic phase, the system will experience creep and renewed fault 60 61 healing. Currently, natural earthquake predictions are made using reoccurrence intervals of

the seismic cycle, i.e. the average duration of the post-seismic phase (Shimazaki & Nakata, 62 1980), or using the precursor events during the pre-seismic phase, such as the average 63 earthquake size distribution (b-value) (Gulia et al., 2020). For induced seismicity specifically, 64 forecasting can be done using probabilistic models (Király-Proag et al., 2016; Langenbruch et 65 al., 2018), which can include various production scenarios (Dempsey & Suckale, 2017). In 66 laboratory settings, frictional sliding experimental studies have been performed using passive 67 acoustic monitoring (Cartwright-Taylor et al., 2022; Guglielmi et al., 2015; Noël et al., 2019; 68 Ye & Ghassemi, 2020), mostly to investigate fault mechanics and often to target the onset of 69 the first small and precursory slip events of the pre-seismic phase. However, robust, and 70 reliable predicting of fault failure and the resulting earthquake has proven to be a challenging 71 72 task (Geller, 1997; Pritchard et al., 2020), even for experimental faults under controlled

⁷³ laboratory settings (Main & Meredith, 1989).

Pore fluid pressure changes play an important role in the frictional strength and 74 stability of faults and are considered the main trigger for induced seismicity in several real 75 world applications such as hydrocarbon extraction or geothermal energy production 76 (Guglielmi et al., 2015; Kaproth & Marone, 2013a; Stanchits et al., 2011; L. Wang et al., 77 2020). In contrast to the natural seismic cycle, in these cases instabilities are created locally 78 due to the local pore pressure variations. These cause perturbations in stress magnitude along 79 the fault. Consequently, the pre-seismic phase can arise when the shear strength of the fault 80 plane is exceeded, which then ultimately results in fast shear slip along pre-existing faults and 81 fractures (L. Wang et al., 2020), i.e. the seismic phase in Figure 1. To date, few studies focus 82 83 on predicting fluid-induced seismicity specifically, and hence, predicting the extent of these pore pressure-induced stress changes, and therefore the potential onset and exact location of 84 failure and seismicity remains very challenging. 85

Generally speaking, stress changes can be inferred by analyzing the change in 86 acoustic or seismic velocity (Cartwright-Taylor et al., 2022; Xie et al., 2018). For intact 87 88 rocks, it has been shown that seismic velocities change in response to stress, for example, due 89 to compression of the rocks (Barnhoorn et al., 2018; Winkler & Nur, 1979). In particular, it has been shown that the coda of the acoustic wave traveling through the medium is 90 91 exceptionally sensitive to changes in the microstructure (Snieder et al., 2002; Stähler et al., 2011; Zhang et al., 2012; Zotz-Wilson et al., 2019), where the use of coda wave 92 93 interferometry can predict the onset of failure before the stress drops in intact rock loaded 94 under a constant rate. However, only a very limited number of laboratory fault sliding studies included continuous active ultrasonic monitoring (Kaproth & Marone, 2013a; Passelègue et 95 al., 2018; Shreedharan et al., 2019, 2020, 2021a; Veltmeijer et al., 2023a). Moreover, these 96 97 studies focused only on the elastic wave velocity and changes in amplitude for sliding on smooth faults. Results show precursory changes in elastic wave velocity (Kaproth & Marone, 98 2013b; Passelègue et al., 2018; Veltmeijer et al., 2023a) and amplitude (Shreedharan et al., 99 2019, 2020, 2021a; Veltmeijer et al., 2022) during the pre-seismic phase of fault reactivation 100 (Figure 1). However, the relations between these changes in the elastic wave properties and 101 the mechanisms of precursors to failure remain poorly understood. Moreover, it is unknown 102 if monitoring techniques based on arrival time and amplitude would still work for complex, 103 104 rough fault surfaces, which can be considered more representative of natural fault zones (Frank et al., 2020). Given the success of coda wave interferometry on predicting oncoming 105 failure in intact rocks, we also test the possibilities of coda wave interferometry for 106 monitoring the laboratory seismic cycle with different fluid injection protocols in smooth and 107 rough faults. 108

109 This paper aims to monitor slip by identifying precursors from the temporal evolution 110 of ultrasonic seismic waves and to understand the connection between precursors and

- mechanisms of failure. We present the results of injection-driven reactivation of fault
- 112 experiments in combination with continuous active ultrasonic monitoring. Fluid pressure was
- increased cyclically and stepwise to induce slip on the critically stressed saw-cut and in-situ
- 114 faulted permeable Red-Felser sandstones.



115

Figure 1: Cartoon of fault movement and the corresponding laboratory seismic/ fault reactivation stages. Fault instability and movement occur when the shear stress τ is larger than the shear strength τ_s .

119

120 2 Materials and Methods

121 2.1 Rock samples

Red Felser sandstones were used in the experiments. These sandstones originate from the Rotliegend formation, which is the same formation as the Groningen reservoir sandstones, and are obtained from a quarry near Kaiserslautern, in Germany (Naderloo et al., 2023; van Uijlen, 2013). The rock properties, specifically lithology, porosity, and permeability, of the Red Felser are very similar to the Slochteren sandstone (Eradus, 2019). The intact rock samples have a porosity of $21.4\% \pm 0.7\%$ and were 30+/-0.1 mm in diameter and 70+/-0.1mm in length.

129 2.2 Experimental protocol

The experiments were conducted using a Hoek-cell, a triaxial apparatus (Figure 2) 130 which is placed in an in-house built uniaxial loading frame with a 500 kN loadcell. Confining 131 pressure and pore fluid pressure were maintained using an ISCO pump model 100DM. Fluid 132 pressure was imposed at the bottom of the sample but was measured at the top and bottom of 133 the sample. The difference in fluid pressure between top and bottom was within ± 0.2 MPa. 134 We recorded the shortening of the sample using two Solartron AX/1/S linear variable 135 displacement transducers (LVDTs) with a \pm -0.1 µm precision. All displacement data was 136 corrected for elastic machine and piston deformation afterward. 137

Four types of experiments were performed using two fluid injection protocols, namely stepwise and cyclic fluid injection, on smooth and rough faulted samples. By performing multiple repeat tests for the different configurations, the consistency of the acoustic responses has been confirmed. The first sample type has a smooth saw-cut fault, cut at an angle of 35 degrees to the vertical axis (i.e., similar to Ye & Ghassemi, 2020). The tips of the saw-cut plane were slightly rounded to prevent breaking of the edges, resulting in an approximately elliptical fault surface of 45mm \pm 0.7mm in length and 29.6mm \pm 0.1mm in width (Figure 145 3a). The second sample type has a rough fault created in-situ in the laboratory assembly,

- 146 which is assumed to be more representative of natural rough faults. Prior to testing, all
- samples were vacuum-saturated with tap water. For the sample with a rough fault, prior to
- injection, we fractured an intact sample at 10 MPa confining and 5 MPa fluid pressure. After
 the fracture was formed, loading of the sample was continued in displacement control for 2
- the fracture was formed, loading of the sample was continued in displacement control for 2 min to eliminate cohesive strength and to slightly open the fracture, to promote slip along the
- 151 created fracture during the injection stage of the experiment. After creating the rough fault,
- the experiment proceeded with the same loading and injection protocol as the saw-cut fault
- samples (Figure 2).

Before the fluid injection protocols starts, all faulted samples were stressed to a 154 confining pressure of 33 MPa and 5 MPa fluid pressure. Note that the confining pressure (σ 3 155 $= \sigma^2$) was held constant during the entire experiment. Then the sample was loaded with a 156 constant vertical strain rate of 0.0005s⁻¹ until the stress-strain curve starts to deviate from 157 linearity (the start of fault reactivation), and reaching a critical stressed condition of the shear 158 stress (τ) (L. Wang et al., 2020; Ye & Ghassemi, 2020)). Here the position of the axial 159 loading press was fixed and held constant. After 10 minutes waiting time, to allow the 160 settling of the sample and assembly, the fluid injection started. 161

In the first protocol, the stepwise injection (A in Figure 2), the fluid pressure was increased stepwise by 5 MPa at a rate of 2 MPa/min with 5 min of waiting time in between each step until the maximum pressure of 28 MPa was reached. In the second protocol, the cyclic injection (B in Figure 2), the fluid pressure was returned to the initial pressure of 5 MPa after each increasing step (5 MPa above the previous pressure) of the fluid pressure, and using the same rate of 2 MPa /min but with 3 min waiting time in between each cycle. The fluid pressure was cyclically increased to the same maximum of 28 MPa.

After finishing the experiment, the sample with the created rough fault was removed
 from the Hoek-cell and scanned in a Nanotom NF180 microCT scanner with a resolution of
 (voxel size) 64 μm and processed using Avizo © software.

Active ultrasonic seismic monitoring was performed on all experiments, 172 simultaneously with the mechanical data acquisition. The waveforms were generated by an 173 Agilent 33210A waveform generator, amplified by an RF Power amplifier, sent and received 174 175 using Olympus 1MHz/.5" v153 transducers, and finally recorded using a Yokogawa DL9240L oscilloscope. The transducers are integrated into the pistons of the loading system. 176 Two S-wave transducers were used, with the source at the top and the receiver at the bottom 177 178 of the samples. The transducers were placed such that the polarization of the shear source and receiver was aligned. The peak operating frequency of the S-wave transducers is 1 MHz and 179 the ultrasonic signals were recorded every 3 seconds for 100 µs. To increase the signal-to-180 noise ratio, every recorded waveform is a stack of 256 S-waves, each sent 4 ms apart (Figure 181 4a). 182





Figure 2: Left: Scheme of Hoek-cell used for triaxial experiments (not to scale). 184 Right: scheme of loading and injection protocol for the saw-cut (top) and fractured (bottom) 185 samples. In both cases, protocol A shows stepwise injection and protocol B cyclic injection. 186 The loading plate is fixed during injection, hence the axial stress is allowed to drop during 187 fault reactivation due to fluid injection. 188

2.3 Data Analysis 189

with

During the experiment, signals were logged for force (N), confining pressure (bar), 190 displacement (μ m), pore fluid pressure (bar), wave arrival time (s), and amplitude (volt). The 191 shear stress (τ), friction coefficient (μ), and effective normal stress (σ_n) along the fault plane 192 193 are determined using the principal stresses, $\sigma 1$ and $\sigma 2 = \sigma 3$, derived from the force and confining pressure data respectively, and the fluid pressure (P_f) as given by 194

$$\mu = \frac{\tau}{\sigma_n - P_f},$$

(1)

197

198
$$\tau = \frac{\sigma_1 - \sigma_3}{2} \sin(2\alpha),$$
199 (2)

199

201

202

196

200 and

$$\sigma_n = \frac{\sigma_1 + \sigma_3 - 2P_f}{2} - \frac{\sigma_1 - \sigma_3}{2} \cos(2\alpha), \tag{3}$$

where σ_1 and σ_3 are the axial and radial stress respectively and α is the fault angle 203 with respect to the vertical (Byerlee, 1967; L. Wang et al., 2020). The τ and σ_n are corrected 204 for a changing contact area of the fault due to fault slip. The fault slip (s) is determined from 205 the total axial displacement (ΔI_{LVDT}), corrected for the displacement of the loading machine 206 (Δl_{MD}) and the rock matrix (Δl_{RM}) (L. Wang et al., 2020), as follows: 207

208
$$s = \frac{\Delta l_{LVDT} - \Delta l_{MD} - \Delta l_{RM}}{\cos(\alpha)}.$$
209 (4)

209

The displacement of the loading machine (Δl_{MD}) and the rock matrix (Δl_{RM}) can be 210 estimated using the stiffness of the machine (K_M) and rock matrix (K_{rock}) , and the force drop 211 (F_N) , rewriting Equation (4) into: 212

213
$$s = \frac{\Delta l_{LVDT} - \frac{F_N}{K_M} - \frac{F_N}{K_{rock}}}{\cos(\alpha)}.$$

214

For the stiffness of the machine and that of the rock matrix we performed a series of 215 calibration experiments using aluminium reference samples and intact rock samples. The 216 recorded waveforms are analysed using the maximum transmitted amplitude of the recorded 217 P- or S-wave as transmissivity $T = |A_{max}|$ (Shreedharan et al., 2020). In addition to the 218 219 arriving amplitudes, coda wave interferometry (CWI) is used to monitor velocity change between two recorded waves. The theory of CWI as presented by Snieder (2002) states that 220 the unperturbed wavefield $u_{\mu}(t)$ can be written as a sum of all possible paths (p) the waves 221 can travel through the medium, where t is time and $A_p(t)$ is the wave along travel path P: 222

(5)

(7)

223
$$u_u(t) = \sum_P A_p(t).$$
224 (6)

Each scatterer in the medium is assumed to have stationary properties. Therefore, the 225 scatterer does not change its size, shape, density, and velocity. Additionally, the distance 226 between the individual scatterers is assumed to be much larger than the dominant wavelength 227 $(l \gg \lambda)$. The major difference between the wavefields, when the medium changes over time, 228 is the arrival times of the waves propagating along each travel path p. The perturbed 229 wavefield can thus be represented as 230

 $u_n(t) = \sum_P A_n(t - \delta t_n),$

- 231
- 232

where δt_p is the travel time change along the path P. This implies that the perturbed 233 wavefield shows only a change in time and does not change the dispersion of the wavefield. 234 By comparing the wave fields the variations in the medium can be assessed. The cross-235 correlation coefficient is a common method to quantify these variations. The cross-correlation 236 coefficient (CC) for a time window of width $2t_w$ and centered around time t_k is given by 237

238
238

$$CC(t_{s}) = \frac{\int_{t_{k}-t_{W}}^{t_{k}+t_{W}} u_{u}(t)u_{p}(t+t_{s})dt}{\sqrt{\int_{t_{k}-t_{W}}^{t_{k}+t_{W}} u_{u}^{2}(t)dt \int_{t_{k}-t_{W}}^{t_{k}+t_{W}} u_{p}^{2}(t)dt}}.$$
239
(8)

The cross-correlation coefficient (CC) reaches its maximum if the travel time 240 perturbation δt across all possible perturbed paths P is 241

$$\delta t = t_s. \tag{9}$$

The velocity change can be written as the average slope of δt versus t, assuming the 244 time shift is constant in the considered time window, as follows: 245

(10)

$$\frac{\delta v}{v} = \frac{\delta t}{t} \,.$$

247

To investigate the changes in material scattering, the decorrelation coefficient (K) is determined. The method of coda wave decorrelation (CWD) introduced by Larose et al. (2010) is based on the theory of Snieder (2006). The decorrelation coefficient is formulated as

252
$$K(t_s) = 1 - CC(t_s) = 1 - \frac{\int_{t_k - t_w}^{t_k + t_w} u_{p_j - N}(t) u_{p_j}(t + t_s) dt}{\sqrt{\int_{t_k - t_w}^{t_k + t_w} u_{p_j - N}^2(t) dt \int_{t_k - t_w}^{t_k + t_w} u_{p_j}^2(t) dt}},$$
(11)

253

where N is the number of measurements the reference wavefield $u_{p_i-N}(t)$ is lagging 254 behind the to-be-correlated wavefield $u_{p_i}(t)$ (Figure 4b). For continuously monitoring the 255 evolving scattering medium, a moving reference wavefield is used (c.f. Grêt et al., 2006; 256 Zotz-Wilson et al., 2019). The decorrelation coefficient K is related to the changes in material 257 scattering due to the addition or removal of scatter(ers) in the medium (Planès et al., 2014, 258 2015). The coda waves seem random due to the complex paths they take through the 259 medium, but the changes they are subjected to are strongly related to the position and strength 260 of the changes in the medium (Planès et al., 2014). The scattering in a medium along the 261 transport mean free path l can be described using the cross-sectional area of a single scatterer 262 σ and the density of scatterers ρ (Planès et al., 2014). The total scattering coefficient, as 263 described by Aki and Chouet (1975), is given by 264

265
$$g_0 = \rho \sigma = l^{-1}$$
. (12)

Following the theory of Aki and Chouet (1975), we can rewrite the coda decorrelation in terms of the scattering coefficient (g_0) between a perturbed (p) and unperturbed (u)medium (Zotz-wilson et al., 2020).

270
$$K(t) = \frac{v_0}{2} t \left| \Delta g_{0p-u} \right|,$$
271 (13)

where K(t) is the theoretical decorrelation coefficient, t the time in the coda, and v_0 the velocity in the medium. Using a rolling reference (N=1), the changes in the absolute value of $|g_0|$ are monitored as a rate of change (e.g., Zotz-Wilson et al., 2020).



275

Figure 3: Pictures of (dried) samples before (a) and after the experiment was finished (b and c). Note that the tips of the saw-cut are ground off <3 mm, but the overall shape is still elliptical, with dimensions [45mm ± 0.7mm / 29.6mm ± 0.1mm]. The middle (b) shows a sample after stepwise injection and the right (c) after cyclic injection. The formed gouge is

visible as the patchy whitish powder on the saw-cut fault surface. The patterns of final gouge

distribution were different after each experiment, without any relationship to experimental

282 parameters.



283

Figure 4: Example of a recorded waveform (a) showing the arrival time of the P-wave (t_P) and of the S-wave (t_S) as well as the maximum transmitted amplitude of the S-waves. The length of the coda is indicated by the box and starts at t = 1.5 t_S . Part of the coda is enlarged in (b) to illustrate the shift in the coda over time, showing the to-be-correlated wavefield $u_{p_i}(t)$

and the reference wavefield $u_{p_i-N}(t)$ with N = 1 and 20.

289

290 **3 Results**



291 292

Figure 5: Evolution of mechanical and acoustic parameters during the reactivation of the saw-cut samples. a and b show the results of the stepwise injection experiment. c and d show the results of the cyclic injection experiment. a and c show the evolution of the shear stress τ , friction coefficient μ , and slip velocity along the fault due to increasing pore pressure. b and d show the derivative transmissivity T and the evolution of coda wave parameters K and dv/v. Slip event shaded in grey zoomed view visible in Figure 6.







Figure 6: Zoom of single slip events (shaded grey in Figure 5) a and b showing the evolution of mechanical and acoustic parameters during the reactivation of the saw-cut 301 samples of the second slip event induced by stepwise injection experiment and c and d the 302 second slip event induced by cyclic injection experiment. The shaded grey around the 303 decorrelation coefficient K shows the standard deviation and the coloured shaded areas in 304 figures a to d indicate the four stages of fault reactivation green: inter-seismic stage, yellow: 305 pre-seismic stage, red: co-seismic stage, and blue: post-co-seismic stage. 306

3.1 Fault Slip Behaviour 307

From the principle stresses, increasing fluid pressures, and area of the fault plane, the 308 evolution of friction coefficient u is estimated for the saw-cut samples (Eq.1, Figure 5 a, c, 309 Figure 6a, c). It is assumed that the whole fault plane accommodates slip in each event (see a 310 zoomed view of a single step in Figure 6a, c). As μ increases during fluid pressurization, 311 frictional strengthening is visible for the two different injection patterns (shaded green in 312 Figure 6). At the onset of fault reactivation, u deviates from linearity (start of vellow shaded 313 area in Figure 6) and drops (shaded red in Figure 6), simultaneously with the shear stress, 314 when the fault slips. During each slip event (red shaded areas in Figure 6 and Figure 8), the 315 316 slip velocity rapidly accelerates to a maximum sliding velocity. Stick-slip events with peak slip velocities below 1 mm/s are defined as slow stick-slip events (L. Wang et al., 2020). The 317 maximum slip velocities observed are $<6.5 \mu m/s$, therefore all recorded slip events in these 318 experiments are slow stick-slip. After reactivation of the fault, μ continues to increase with 319 continued fluid pressurization (shaded blue in Figure 6). During this stage, μ is not affected 320 by fault slip, as the fault continues to slip with low background velocities of $\approx 0.8 \,\mu\text{m/s}$. At 321

the end of each injection step, a gradual drop of μ indicates sample relaxation. During the rest in between injection periods, the slip velocity drops to creep velocities near zero (<0.1*10⁻³ um/s), until a new injection stage starts.

In general, the rough fault exhibits very similar behaviour during cyclic injection (Figure 3 c, d, and Figure 4 c, d). However, during cyclic injection, the slip events show larger and more abrupt drops in τ , μ , and peaks in slip velocity. But after the slow stick-slip event, similar low background velocities of $\approx 0.8 \mu m/s$ are recorded, and in between injection events the rates drop to near zero as well.





Figure 7: Evolution of mechanical and acoustic parameters during the reactivation of fractured samples, or rough fault. a and b show the results of the stepwise injection experiment. c and d show the results of the cyclic injection experiment. a and c show the evolution of the shear stress τ , friction coefficient μ , and slip velocity along the fault due to increasing pore pressure. b and d the derivative transmissivity T and the evolution of coda wave parameters K and dv/v. The slip event is shaded in grey, zoomed view visible in Figure 8.

338





Figure 8: Zoom of single slip events (shaded grey in Figure 7). a and b showing the evolution of mechanical and acoustic parameters during the reactivation of fractured samples, or rough fault of the second slip event induced by stepwise injection experiment and c and d the second slip event induced by cyclic injection experiment. The shaded grey around the decorrelation coefficient K shows the standard deviation and the coloured shaded areas in figures a to d indicate the four stages of fault reactivation green: inter-seismic stage, yellow: pre-seismic stage, red: co-seismic stage.

The exact area of slip in the rough fault and how it changes during slip is unknown, 347 therefore the evolution of the friction coefficient on the rough fault can't be estimated. 348 349 However, using the evolution of shear stress and displacement, we can still observe the following. Slow slip is observed along the fault plane with peak velocities well below the 350 velocities observed for slip on a saw-cut fault (Figure 9). After the slow slip event 351 reactivation (shaded red in Figure 8), sample relaxation causes the slip velocity to drop to 352 creep velocities near zero ($<0.1*10^{-3}$ µm/s) until a new injection stage starts, similar to the 353 saw-cut faults (Figure 8). Also on rough faults, the slip velocities are again higher for cyclic 354 than for step-wise injection, however, the difference is less substantial than observed for slip 355 along the saw-cut fault (Figure 9). During the last stepwise injection step a large stress drop 356 occurred, and when taking the sample out it had an additional fracture. Therefore, the last 357 358 step of the stepwise injection needs to be disregarded in the fault slip analysis.





Figure 9: Peak slip velocity for each injection (stepwise and cyclic) step for the sawcut (SC) and fractured (F) samples. The co-seismic phase for the rough fault (fractured samples) is more prolonged, the markers show the potential start of the co-seismic phase whereas in the SC samples the peak in velocity coincides with the co-seismic phase.

364





Figure 10: Showing the relation between the principal stresses on the fault plane 'colour coded' by the applied pore pressure; a) for the saw-cut stepwise injection experiment; b) for the saw-cut stepwise cyclic experiment; c-d; for the fractured samples stepwise and cyclic injection protocol respectively. Indicative failure envelopes are drawn for failure planes with friction coefficient μ is 0.8 or 1 and cohesion c is 0 or 7.

371 3.2. (Micro-) Structural Observations

The fault plane of samples shows damage after the reactivation experiments. Most of the gouge forms during fault slip, due to shear slip, significant grain size reduction took place, resulting in fault gouge formation (Figure 3). During sliding, the quartz grains at the surface are crushed, and the resulting gault gouge coats the fault plane upon post-experimental sample retrieval.

In the sawcut experiments, the contact of the fault plane can be considered smooth and a single contact in macro-scale. On the micro-scale, however, each single grain contact acts as an asperity. This is also shown by the gouge which is distributed heterogeneously on the fault surface, suggesting that even the relatively smooth surface of the saw-cut still has heterogeneous frictional properties across the fault (Figure 3). Each experiment comes out with its own distinct pattern of gouge distribution, without obvious correlation to the experimental parameters.

After finishing the experiment with a rough fault experiments, a CT image (Figure 11) was made to shows slices of the fault plane after finishing the experiment. Along the fault plane, black areas are visible, indicating open pore space. There are also intermediately shaded grey areas, where the fault plane is harder to track. Image segmentation by simple thresholding shows the approximate 3D view of the fault plane. It shows a very irregular fault surface

(Figure 12c), which form a stark contrast to the simple and straight saw-cut planes.

390

391 3.3. Ultrasonic Monitoring

We first describe the results of the saw-cut experiments. Monitoring the evolving the 392 transmissivity T, a measure of the transmitted amplitude, was used by Nagata et al. (2008) 393 394 and Shreedharan et al. (2021) before to track fault properties in direct shear experimental setting, without considering the effects of pore pressure. It is known that pore pressure has a 395 large effect on wave energy (Winkler & Nur, 1979). This is also observed in this set of 396 397 experiments, in which was observed that transmitted amplitudes decrease and increase inversely with pore pressure. To investigate the more subtle changes due to fault reactivation, 398 the derivative of T is plotted (Figure 5b, d, Figure 6b, d). This shows that during fault slip 399 there is an accelerated drop in the transmitted amplitude. During each slip event the sample is 400 shortened, decreasing the direct travel path of the wave, which should increase the amplitude. 401 However, the transmissivity decreases with each injection step instead, and exhibits a faster 402 403 rate during slip. We observed gouge formation during experiments with slip. Theoretically, thicker gouge layer should attenuate waveforms travelling through the sample more than a 404 thinner gouge layer. Given that the transmissivity still shows a decrease during cyclic 405 injection, even while the pore pressure was returned to the initial pressure and including the 406 shortening of the sample due to slip, we infer this decrease to be due to additional attenuation 407 by ongoing gouge formation. 408

The small stress variations along the fault plane are interpreted and assessed by 409 comparing the coda of the recorded wave fields, where a moving reference wavefield was 410 used $(t_{N-1} - t_N)$. Therefore the decorrelation coefficient K and velocity change dv/v are 411 monitored as a rate of change. Coda wave parameters K and dv/v respond to fluid injection, 412 and increase and decrease in conjunction with the injection pattern, showing their sensitivity 413 to stress perturbation on the sample scale (Figure 5b and d, Figure 6b, d). Within this 414 background response to the change in sample stress during injection, another trend is visible. 415 The evolution of coda wave parameters K and dv/v show a strong correlation to the slip 416 velocity, with an accelerating increase before slip (yellow shaded areas in Figure 6), an 417

d18 obvious peak during slip (red shaded areas in Figure 6), and a reduction to background levels d19 at moments of relaxation. The magnitude of these peaks increases per cycle (Figure 5b, d) d20 similar to the slip velocity (Figure 5a, c). This indicates that dv/v and K are indeed sensitive d21 to the slip velocity along the saw-cut fault plane. As fault slip is a result of stress changes and d22 the resulting loss of asperity contact along the fault plane, we infer the changes in dv/v and K d23 are results of changes in fault contact on the microscale. T shows a similar trend to dv/v showing an equivalent sensitivity to the stress changes along a saw-cut fault.

Moving to the more complex situation of the rough fault, we observe that for the 425 rough fault, the T pattern changes per slip event (Figure 7b, d). Rather than decreasing 426 amplitudes prior to slip (Figure 6b, d), increasing amplitudes in the transmitted waves are 427 observed during and just before slipping along the rough fault (Figure 7b, d). A similar 428 observation can be made for coda parameter K (Figure 7b, d and Figure 8b, d). The 429 scattering along the more uneven slip along the rough fault causes an incoherent signal from 430 the decorrelation coefficient K (Figure 7b, d). While the general sample scale pattern of fluid 431 injection is still visible (Figure 7d), the more subtle trend with accelerated increase during 432 fault reactivation (observed in the saw-cut faults; shaded yellow in Figure 6b, d) is lost by the 433 more complicated slip along the rough fault plane (Figure 7b, d). Nonetheless, the velocity 434 change dv/v, however, is still showing the same trends with slip velocity (Figure 8a, c). This 435 suggests that the velocity change obtained by the coda wave, which sampled the fault, still is 436 a promising indicator for the pre-slip and slip phase along the rough fault plane (shaded 437 vellow and red respectively in Figure 8a, c). 438

439



440

Figure 11: CT sections cutting through the fault plane, showing the irregular shape of the rough fault plane. Arrows point at the black areas, which indicate areas of more pore space, hence opening of the fault, and to more greyish blurry areas, which show the interlocking and compaction areas along the fault. The red lines show the horizontal and vertical position of the slices. The movement along the fault plane is caused by downward sliding of the top half of the sample. The white arrows indicate areas of compaction (a and b) and areas of opening (d and e). The direction of movement is indicated in c.



448

Figure 12: Image of the fault area, extracted from the CT images. This shows the
irregular shape of the rough fault plane, the gaps are stronger compaction areas of fault.
Which weren't picked up in processing of the fault area in the CT scans. C shows a jump in

the fault plane after an area of compaction.

453 4 Discussion

In the following, we will discuss the effect of injection pattern on fault reactivation and
measured waveforms. Then we go on to discuss the difference of the effectiveness of
ultrasonic monitoring for smooth versus rough faults, where we presume that the type of
roughness created by the faulting procedure is more representative for in-situ roughness.
Following, we will discuss the added benefit is of using coda wave interferometry to
determine precursors to fault reactivation, and finally, we will discuss the implications of our
results for earthquake predictions.

461 4.1. Effect of Injection Pattern

By stepping or cycling the pore pressure, fault instability is reached multiple times. In 462 each cycle or step, when pore pressure stops increasing, we allow the system to re-stabilize 463 and reach a new equilibrium. By reducing the pore pressure each cycle, the fault plane can 464 relax and build strength caused by the compaction of the fault due to an increased effective 465 normal stress. (Figure 10). In cycles where pore pressure is reduced the fault compacts 466 further, and subsequently, more energy is needed to reactivate the fault. This corresponds to 467 an increase in the fault energy release, as observed by increasing slip velocities in cyclic 468 injection (Figure 9). 469

In the faulted samples, the grains on the fault surface are crushed during sliding and 470 pressuring of the fault, creating a gouge layer along the fault surface. This changes the fault 471 properties like the friction coefficient, which in the quartz-rich Red Felser sandstone, would 472 be expected to have a frictional strengthening effect (Bakker et al., 2016; He et al., 2013). We 473 474 do observe continuous restrengthening of the fault throughout the experiment (Figure 10). Most of the gouge is expected to form just prior to and during fault slip, when we expect to 475 have the highest local stresses on the asperities and movement, causing the observed grain 476 size reduction (Figure 3). Seismic waves are increasingly attenuated and scattered due to the 477 gouge formation and due to the changes in stress and movement and repositioning of the 478

479 scatterers along the fault. These changes were used as a precursor to fault reactivation during480 ultrasonic monitoring.

The peaks of decorrelation coefficient K, a proxy for the scattering coefficient (Eq. 481 12,13), during slip can be explained by an increased addition of scatterers, caused by the 482 fracturing, crushing and movement of the grains along the surface area of the fault plane 483 forming a progressively thicker gouge layer. The creation of this layer along with stress 484 release during slip also causes the drop in velocity dv/v, and the transmitted amplitude T 485 during fault reactivation. Both parameters peak during fault slip, afterward they are 486 fluctuating around a constant rate, similar to the observed constant slow slip (Figure 5b, d). 487 The slow stick-slip events induced by cyclic injection have a greater amplitude and are more 488 489 abrupt than for stepwise injection due to a greater release of fault energy (Figure 5b, d and Figure 6b, d). This results in larger amplitudes in the coda wave parameters K and dv/v, but 490 also fewer sampling points per slip event. 491

492 4.2. Effect of Roughness

The roughness of the fault plane illustrated by the CT image (Figure 11), implies the 493 fault plane has multiple areas of compaction (Figure 11a, b), where interlocking of asperities 494 can occur, and areas of opening (Figure 11d, e). During slip, parts of such a rough fault can 495 496 lock, and the fault will locally compact, whereas it will dilate locally there where the two halves move apart. Both phenomena could enhance resistance to shear along the fault by 497 interlocking asperities or dilatant hardening (Rudnicki & Chen, 1988). This increased 498 499 cohesion of the fault (Figure 10b, d) and resistance to shear result in more prolonged slow slip (Figure 8a, c) upon reactivation until the fluid injection is stopped in which we observe 500 fluctuating slip velocities, suggesting the overcoming the interface locking. In contrast, the 501 saw-cut fault is smooth and could therefore slip more easily in its entirety once fault 502 instability is reached. Accordingly, we observe higher slip velocities (Figure 9) upon 503 reactivation and a short and larger stress drop (Figure 6a, c), indicating short and fast 504 reactivation with afterward continuous slow slip phase due to continued elevated pore 505 pressure and reduced effective normal stress reducing the interface locking along the smooth 506 fault (Alghannam & Juanes, 2020). 507

The effect of compaction and dilation along the rough fault can be discerned in the 508 ultrasonic data. Compaction will cause increasing acoustic amplitudes, whereas dilation 509 causes more attenuation of the waves and lower transmissivity. This interpretation is 510 511 consistent with the systematic differences in the increasing and decreasing behaviour of T prior to fault reactivation (Figure 7b, d) of the rough fault. Where the decreasing behaviour of 512 T during fault reactivation of the smooth fault (Figure 5b,d) suggests the detection of dilation 513 514 along the fault plane, its increase suggest the detection of compaction. The scattering along the more uneven slip along the rough fault causes an more incoherent signal from the K 515 (Figure 7b, d). While the general pattern of fluid injection is still visible (Figure 7d), the more 516 subtle trend of fault reactivation is lost by the more complicated slip along the rough fault 517 plane (Figure 8b, d). Cartwright-Taylor et al., 2022 described crack rotation with antithetic 518 519 slip as an additional mechanism for local stress rotation and slip allowing shear along more unfavourably-orientated faults, which among fracturing and crushing of the grains influence 520 the scattering therefore causing a more incoherent K compared to sliding along the smooth 521 fault surface, where we won't expect this fault rotation and antithetic slip. 522

- 523 4.3. Precursors to fault reactivation
- 524 The direct shear experiments by Shreedharan et al. (2021) suggest a physical 525 connection between ultrasonic evolution (amplitude and direct wave velocity) and variations

526 in healing, pre-slip driven asperity changes, and shear stiffening of wallrock. Their results,

- similar to ours, suggested as well that the destruction of asperities and increase in fracture
 density due stress changes along the fault during and prior to fault slip is expected to result in
- density due stress changes along the fault during and prior to fault slip is expected to result i reduction in transmitted amplitude T and P-wave velocity. However, the work done by
- 530 Shreedharan et al. (2021) lacked the additional layer of complexity introduced by the
- 531 presence of pore pressure variations. Research by Passelègue et al., 2018, and Winkler &
- 532 Nur, 1979, indicates that ultrasonic amplitude and velocity are influenced by pore pressure. In
- this study and in Veltmeijer et al. (2022), we observe that pore pressure increases have a large
- effect on the transmitted amplitude, emphasizing the importance of considering relative
- changes in transmissivity to infer the nuance introduced by small variations in healing and
- 536 interface locking along the fault.
- The presented slip velocities can be categorized as slow slip (<6.5µm) or creeping velocities 537 $(<0.1*10^{-3}\mu m)$ (Figure 5 and Figure 7). These velocities are commonly thought to be 538 aseismic. However, experiments shown by Wang et al. (2020), Ye & Ghassemi (2020), and 539 Veltmeijer et al. (2023a) show recorded micro seismic events with similar slow slip 540 velocities. Hence, some seismic energy has been released, and we will characterize the fault 541 reactivation according to the fault reactivation stages (Figure 1) (Shreedharan et al., 2021a). 542 By analysing the temporal evolution of the coda waves, stress changes on the fault surface 543 can be identified, demonstrating the potential of coda waves to identify the stages of fault 544 reactivation: inter-seismic phase: linear stress build-up, the pre-seismic phase: early 545 creep/pre-slip, the co-seismic phase: stress drop and a continuous sliding phase for the saw 546 cut fault planes followed by a post-seismic phase at the end of injection: fault healing (i.e. 547 following the terminology and sequence shown in Figure 1). Our results show that we can 548 identify the pre-seismic phase of laboratory injection-induced fault slip. By zooming on a 549 550 single step or cycle, the K, dv/v, and T can be used to identify the different stages of reactivation. dv/v reaches a new equilibrium after the start of injection (Figure 6 and Figure 551 8), this can also be observed in the K and T for the reactivation of the saw-cut fault. The 552 linear stress build up along the fault causes a constant drop in velocity following the fluid 553 pressure identifying as the inter-seismic phase (green shaded area in Figure 6 and Figure 8). 554 Once the fault plane starts to become unstable in the pre-slip phase (yellow shaded area in 555 Figure 6 and Figure 8) the dv/v, K, and T show an accelerated decrease/increase in values 556 (Figure 6) peaking at the co-seismic stage (red shaded area in Figure 6 and Figure 8). These 557 early changes in values deviate from the change caused by increased pore pressure and are 558 hence a proxy of the stress change along the fault plane. Detecting the pre-slip phase could be 559 a first step for forecasting the upcoming fault reactivation as it is an indication of the 560 upcoming co-seismic slip phase. 561
- The drop in dv/v occurs over a narrow range, as well as the standard deviation 562 indicated in grey, hence it gives a fairly accurate indication of both the preparatory phase and 563 fault reactivation (Figure 6b). Due to the smooth fault, the stress release and fault reactivation 564 are rapid, and hence the preparatory phase is short. To reactivate the rough fracture, more 565 energy is needed, as some parts of the fracture aren't favourably oriented to move (Figure 566 11). During this extended preparatory phase, the drop in velocity remains clear and shows the 567 568 same pattern (Figure 6d), albeit more noisy one due to the more complex fault area. Using CWD, the scattering coefficient K, a proxy for grain crushing or movement, is determined. 569 This K clearly indicated the saw-cut fault reactivation, however, when the fault plane 570 becomes more complex, the K seems to be of little use in detecting both the preparatory 571 phase and fault reactivation (Figure 8c, d). A similar conclusion can be drawn from the 572 transmissivity. T in the rough fault initially showed similar patterns to the saw-cut fault 573 574 reactivation for the first injection step/cycle, but the later steps differ. Even though

575 monitoring of fault reactivation is more complex, and the signal is noisier for the rough fault, 576 using the dv/v, the pre-slip and co-seismic phase of fault reactivation can still be determined.

577 Due to the more prolonged pre-slip phase, the forecast of the co-seismic stage can be done

relatively earlier as higher differential stresses are needed to reactivate the rough fault.

After the co-seismic stage, post-slip sliding is observed in the saw-cut reactivated faults. As the fault remains prone to sliding due to continued fluid injection the fault plane continues to slowly slip until fluid injection ends (Figure 6). No post-slip during the injection is observed as the rough fault continues to slip slowly (Figure 8), rather than show a short and rapid co-seismic phase (as happened for the smooth fault). Once injection stops, the fault is not perturbed anymore, which signifies the start of post-seismic phase, during which the fault relaxes and can heal until the next step in the injection protocol starts.

586 4.4 Implications for induced seismicity

In our constrained laboratory setting, we accurately identified the pre-slip phase using 587 a combination of parameters, including transmitted amplitude, and CWI parameters, 588 highlighting that velocity changes obtained from coda offer more precision in complex 589 situations compared to the amplitudes. This suggests the potential inclusion of coda wave 590 interferometry in forecasting fault reactivation, presenting an improvement for input in 591 forecasting models. Efforts, including machine learning models, have been made to improve 592 predictions of lab quakes (Laurenti et al., 2022; Rouet-Leduc et al., 2017; K. Wang et al., 593 2022), also including transmitted amplitudes to the models (Shreedharan et al., 2021b). 594

595 Upscaling these findings to real reservoir remains a challenge, even though preseismic crustal velocity anomalies have been observed for a limited number of earthquakes 596 (Chiarabba et al., 2020; Niu et al., 2008). More work is needed to verify the usefulness of the 597 results for upscaled fault zone length, maturity, time, and complexity and extent of the 598 damage zone. From the engineering perspective it would require work on placement of 599 monitoring stations and monitoring frequency. Due to the fast nature of fault reactivation in 600 the laboratory, with pre- and co-seismic phases lasting seconds, monitoring points during the 601 pre-slip phase are limited due to equipment constraints. Nevertheless, assuming a one-to-one 602 relationship between the laboratory and field scale, we do see potential in this method for 603 monitoring fault reactivation. In the laboratory, the pre-slip phase spans only a few seconds, 604 equivalent to a 5 MPa increase in pore pressure (or a 5 MPa decrease in effective stress). 605 Extrapolating this to the field, a similar pore pressure change may take several days to weeks 606 or more to build up after which reactivation occurs. This potentially would allow more time 607 608 for measurements and forecasting. Our work is performed in a carefully constrained laboratory setting, and does not take in account temperature, maturity or forward prediction 609 of fault reactivation. We encourage future experimental research in these directions as well as 610 upscaling and field applicability. 611

612 **5 Conclusions**

In this paper, we aim to monitor fluid-induced fault slip in laboratory experiments more accurately and understand the connection between precursors and mechanisms of failure. By analysing the temporal evolution of the coda waves and seismic amplitudes, stress changes on the fault surface can be identified, demonstrating the potential of coda waves to identify the stages of fault reactivation as a possible basis for forecasting injection-induced fault-slip. The precursory signals obtained by coda wave interferometry and decorrelation are compared for both a smooth saw-cut and rough fault.

It is shown that the CWI velocity change is most sensitive to the pre-slip phase and fault reactivation. However, as all the compared attributes are obtained from the same

wavelet a combination of these properties shows that the stress changes along the fault can be 622 inferred with more accuracy. As a result, the combination may be useful for monitoring 623 faulted or critically stressed reservoirs that experience pore pressure changes. 624

The coda analysis and amplitudes are used to identify the different stages in the 625 laboratory seismic cycle, as precursors to fault slip and to give insight into reactivation 626 mechanisms. Showing ultrasonic monitoring techniques can be used to detect the different 627 fault reactivation stages: inter-seismic phase: linear stress build-up, the pre-seismic phase: 628 early creep/pre-slip, the co-seismic phase: stress drop and a continuous sliding phase for the 629 saw cut fault planes followed by a post-seismic phase at the end of injection: fault healing . 630

Our experiments demonstrate the feasibility of active ultrasonic monitoring as a tool 631 to identify precursors to laboratory fluid-induced earthquakes. While these experiments show 632 the feasibility of the active monitoring method in a controlled environment in the laboratory, 633 and its potential to infer the pre-seismic phase it does not yet include the forward forecasting. 634 The timing of the pre-phase, from detection to forward forecasting and the added complexity 635 from lab to field-scale should still be studied. The potential to infer aseismic stress changes 636 pointing toward seismicity from active ultrasonic campaigns could be of added value to 637 monitoring and forecasting (models). As a result, active techniques for monitoring and 638 predicting stress changes could improve the prediction of induced seismicity, which warrants 639 future studies. 640

641

Acknowledgments 642

This research was (partially) funded by NWO Science domain (NWO-ENW), project 643 DEEP.NL.2018.048. 644

645

Open Research 646

The laboratory facilities at TU Delft were used to perform the experiments and record 647 the data (loading data and waveforms) used in this publication. This data is accessible at the 648 4TU.ResearchData repository under a CC BY 4.0 licence. https://doi.org/10.4121/21557910 649 (Veltmeijer et al., 2023b). 650

651

References 652

- Aki, K., & Chouet, B. (1975). Origin of coda waves: Source, attenuation, and scattering 653
- effects. Journal of Geophysical Research, 80(23), 3322-3342. 654
- https://doi.org/10.1029/jb080i023p03322 655
- Alghannam, M., & Juanes, R. (2020). Understanding rate effects in injection-induced 656
- earthquakes. Nature Communications, 11(1), 1-6. https://doi.org/10.1038/s41467-020-657
- 16860-v 658
- Bakker, E., Hangx, S. J. T., Niemeijer, A. R., & Spiers, C. J. (2016). Frictional behaviour and 659
- transport properties of simulated fault gouges derived from a natural CO2 reservoir. 660

- 661 International Journal of Greenhouse Gas Control, 54, 70–83.
- 662 https://doi.org/10.1016/j.ijggc.2016.08.029
- Barnhoorn, A., Verheij, J., Frehner, M., Zhubayev, A., & Houben, M. (2018). Experimental
- identification of the transition from elasticity to inelasticity from ultrasonic attenuation
- analyses. *Geophysics*, 83(4), MR221–MR229. https://doi.org/10.1190/geo2017-0534.1
- ⁶⁶⁶ Byerlee, J. D. (1967). Frictional characteristics of granite under high confining pressure.
- *Journal of Geophysical Research*, 72(14), 3639–3648.
- 668 https://doi.org/10.1029/JZ072i014p03639
- 669 Cartwright-Taylor, A., Mangriotis, M. D., Main, I. G., Butler, I. B., Fusseis, F., Ling, M., et
- al. (2022). Seismic events miss important kinematically governed grain scale
- 671 mechanisms during shear failure of porous rock. *Nature Communications*, *13*(1).
- 672 https://doi.org/10.1038/s41467-022-33855-z
- 673 Chiarabba, C., De Gori, P., Segou, M., & Cattaneo, M. (2020). Seismic velocity precursors to
- 674 the 2016 Mw 6.5 Norcia (Italy) earthquake. *Geology*, 48(9), 924–928.
- 675 https://doi.org/10.1130/G47048.1
- Dempsey, D., & Suckale, J. (2017). Physics-based forecasting of induced seismicity at
- 677 Groningen gas field, the Netherlands. *Geophysical Research Letters*, 44(15), 7773–
- 678 7782. https://doi.org/10.1002/2017GL073878
- Eradus, D. (2019). Petrographical Description and Petrophysical Measurements on the Red
 Felser Sandstone. Delft University of Technology.
- Frank, S., Heinze, T., & Wohnlich, S. (2020). Comparison of surface roughness and transport
- 682 processes of sawed, split and natural sandstone fractures. *Water (Switzerland)*, 12(9).
- 683 https://doi.org/10.3390/w12092530
- 684 Geller, R. J. (1997). Earthquake prediction: a critical review. *Geophysical Journal*
- 685 *International*, *131*(3), 425–450. https://doi.org/10.1111/j.1365-246x.1997.tb06588.x

- 686 Grêt, A., Snieder, R., & Scales, J. (2006). Time-lapse monitoring of rock properties with coda
- 687 wave interferometry. *Journal of Geophysical Research: Solid Earth*, 111(3), 1–11.

688 https://doi.org/10.1029/2004JB003354

- 689 Guglielmi, Y., Cappa, F., Avouac, J. P., Henry, P., & Elsworth, D. (2015). Seismicity
- triggered by fluid injection-induced aseismic slip. *Science*, *348*(6240), 1224–1226.
- 691 https://doi.org/10.1126/science.aab0476
- 692 Gulia, L., Wiemer, S., & Vannucci, G. (2020). Pseudoprospective evaluation of the foreshock
- 693 traffic-light system in ridgecrest and implications for aftershock hazard assessment.
- 694 Seismological Research Letters, 91(5), 2828–2842. https://doi.org/10.1785/0220190307
- 695 He, C., Luo, L., Hao, Q. M., & Zhou, Y. (2013). Velocity-weakening behavior of plagioclase
- and pyroxene gouges and stabilizing effect of small amounts of quartz under
- 697 hydrothermal conditions. Journal of Geophysical Research: Solid Earth, 118(7), 3408–
- 698 3430. https://doi.org/10.1002/jgrb.50280
- 699 Kaproth, B. M., & Marone, C. (2013a). Slow earthquakes, preseismic velocity changes, and
- the origin of slow frictional stick-slip. *Science*, *341*(6151), 1229–1232.
- 701 https://doi.org/10.1126/science.1239577
- 702 Kaproth, B. M., & Marone, C. (2013b). Slow Earthquakes, Preseismic Velocity Changes, and
- the Origin of Slow Frictional Stick-Slip. *Science*, *341*(6151), 1229–1232.
- 704 https://doi.org/10.1126/science.1239577
- Király-Proag, E., Zechar, J. D., Gischig, V., Wiemer, S., Karvounis, D., & Doetsch, J. (2016).
- Validating induced seismicity forecast models—Induced Seismicity Test Bench. *Journal*
- 707 of Geophysical Research: Solid Earth, 121(8), 6009–6029.
- 708 https://doi.org/10.1002/2016JB013236
- Langenbruch, C., Weingarten, M., & Zoback, M. D. (2018). Physics-based forecasting of
- man-made earthquake hazards in Oklahoma and Kansas. *Nature Communications*, 9(1),

- 711 1–10. https://doi.org/10.1038/s41467-018-06167-4
- Larose, E., Planes, T., Rossetto, V., & Margerin, L. (2010). Locating a small change in a
- 713 multiple scattering environment. *Applied Physics Letters*, 96(20), 1–4.
- 714 https://doi.org/10.1063/1.3431269
- Laurenti, L., Tinti, E., Galasso, F., Franco, L., & Marone, C. (2022). Deep learning for
- ⁷¹⁶ laboratory earthquake prediction and autoregressive forecasting of fault zone stress.
- *Earth and Planetary Science Letters*, 598, 117825.
- 718 https://doi.org/10.1016/j.epsl.2022.117825
- 719 Main, I. G., & Meredith, P. G. (1989). Classification of earthquake precursors from a fracture
- 720 mechanics model. *Tectonophysics*, *167*(2–4), 273–283. https://doi.org/10.1016/0040-
- 721 1951(89)90078-4
- Naderloo, M., Kumar, K. R., Hernandez, E., Hajibeygi, H., & Barnhoorn, A. (2023).
- Experimental and numerical investigation of sandstone deformation under cycling
- 124 loading relevant for underground energy storage. *Journal of Energy Storage*,
- 725 64(February), 107198. https://doi.org/10.1016/j.est.2023.107198
- Niu, F., Silver, P. G., Daley, T. M., Cheng, X., & Majer, E. L. (2008). Preseismic velocity
- changes observed from active source monitoring at the Parkfield SAFOD drill site.
- 728 *Nature*, 454(7201), 204–208. https://doi.org/10.1038/nature07111
- Noël, C., Passelègue, F. X., Giorgetti, C., & Violay, M. (2019). Fault Reactivation During
- 730 Fluid Pressure Oscillations: Transition From Stable to Unstable Slip. *Journal of*
- 731 *Geophysical Research: Solid Earth*, *124*(11), 10940–10953.
- 732 https://doi.org/10.1029/2018JB016045
- 733 Passelègue, F. X., Brantut, N., & Mitchell, T. M. (2018). Fault Reactivation by Fluid
- 734 Injection: Controls From Stress State and Injection Rate. *Geophysical Research Letters*,
- 735 45(23), 12,837-12,846. https://doi.org/10.1029/2018GL080470

- 736 Planès, T., Larose, E., Margerin, L., Rossetto, V., & Sens-Schönfelder, C. (2014).
- 737 Decorrelation and phase-shift of coda waves induced by local changes: Multiple
- scattering approach and numerical validation. *Waves in Random and Complex Media*,
- 739 24(2), 99–125. https://doi.org/10.1080/17455030.2014.880821
- Planès, T., Larose, E., Rossetto, V., & Margerin, L. (2015). Imaging multiple local changes in
- 741 heterogeneous media with diffuse waves. *The Journal of the Acoustical Society of*
- 742 *America*, *137*(2), 660–667. https://doi.org/10.1121/1.4906824
- 743 Pritchard, M. E., Allen, R. M., Becker, T. W., Behn, M. D., Brodsky, E. E., Bürgmann, R., et
- al. (2020). New Opportunities to Study Earthquake Precursors. *Seismological Research*
- 745 *Letters*, 91(5), 2444–2447. https://doi.org/10.1785/0220200089
- Rouet-Leduc, B., Hulbert, C., Lubbers, N., Barros, K., Humphreys, C. J., & Johnson, P. A.
- 747 (2017). Machine Learning Predicts Laboratory Earthquakes. *Geophysical Research*
- 748 *Letters*, 44(18), 9276–9282. https://doi.org/10.1002/2017GL074677
- 749 Rudnicki, J. W., & Chen, C. H. (1988). Stabilization of rapid frictional slip on a weakening
- fault by dilatant hardening. *Journal of Geophysical Research*, 93(B5), 4745–4757.
- 751 https://doi.org/10.1029/JB093iB05p04745
- 752 Shimazaki, K., & Nakata, T. (1980). Time-predictable recurrence model for large
- earthquakes. *Geophysical Research Letters*, 7(4), 279–282.
- 754 https://doi.org/10.1029/GL007i004p00279
- 755 Shreedharan, S., Rivière, J., Bhattacharya, P., & Marone, C. (2019). Frictional State
- 756 Evolution During Normal Stress Perturbations Probed With Ultrasonic Waves. *Journal*
- 757 of Geophysical Research: Solid Earth, 124(6), 5469–5491.
- 758 https://doi.org/10.1029/2018JB016885
- 759 Shreedharan, S., Bolton, D. C., Rivière, J., & Marone, C. (2020). Preseismic Fault Creep and
- 760 Elastic Wave Amplitude Precursors Scale With Lab Earthquake Magnitude for the

- 761 Continuum of Tectonic Failure Modes. *Geophysical Research Letters*, 47(8), 1–10.
- 762 https://doi.org/10.1029/2020GL086986
- ⁷⁶³ Shreedharan, S., Bolton, D. C., Rivière, J., & Marone, C. (2021a). Competition between
- 764 preslip and deviatoric stress modulates precursors for laboratory earthquakes. *Earth and*
- 765 Planetary Science Letters, 553, 116623. https://doi.org/10.1016/j.epsl.2020.116623
- ⁷⁶⁶ Shreedharan, S., Bolton, D. C., Rivière, J., & Marone, C. (2021b). Machine Learning Predicts
- the Timing and Shear Stress Evolution of Lab Earthquakes Using Active Seismic
- 768 Monitoring of Fault Zone Processes. Journal of Geophysical Research: Solid Earth,
- 769 *126*(7), 1–18. https://doi.org/10.1029/2020JB021588
- 570 Snieder, R. (2002). Coda wave interferometry and the equilibration of energy in elastic
- 771 media. *Physical Review E Statistical Physics, Plasmas, Fluids, and Related*
- 772 Interdisciplinary Topics, 66(4), 8. https://doi.org/10.1103/PhysRevE.66.046615
- Snieder, R. (2006). The theory of coda wave interferometry. *Pure and Applied Geophysics*,

774 *163*(2–3), 455–473. https://doi.org/10.1007/s00024-005-0026-6

- Snieder, R., Grêt, A., Douma, H., & Scales, J. (2002). Coda wave interferometry for
- estimating nonlinear behavior in seismic velocity. *Science*, 295(5563), 2253–2255.
- 777 https://doi.org/10.1126/science.1070015
- 778 Stähler, S. C., Sens-Schönfelder, C., & Niederleithinger, E. (2011). Monitoring stress
- changes in a concrete bridge with coda wave interferometry. *The Journal of the*
- 780 *Acoustical Society of America*, *129*(4), 1945–1952. https://doi.org/10.1121/1.3553226
- 781 Stanchits, S., Mayr, S., Shapiro, S., & Dresen, G. (2011). Fracturing of porous rock induced
- 782 by fluid injection. *Tectonophysics*, *503*(1–2), 129–145.
- 783 https://doi.org/10.1016/j.tecto.2010.09.022
- van Uijlen, W. M. (2013). Rotliegend geology in the Southern Permian Basin: the develop-
- 785 *ment of synrift sediments and its relation to seismic imaging.* Utrecht University.

- 786 Retrieved from https://studenttheses.uu.nl/handle/20.500.12932/14228
- 787 Veltmeijer, A., Naderloo, M., Pluymakers, A., & Barnhoorn, A. (2022). Acoustic Monitoring
- 788 of Laboratory Induced Fault Reactivation. In 83rd EAGE Annual Conference &
- *Exhibition* (pp. 1–5). European Association of Geoscientists & Engineers.
- 790 https://doi.org/10.3997/2214-4609.202210269
- 791 Veltmeijer, A., Naderloo, M., & Barnhoorn, A. (2023a). Active and Passive Seismic
- 792 Monitoring of Laboratory-Based Injection-Driven Fault Reactivation. In 84th EAGE
- 793 Annual Conference & Exhibition (pp. 1–5). European Association of Geoscientists &
- 794 Engineers. https://doi.org/10.3997/2214-4609.202310513
- 795 Veltmeijer, A., Naderloo, M., & Barnhoorn, A. (2023b). Supporting data for the article
- ⁷⁹⁶ "Forecasting of Rock Failure in the Laboratory using Active Acoustic Monitoring
- 797 Methods." [Dataset]: 4TU.ResearchData repository.
- 798 https://doi.org/https://doi.org/10.4121/21557910
- 799 Wang, K., Johnson, C. W., Bennett, K. C., & Johnson, P. A. (2022). Predicting Future
- 800 Laboratory Fault Friction Through Deep Learning Transformer Models. *Geophysical*
- 801 *Research Letters*, 49(19), 1–9. https://doi.org/10.1029/2022GL098233
- Wang, L., Kwiatek, G., Rybacki, E., Bonnelye, A., Bohnhoff, M., & Dresen, G. (2020).
- 803 Laboratory Study on Fluid-Induced Fault Slip Behavior: The Role of Fluid
- 804 Pressurization Rate. *Geophysical Research Letters*, 47(6), 1–12.
- 805 https://doi.org/10.1029/2019GL086627
- 806 Winkler, K., & Nur, A. (1979). Pore fluids and seismic attenuation in rocks. *Geophysical*
- 807 *Research Letters*, 6(1), 1–4. https://doi.org/10.1029/GL006i001p00001
- Xie, F., Ren, Y., Zhou, Y., Larose, E., & Baillet, L. (2018). Monitoring Local Changes in
- 809 Granite Rock Under Biaxial Test: A Spatiotemporal Imaging Application With Diffuse
- 810 Waves. Journal of Geophysical Research: Solid Earth, 123(3), 2214–2227.

- 811 https://doi.org/10.1002/2017JB014940
- 812 Ye, Z., & Ghassemi, A. (2020). Heterogeneous Fracture Slip and Aseismic-Seismic
- 813 Transition in a Triaxial Injection Test. *Geophysical Research Letters*, 47(14), 1–9.
- 814 https://doi.org/10.1029/2020GL087739
- 815 Zhang, Y., Abraham, O., Grondin, F., Loukili, A., Tournat, V., Duff, A. Le, et al. (2012).
- 816 Study of stress-induced velocity variation in concrete under direct tensile force and
- 817 monitoring of the damage level by using thermally-compensated Coda Wave
- 818 Interferometry. *Ultrasonics*, 52(8), 1038–1045.
- 819 https://doi.org/10.1016/j.ultras.2012.08.011
- 820 Zotz-wilson, R., Filippidou, N., Linden, A. Van Der, & Verberne, B. A. (2020). Coda-Wave
- 821 Based Monitoring of Pore-Pressure Depletion-driven Compaction of Slochteren
- 822 Sandstone Samples from the Groningen Gas Field. *Journal of Geophysical Research:*
- *Solid Earth*. https://doi.org/https://doi.org/10.1002/essoar.10501522.2
- 824 Zotz-Wilson, R., Boerrigter, T., & Barnhoorn, A. (2019). Coda-wave monitoring of
- s25 continuously evolving material properties and the precursory detection of yielding. *The*
- *Journal of the Acoustical Society of America*, *145*(2), 1060–1068.
- 827 https://doi.org/10.1121/1.5091012

828

Figure 1.



Stress build-up Compaction and increase of stress on the fault



stress

Fault reactivation Large slip and stress release along the fault Fault Reactivation Stages



Pre-slip/early creep pre-seismic High stresses on fault and small amounts of stress COrelease/slip seismic inter-seismic post-seismic Fault healing time Slow build-up of stress again Figure 2.









Figure 3.



Figure 4.





a

Figure 5.



Figure 6.



Figure 7.



Figure 8.



Figure 9.



Figure 10.



Figure 11.





е

a

3

D

Figure 12.

