Fine sediment in mixed sand-silt environments impacts bedform geometry by altering sediment mobility

Sjoukje Irene de Lange¹, Iris Niesten¹, Sanne H.J. van de Veen¹, Jaco H. Baas², Jasper F.D. Lammers³, Kryss Waldschläger⁴, David Boelee⁵, and A.J.F. (Ton) Hoitink¹

¹Wageningen University
²Bangor University
³Wageningen University & Research
⁴Wageningen University of Research
⁵Wageningen University

January 22, 2024

Abstract

Geometric characteristics of subaqueous bedforms, such as height, length and leeside angle, are crucial for determining hydraulic form roughness and interpreting sedimentary records. Traditionally, bedform existence and geometry predictors are primarily based on uniform, cohesionless sediments. However, mixtures of sand, silt and clay are common in deltaic, estuarine, and lowland river environments, where bedforms are ubiquitous. Therefore, we investigate the impact of fine sand and silt in sand-silt mixtures on bedform geometry, based on laboratory experiments conducted in a recirculating flume. We systematically varied the content of sand and silt for different discharges, and utilized a UB-Lab 2C (a type of acoustic Doppler velocimeter) to measure flow velocity profiles. The final bed geometry was captured using a line laser scanner. Our findings reveal that the response of bedforms to an altered fine sediment percentage is ambiguous, and depends on, among others, bimodality-driven bed mobility and sediment cohesiveness. When fine, non-cohesive material (fine sand or coarse silt) is mixed with the base material (medium sand), the hiding-exposure effect comes into play, resulting in enhanced mobility of the coarser material and leading to an increase in dune height and length. However, the addition of weakly-cohesive fine silt reduces the mobility, suppressing dune height and length. Finally, in the transition from dunes to upper stage plane bed, the bed becomes unstable and bedform heights vary over time. The composition of the bed material does not significantly impact the hydraulic roughness, but mainly affects roughness via the bed morphology, especially the leeside angle.

Fine sediment in mixed sand-silt environments impact bedform geometry by altering sediment mobility

S.I. de Lange¹, I. Niesten¹, S.H.J. van de Veen¹, J.H. Baas², J. Lammers¹, K. Waldschläger¹, D. Boelee¹, A.J.F. Hoitink¹

¹Wageningen University, Department of Environmental Sciences, Hydrology and Environmental Hydraulics, Wageningen, the Netherlands ²School of Ocean Sciences, Bangor University, Menai Bridge, United Kingdom

Key Points:

1

2

3

4

5

6

8

9	• Adding finer, non-cohesive material to a sand bed increases the mobility of the
10	sand, resulting in an increased dune length.
11	• Adding finer, weakly-cohesive silt to a sand bed, decreases the mobility of the sand,
12	which hampers dune formation and growth.
13	• Sediment bed composition does not directly impact total hydraulic roughness, but
14	indirectly affects it via altering the bed morphology.

Corresponding author: Sjoukje de Lange, sjoukje.delange@wur.nl

15 Abstract

Geometric characteristics of subaqueous bedforms, such as height, length and leeside an-16 gle, are crucial for determining hydraulic form roughness and interpreting sedimentary 17 records. Traditionally, bedform existence and geometry predictors are primarily based 18 on uniform, cohesionless sediments. However, mixtures of sand, silt and clay are com-19 mon in deltaic, estuarine, and lowland river environments, where bedforms are ubiqui-20 tous. Therefore, we investigate the impact of fine sand and silt in sand-silt mixtures on 21 bedform geometry, based on laboratory experiments conducted in a recirculating flume. 22 We systematically varied the content of sand and silt for different discharges, and uti-23 lized a UB-Lab 2C (a type of acoustic Doppler velocimeter) to measure flow velocity pro-24 files. The final bed geometry was captured using a line laser scanner. Our findings re-25 veal that the response of bedforms to an altered fine sediment percentage is ambiguous, 26 and depends on, among others, bimodality-driven bed mobility and sediment cohesive-27 ness. When fine, non-cohesive material (fine sand or coarse silt) is mixed with the base 28 material (medium sand), the hiding-exposure effect comes into play, resulting in enhanced 29 mobility of the coarser material and leading to an increase in dune height and length. 30 However, the addition of weakly-cohesive fine silt reduces the mobility, suppressing dune 31 height and length. Finally, in the transition from dunes to upper stage plane bed, the 32 bed becomes unstable and bedform heights vary over time. The composition of the bed 33 34 material does not significantly impact the hydraulic roughness, but mainly affects roughness via the bed morphology, especially the leeside angle. 35

³⁶ Plain Language Summary

Underwater bedforms, such as dunes, are often found on the bed of rivers and deltas. 37 These rhythmic undulations have specific shapes and sizes, and they affect how water 38 flows. When the bed of the river is made up of sand, we can predict the dune height and 39 length. However, mixtures of different-sized sediments are common in rivers, and it is 40 unknown how this impacts the geometry of the dunes. Therefore, we did experiments 41 in a flume, a laboratory facility to simulate a river, and we tested different sediment bed 42 mixtures. We found that adding non-cohesive fine particles to the base material caused 43 the base material to be more mobile, leading to longer dunes. However, when adding weakly-44 cohesive fine particles, the effect was the opposite, and the dunes became shorter due 45 to the limited mobility of the sediment. Finally, we observed that under high flow con-46 ditions, the bed became unstable and different dune shapes occurred. We found that the 47 friction the water experiences is not directly impacted by the sediment bed mixtures, but 48 is mostly affected by the shape of the bedforms. 49

50 1 Introduction

River bedforms are ubiquitous in low-land rivers, and they are known to impact the river 51 by altering its hydraulics, ecology, and sediment balance. The geometry of river bedforms, 52 especially dunes, impacts the fairway depth (ASCE Task Force, 2002; Best, 2005), adds to 53 the form roughness of the river bed (Warmink et al., 2013; Venditti and Bradley, 2022), and 54 determines suitable foraging places for fish (Greene et al., 2020). It is therefore useful to 55 predict the geometry of bedforms without having to perform regular field measurements. In 56 non-supply limited conditions, river dunes may scale with flow depth (Allen, 1978). However, 57 more recent studies have reinstated the observations by Yalin (1964), Van Rijn (1984), 58 and Karim (1995), indicating a relation between bedform geometry and some measure of 59 transport stage (Bradley and Venditti, 2019; Venditti and Bradley, 2022), where transport 60 stage represents the ratio between flow strength and the mobility of the bed material. Dune 61 length increases with transport stage, while dune height increases with transport stage until 62 a maximum is reached, whereafter the height decreases and the bedforms start to wash out 63 (Baas and Koning, 1995; Bradley and Venditti, 2019). This framework effectively predicts 64

dune height and length, despite considerable variability, which can be up to two-orders of magnitude (Bradley and Venditti, 2017). This variability may in part be attributed to the influence of bed composition on bedform geometry.

The bed composition, i.e. the grain size distribution of the bed sediment, is one of 68 the primary determinants for bedform existence and size. Measures of grain size appear 69 in almost all existing phase diagrams (Southard and Boguchwal, 1990; Berg and Gelder, 70 1993; Perillo et al., 2014), with the median grain size D_{50} as general parameterization. 71 However, this simplification poses challenges when dealing with natural sediment mixtures 72 73 characterized by complex, multimodal sediment size distributions, which are common in deltaic, estuarine and coastal environments featuring sediment mixtures of mud (i.e. clay 74 and silt) and sand (Healy et al., 2002). 75

Recent research has focused on understanding how cohesive clay affects bedform geometry. It has been observed that even a small percentage of cohesive clay in sand-clay mixtures
can effectively suppress bed mobility, resulting in a reduced bedform height (Schindler et al.,
2015; Parsons et al., 2016) and limited bedform growth (Wu et al., 2022). It is, however,
unknown what the impact of non- and weakly cohesive fine materials (silts and fine sands)
is on dune morphology, despite their abundance in downriver environments.

A few studies explored the influence of silt on erodibility of the sediment bed. For 82 instance, Bartzke et al. (2013) examined the behavior of sand (300 μ m)-silt (50 μ m) beds 83 in an annular laboratory flume. They found that an increasing silt content, even at low 84 percentages (as little as 0.18% silt), contributed to bed stabilization through a reduction 85 in water inflow, attributed to pore-space plugging by silt. Yao et al. (2022) also reported 86 increased stability (i.e., increased erosion threshold) with increasing silt content in their 87 laboratory experiments, although stabilization only occurred at a silt content of >35%, 88 when a stable silt skeleton could be formed. Opposing Bartzke et al. (2013), a change in 89 bed stability was not observed at lower silt contents. 90

Additionally, Ma et al. (2017) and Ma et al. (2020) studied a silt-rich sediment bed 91 $(D_{50} = 15 - 150 \ \mu m)$ with low dunes in the Yellow River. Ma et al. (2020) showed that 92 the presence of fine sediment (silt) led to a shift from a low-efficiency sediment transport 93 regime (following the Engelund-Hansen equations (Engelund and Hansen, 1967)) to a high-94 efficiency regime. The high-efficiency regime prevailed for sediment beds with a medium 95 grain size smaller than 88 μ m, and, in the transitional range (88 μ m < D₅₀ < 153 μ m), 96 the existence of this regime depended on sorting of the material $(\sqrt{D_{84}/D_{16}})$. They argued 97 that the shift from a low- to a high-efficiency transport regime resulted from the transition 98 from mixed load to suspended sediment transport, caused by the presence of silt. 99

Yet, none of these studies discussed the potential impact of silt content on bedforms. 100 This is an important research gap, because an increase in bed stability, as observed by 101 Bartzke et al. (2013) and Yao et al. (2022), could theoretically reduce bedform formation 102 and growth due to a decrease in sediment transport, whilst Ma et al. (2020)'s suspension-103 load dominated high-efficiency regime would also mean suppression of bedform formation 104 and growth, but then because bedload transport gets increasingly replaced by suspended 105 load transport, which is incapable of forming bedforms. Clearly, the effect of silt in sand-silt 106 mixtures on the resulting bedform geometry is largely unexplored. Therefore, our research 107 seeks to address the following question: What is the influence of the fraction non-cohesive 108 and weakly cohesive fine sediment in sand-silt mixtures on the dynamic equilibrium bedform 109 geometry and the resulting hydraulic roughness? 110

To answer this question, we conducted 52 laboratory experiments in a recirculating flume, in which the influence of fine sand and silt percentage in sand-silt mixtures on bedform geometry was studied. For three flow velocities, three different sediment mixtures, largely falling within the studied range of Ma et al. (2020), were tested by systematically mixing various fractions of fine sand, coarse silt and fine silt with a coarser base material of



Figure 1. Schematic drawing of the experimental setup. The flume recirculates both water and sediment.

medium sand. These experiments allowed us to assess how different sizes of fine sediment 116 in a sand-silt mixture affect the transport stage and the resulting bedform geometry under 117 different flow conditions. In the following sections, we provide a detailed description of the 118 experimental setup, after which we discuss the different equilibrium bedform geometries 119 that resulted from the experiments. We argue that the hiding-exposure effect enhances the 120 mobility of the coarser fraction, whereas cohesion from fine silt decreases the bed mobility, 121 leading to deviations from the expected relationship between transport stage and bedform 122 dimensions. 123

124 2 Methods

125

2.1 Experimental setup

The experiments were conducted in a tilting flume with recirculation facilities for both 126 water and sediment in the Kraijenhoff van de Leur Laboratory for Water and Sediment 127 Dynamics of Wageningen University and Research (Figure 1 and 2). The flume has an 128 internal width of 1.20 m, a length of 14.4 m, and a height of 0.5 m. The water level is 129 controlled by adjusting a downstream weir. A diffuser (Figure 2a) at the upstream part 130 ensures that the inflow is distributed over the entire width of the flume. The diffuser is 131 followed by a stacked pile of PVC tubes that serve as a laminator, suppressing turbulence 132 at the inflow section. At the end of the flume, a funnel was installed to channel bedload 133 material to a lower reservoir (Figure 1), and to prevent deposition in front of the weir. A 134 continuously running sediment scraper ensures that the sediment stays in suspension in the 135 lower reservoir, upon being pumped back to the inflow of the flume. At the end of one 136 experiment (35% fine sand, medium discharge) the sediment funnel was clogged and the 137 sediment was not fully recirculated. This run was excluded from the analysis. 138

The flow depth was set to 15 cm, measured from the initial flat sediment bed, and it was kept the same for all experimental runs by adjusting the weir height. The slope was set to 0.01 m m⁻¹. Experimental runs were performed for different discharges (low: 45 L s⁻¹; medium: 80 L s⁻¹; high: 100 L s⁻¹), to be able to distinguish the effects of different trans-



Figure 2. Pictures of the laboratory flume and the instrumentation. a) Flume with flatbed, facing upstream, including the upstream-located diffuser. b) Bed covered with small bedforms, facing downstream, including the downstream-located weir. c) UB-Lab 2C flow velocity profiler. d) Dune-covered bed, facing upstream. e) Dune-covered bed, facing downstream, with the UB-Lab 2C in background. f) Line laser scanner.

port stages on bedform morphology. The discharge was monitored and regulated with an 143 electromagnetic flow meter. The corresponding calculated width- and depth-averaged flow 144 velocities were 0.25, 0.44 and 0.56 m s⁻¹, the corresponding depth-averaged flow velocities 145 in the middle of the flume (measured with an UB-Lab 2C, see section 2.2) were slightly 146 larger due to a side-wall effect (0.30, 0.45 and 0.58 m s⁻¹, respectively). The experiments 147 were run for 12, 5 and 3 hours for the low, medium, and high discharges, respectively. Based 148 on the ripple size predictor of Soulsby et al. (2012), the medium-sand ripples formed in the 149 low-discharge experiments reached about 80% of their equilibrium height and length after 150 12 hours. Their planform at this development stage was linguoid, which agrees with the 151 planform predicted by ripple development model of Baas (1999). Nagshband et al. (2016) 152 studied the dune equilibrium time for medium sand (290 μ m). Their equilibrium dimen-153 sions were reached after 3 hours for the experiments with a flow velocity of 0.64 m s^{-1} and 154 after 1.5 hours for 0.80 m s^{-1} . This suggests that the dunes formed at medium and high 155 discharges in the present experiments reached equilibrium size. 156

The flow was sub-critical and turbulent during all experiments, determined by the Froude number, Fr (-), being smaller than 1 (0.30, 0.54 and 0.69, respectively) and the Reynolds number, Re (-), being larger than 4000 (38000, 67000, 83000, respectively), calculated with:

$$Fr = \frac{u}{\sqrt{gh}} \tag{1}$$

$$Re = \frac{hu}{\nu} \tag{2}$$

where u is the time and depth-averaged flow velocity (m s⁻¹), g is the gravitational acceleration (9.81 m s⁻²), h is the water depth (0.15 m), and ν is the kinematic viscosity (m² s⁻¹), which is weakly dependent on water temperature, t (°C), as $\nu = 4 * 10^{-5}/(20+t)$. Here, $\nu = 1.05 * 10^{-6}$ m² s⁻¹ for 18 °C is used.



Figure 3. a) Grain-size distributions of the sediments used in the experiments. b) D_{10} , D_{50} and D_{90} of the tested mixtures, in which the finer material (fine sand, coarse silt or fine silt) is mixed with the base material (medium sand).

A sediment bed with a thickness of 0.10 m was applied, which consisted of a mixture of 165 two grain sizes: a base sediment of medium sand (median size, $D_{50} = 256 \ \mu$ m), mixed with 166 fine sand $(D_{50} = 170 \ \mu\text{m})$, coarse silt $(D_{50} = 37 \ \mu\text{m})$ or fine silt $(D_{50} = 17 \ \mu\text{m})$ (Figure 3a 167 and Supplementary Figure S1 for images of the sediment). All sediments were composed of 168 silica (SiO_2) . The particle size distribution of the original sediments was measured with a 169 Mastersizer 3000 (Figure 3). The fine sand and coarse silt are non-cohesive, whereas the fine 170 silt could be classified as weakly-cohesive (Wolanski, 2007), confirmed by visual observation 171 of the sticky fine silt slurry and a significantly higher submerged angle of repose (40° instead 172 of 30° for sand). No visible flocculation of the silt fraction occurred during the experiments. 173

The weight percentage of finer material mixed with the base material ranged from 0 to 175 100 wt% for fine sand, to 51 wt% for coarse silt (with 49 wt% medium sand) and to 30 wt% 176 for fine silt (with 70 wt% medium sand). In total, 17 different mixtures were tested, which 177 were all exposed to the low, medium and high discharge. In Table 1, an overview of the 178 experimental mixtures is given. The D_{50} and 90th-percentile, D_{90} , values of the mixtures 179 hardly changed when adding finer material, but the 10th-percentile, D_{10} , values dropped 180 significantly when adding coarse or fine silt (Figure 3b).

2.2 Instrumentation

181

A line laser and 3D camera (Figure 2f), equipped with Gigabit Ethernet (SICK, 2012), was used to scan the bed topography. The devices were mounted on a measurement carriage that moved on fixed rails along the flume. After every experimental run, the flume was slowly drained, and an area of 7 x 1 m was recorded in three parallel, partially overlapping, swaths, with a resolution of 0.1 mm. See Ruijsscher et al. (2018) for a detailed description of the line laser scanner.

During the first and last 30 minutes of an experimental run, an UB-Lab 2C (UBER-TONE) (Figure 2c) was deployed to measure flow velocity profiles. The UB-Lab 2C is an ADVP (acoustic Doppler velocity profiler, e.g. Hurther and Lemmin (2001) and Mignot et al. (2009)), which measures a two-component velocity profile at high spatial (1.5 mm) and temporal resolution, here 10 to 15 Hz. An acoustic signal is transmitted along a single beam and received by two receivers under different observation angles. The resulting 2-component

Table 1. Overview of the performed experiments. Seventeen different sediment mixtures were tested, in which the type and percentage of fine material relative to the coarse material (base material) varied per experimental run. Each experiment with a distinct mixture was conducted for low, medium and high discharge, resulting in 51 experiments. * the experiment with medium discharge was excluded from analysis because of clogging of the pumps.

base expe	riment
1	0/100
experiments with	ith fine sand
2-4	$35/65^{*}$
5-7	51/49
8-10	65/35
11-13	82/18
15-18	100/0
experiments wi	th coarse silt
19-21	2/98
22-24	5/95
25-27	11/89
28-30	22/78
31-33	32/68
34-36	51/49
experiments u	with fine silt
37-39	2/98
40-42	4/96
43-45	9/91
46-48	23/77
49-51	30/70

experiment number % fine / % coarse

vector is than projected to yield the 2-dimensional velocity in the streamwise direction (u)and vertical direction (w) along the beam (1D-profile). The emission frequency was set to 1 MHz with a bin size of 1.5 mm. The pulse repetition frequency ranged from 1200 to 1800 Hz for low and high discharge, respectively.

¹⁹⁸ 2.3 Data analysis

¹⁹⁹ 2.3.1 Sediment characterization

The behavior of the sediment in the experiments was estimated from the span value of the sediment-size distribution and the dominant way of sediment transport. This information was later used to interpret the observed bedform patterns.

The span value of the tested mixtures was used as a measure of distribution width, and was defined as:

$$SV = \frac{D_{90} - D_{10}}{D_{50}} \tag{3}$$

²⁰⁵ The sorting was determined as:

$$\sigma_g = \sqrt{\frac{D_{84}}{D_{16}}} \tag{4}$$

To determine the dominant way of transport, the ratio between the settling velocity of a particle, w_s , and the shear velocity, u^* , was calculated. If this ratio is larger than 3, the dominant transport mode is expected to be bedload, and if the ratio is smaller than 0.3, the dominant mode is expected to be suspended load (Dade and Friend, 1998). In between these values, the transport mode is mixed.

The settling velocity of a particle was approximated with (Ferguson and Church, 2004; Dietrich, 1982):

$$w_s = \frac{\rho_r g D_{50}^2}{C_1 \nu + \sqrt{0.75 C_2 R g D_{50}^3}} \tag{5}$$

where ρ_r is the relative submerged density $= (\rho_s - \rho_w)/\rho_w$, and $C_1 = 18$ and $C_2 = 1$ for natural grains (Ferguson and Church, 2004). The D_{50} of the original sediments was used rather than the D_{50} of the mixture, giving a transport mode for the base sediment and the finer fraction separately. This approximation was verified by visual observation through a window in the side of the flume.

2.3.2 Bedform geometry

218

Final bed configurations were determined from the bed elevation data obtained with 219 the line laser scanner. Five longitudinal transects were constructed across the width of 220 the flume, with an interspacing of 200 mm. The resulting transects served as input for 221 the bedform tracking tool of Mark and Blom (2007), which gives bedform geometry based 222 on specific detrending lengths, used to differentiate between bedform scales. Two bedform 223 length scales were identified: 150 ± 100 mm (hereafter referred to as small bedforms), and 224 1100 ± 400 mm (referred to as large bedforms). Small bedforms were observed in the 225 low-discharge experiments, whilst larger bedforms were observed in the medium and high-226 discharge experiments, and the bedform tracking tool was applied accordingly. Only if the 227 bedform occurred in at least two profiles of a bed scan, bedform statistics were calculated. 228

Bedform characteristics (Figure 4) in this study included bedform height, Δ (m), the vertical distance between crest and downstream trough; bedform length, λ (m), the horizon-



Figure 4. Definition of the bedform characteristics, showing the bedform height (Δ), the length (λ), the total length of the stoss side (λ_{stoss}) and the length of the stoss side at 0.5* Δ ($\lambda_{0.5stoss}$), the leeside angle (*LSA*), in which the upper and lower 1/6th of the leeside is excluded, the stoss-side angle (*SSA*), also excluding the upper and lower 1/6th of the stoss side, and the slip-face angle (*SFA*), which is the steepest part (95-percentile) of the leeside. The steepest part of the leeside is indicated with a small purple marker, and the location of the upper and lower 1/6th of the lee and stoss side are indicated with a small black marker.

tal distance between two subsequent crests; lees
ide angle, LSA (°), the slope angle derived 231 from a linear fit of the bedform's lesside, excluding the upper and lower 1/6 of the bed-232 form height; stoss-side angle, SSA (°), calculated similarly to the leeside angle; and the 233 slip-face angle, SFA (°), the steepest part of the leeside, calculated as the 95-percentile of 234 the distribution of angles along the leeside. The bedform roundness index, BRI, of the small 235 bedforms was defined as the ratio between the length from the dune crest to the stoss side at 236 0.5 times the dune height ($\lambda_{0.5stoss}$) and the length of the stoss side (λ_{stoss}) (Perillo et al., 237 2014; Prokocki et al., 2022). A bedform was classified as rounded if $BRI \ge 0.6$. Finally, the 238 bedform width, W (m), was derived by constructing six cross-sectional profiles transverse 239 to the flow, with an interspacing of 1000 mm. Next, the same bedform tracking tool was 240 applied using the same settings as for the longitudinal profiles. The bedform width was 241 calculated only for the low-discharge experiments, where the width of the bedforms was 242 considerably smaller than the width of the flume. 243

244 2.3.3 Bedform geometry predictors

Various bedform geometry predictors were tested based on our data. The selected predictors for dune height and length included a measure of flow strength (Van Rijn, 1984; Venditti and Bradley, 2022), and the predictor of Soulsby et al. (2012) was used for the height and length of ripples.

Van Rijn (1984) developed an empirical dune height and length predictor, the former being dependent on the transport stage, T_{vRijn} , as measure of flow strength.

$$\Delta_{vRijn} = 0.11h \left(\frac{D_{50}}{h}\right)^{0.3} (1 - e^{-0.5T_{vRijn}})(25 - T_{vRijn}) \tag{6}$$

$$\lambda_{vRijn} = 7.3h\tag{7}$$

 T_{vRijn} depends on shear stress and critical shear stress. See Appendix A for a full explanation. ²⁵³ Venditti and Bradley (2022) developed an empirical equation based on a different trans-²⁵⁴ port stage, T_{VB} , defined as $\frac{\theta}{\theta_c}$, which is the ratio of the dimensionless shear stress, θ , and ²⁵⁵ critical shear stress, θ_c . The equations suitable for laboratory flows with a water depth less ²⁵⁶ than 0.25 m are:

$$\Delta_{VB} = h \left(-0.00100 (\frac{\theta}{\theta_c} - 17.7)^2 + 0.417 \right)$$
(8)

$$\lambda_{VB} = h \left(0.0192 (\frac{\theta}{\theta_c} - 8.46)^2 + 6.23 \right)$$
(9)

The geometry of ripples is only dependent on a measure of grain size (D^*) and independent of transport stage (Baas, 1994; Baas, 1999). According to the equations of Soulsby et al. (2012), their geometry can be predicted with:

$$\Delta_{Souslby} = D_{50} 202 D^{*-0.554} \tag{10}$$

$$\lambda_{Soulsby} = D_{50}(500 + 1881D^{*-1.5}) \tag{11}$$

All definitions and symbols are given in Appendix A.

261 2.3.4 Roughness characterization

Hydraulic roughness was estimated following two methods. Firstly, the measured velocity profiles were used, following the method of Hoitink et al. (2009). Secondly, an indirect hydraulic roughness predictor of Van Rijn (1984) was used, based on bed geometry and sediment characteristics.

The first method is based on the Law of the Wall:

$$\frac{\overline{u}(z)}{u^*} = \frac{1}{\kappa} ln(\frac{z+h}{z_0}) \tag{12}$$

where \overline{u} is the mean velocity (m s⁻¹), $\kappa = 0.4$ is the Von Karman constant, h is the mean water depth (m), z is the height above the bed (m), and z_0 is roughness length (m).

For a water column that satisfies equation (12), i.e. where the velocity profiles are logarithmic (Supplementary Figure S3), the shear velocity can be determined from the slope of the velocity versus dimensionless depth σ_d (equation (B2)). This, in turn, can be used to derive roughness length and, ultimately, Manning's n, n_{man} (s m^{-1/3}). See Appendix B for an elaborate definition. Experiments 13-18 were excluded from analysis, since erroneous mounting caused invalid profiles.

Roughness was also approximated indirectly based on the predictor of Van Rijn (1984). The total predicted hydraulic roughness, expressed as friction factor, \hat{f} , results from form friction and grain friction (Einstein, 1950). The total hydraulic roughness was predicted as in Van Rijn (1984):

$$\hat{f} = \frac{8g}{(18\log(\frac{12h}{k_s}))^2}$$
(13)

where k_s is a measure of roughness both consisting of form roughness and grain roughness. See Appendix B for the corresponding equations. Friction factor f can be converted to n_{man} via (Manning, 1891; Silberman et al., 1963):

$$n_{man} = \frac{R_h^{1/6}}{\sqrt{\frac{8g}{\hat{f}}}} \tag{14}$$

where R_h is the hydraulic radius, which is equal to the cross-sectional area (A) divided by the wetted perimeter (P = width + 2h).

284 3 Results

281

285

289

302

3.1 Observed bed geometries

The bed geometries in the experiments were dependent on discharge (Figure 5a-c, see Supplementary Figures S2-S4 for the bed geometry of all runs), and on the addition of fine material. Below, we show the results separately for low, medium and high discharge.

3.1.1 Low discharge bed geometries

At low discharge, only small bedforms appeared on the bed (Figure 5a). The small bedforms had an average height of 0.011 m, an average length of 0.12 m and a non-rounded shape with a slip-face angle of 22°.

Bedform height and width both decreased with the addition of coarse silt and fine silt, 293 which is especially pronounced at a silt percentage above 20% (Figure 6a). The bedform 294 height decreased by 38% for coarse silt and 28% for fine silt compared to the experiment with 295 pure medium sand. The corresponding decrease in length was considerably smaller (14% 296 and 4%, respectively). This decrease in bedform height was not visible in the experiments 297 with fine sand. Similarly, bedform width decreased by 11% and 23% for coarse and fine silt 298 (Figure 6c), indicating that the bedforms became more three-dimensional in shape. The 299 LSA, SFA and BRI of these bedforms were independent of the type and percentage of finer 300 material added (Figure 6d-f). 301

3.1.2 Medium discharge bed geometries

The bedforms generated during medium discharge were generally larger than those 303 that emerged during low discharge, with an average height of 0.027 m, a length of 0.54 m, 304 and a slightly lower slip-face angle of 20° . Those bedforms followed two general trends. 305 Firstly, the runs with an increasing amount of fine sand and coarse silt showed an increase 306 in bedform height and length (Figure 5b). Especially for the coarse-silt runs, the increase 307 in bedform length was considerable (Figure 7b). The bedform length in these runs was on 308 average 0.59 m for the experiments with 20% coarse silt or less, and increased to 1.1 m for 309 the experiments with a higher coarse-silt percentage in the bed. This increase in bedform 310 length was accompanied by a smaller increase in bedform height from 0.032 m to 0.043 m 311 (Figure 7a). Bedform heights and lengths for the experiments with fine sand were smaller 312 than for the experiments with coarse silt (on average $\Delta = 0.026$ m and $\lambda = 0.54$ m for fine 313 sand, and $\Delta = 0.035$ m and $\lambda = 0.73$ m for coarse silt). The lee-face angles varied per 314 experiment, but the slip-face angles remained relatively constant, lacking a consistent trend 315 with increasing content of fine material (Figure 7c and d). 316

The experiments with fine silt revealed smaller bedforms that were larger than the bedforms in the low-discharge experiments, but comparable in planform (Figure 5d), despite the clear increase in depth-averaged flow velocity. The mean bedform length was 0.38 m, which is significantly smaller than for the experiments with fine sand and coarse silt. However, at 0.025 m, the mean bedform height is comparable to the runs with fine sand. A decrease in length and height was observed for the runs with 0 to 30% fine silt (23% decrease



Figure 5. Dynamic equilibrium bed morphologies at the end of selected experiments. All images represent a 1 m wide and 7 m long section of flume. a) Bed morphologies at low discharge. b) Bed morphologies at medium discharge, showing increasing dune length with increasing finer material. c) Bed morphologies with large variability at high discharge. d) Impact of fine silt on bed morphology. Scans in (c) show small two-dimensional ripples superimposed on larger bedforms and flat beds. These ripples are artifacts caused by draining the flume over an almost flat bed (see Supplementary Figure S5 for verification).



Figure 6. Bedform geometries at low discharge (45 L s⁻¹). a) Bedform height. Δ . b) Bedform length, λ . c) Bedform width, W. d) Bedform roundness index, *BRI*, where *BRI* < 0.6 indicates non-rounded bedforms. e) Leeside angle, *LSA*. f) Slip-face angle, *SFA*.



Figure 7. Bedform geometries at medium discharge (80 L s⁻¹). a) Bedform height, Δ . b) Bedform length, λ . c) Leeside angle, *LSA*. d) Slip-face angle, *SFA*.

in bedform height, 51% decrease in bedform length). Leeside angles were 28% larger than in the experiments with fine sand and coarse silt, but the slip-face angles were comparable.

3.1.3 High discharge bed geometries

The bedforms formed at high discharge were on average slightly larger than during 326 medium discharge (Figure 8), with an average height of 0.029 m and length of 0.72 m. 327 The slip-face angle was 18° , which was slightly lower than at medium discharge. However, 328 the geometrical parameters were highly variable, with a standard deviation of 1.6 cm, 39329 cm, 4.6° for bedform height, length and slip-face angle, respectively, and without a clear 330 relationship with the amount of fine material. The experiments with fine silt resulted on 331 average shorter bedform lengths and higher leeside angles than the experiments with coarse 332 silt and fine sand, which agrees with the observations at medium discharge. 333

The high discharge experiments were conducted close to the suspension threshold (w_s / $u^* < 0.3$), and the bedforms started to wash out towards upper stage plane bed, when three alternating bed states were observed (Figure 5c): an almost flat bed with one or two large, steep bedforms; a bed covered with dunes; and a flat bed.

338 3.2 Bedform variability

325

Relationships between bedform geometry and transport stage, θ/θ_c , are evident from the experimental data. Bedform length increased, and leeside and slip-face angle decreased with increasing transport stage, whereas the relationship between bedform height and transport stage approached a parabola (Figure 9a-d). Additionally, the variability in bedform geometry increased with increasing transport stage, indicated by the gray shaded band in Figure 9a-d.

The near-bed velocity $U_{0.2}$, which is the time-averaged velocity at the dimensionless height above the bed of $\sigma_d = 0.2$ and directly measured with the UB-Lab 2C, is a repre-



Figure 8. Bedform geometries at high discharge (100 L s⁻¹). a) Bedform height, Δ . b) Bedform length, λ . c) Leeside angle, LSA. d) Slip-face angle, SFA. Zero values indicate a flat bed.

sentation of the near-bed conditions influencing and being influenced by the bed geometry. The near-bed velocity shows a strong relation with the dimensionless bedform length (R^2 = 0.66) (Figure 9e).

The bedform height and length predictions for dunes based on Van Rijn (1984) and 350 Venditti and Bradley (2022) are shown in Figure 9a-b. For the low-discharge runs, these 351 predictions overestimate the measured bedform dimensions significantly. However, the rip-352 ple predictor of Soulsby et al. (2012) performs relatively well, with root-mean-square errors 353 of 0.001 m for height and 0.02 m for length. The bedforms can therefore be classified as 354 ripples. For the medium and high discharge runs, the Soulsby et al. (2012) equation for 355 ripples underpredicts the bedform size significantly. These bedforms are therefore classified 356 as dunes. The predictor of Van Rijn (1984) performs reasonably well for medium transport 357 stages, but it mostly underpredicts bedform heights for high transport stages. The predic-358 tor of Venditti and Bradley (2022) slightly overpredicts bedform height, but the measured 359 values are still within their margins of error. The bedform length predictor of Van Rijn 360 (1984), which is purely based on water depth, does not capture the trend of increasing dune 361 length with increasing transport stage. The predictor of Venditti and Bradley (2022) largely 362 overestimates bedform length for medium transport stages, but performs better for the high 363 transport stages by capturing the observed increase in length. 364

365 3.3 Hydraulic roughness

Hydraulic roughness, expressed as the depth-independent Manning's n and calculated 366 via the Law of the Wall based on the velocity profiles (equation (12)), averaged 0.038. 367 Manning's n increased with increasing leeside angle $(R^2 = 0.31)$ and decreasing bedform 368 length $(R^2 = 0.40)$ (Figure 10c-d). The relation with lenside angle stands out (Figure 10c), 369 since the ripples and dunes are both part of the linear correlation, whereas no relation 370 between ripple length and roughness was observed. Generally, the roughness was larger 371 during the experiments with fine silt (Figure 10) and the experiments with a rippled bed 372 (on average 0.039). The larger roughness is likely to be related to the relatively high leeside 373 angle of the bedforms observed in those experiments. 374



Figure 9. Increasing variability in bedform geometry with increasing flow strength, expressed as transport stage (θ/θ_c) in (a-d) and as non-dimensionalized velocity at 20% above the bed in (e). a) Bedform height divided by water depth. b) Bedform length divided by water depth. c) Leeside angle. d) Slip-face angle. e) Bedform length divided by water depth. Grey shading indicates one standard deviation from the mean value, in which the standard deviation is calculated from all bedforms in either low, medium or high discharge experiments. The base runs are indicated with black markers (medium sand). In (a) and (b), the predicted values by Venditti and Bradley (2022) and Van Rijn (1984) are shown.



Figure 10. The relation between the hydraulic roughness n_{man} , calculated with the Law of the Wall, and a) Bedform height, Δ . b) Fraction finer material within the base material. c) Leeside angle, LSA. d) Bedform length, λ . Significant linear relations are shown in c and d.

Counter-intuitively, hydraulic roughness does not exhibit a statistically significant re-375 lationship with dune height and the fraction of added finer material (Figure 10a-b). The 376 lack of a relationship with added fine material is consistent with the roughness predictor 377 of Van Rijn (1984), which differentiates between skin friction, related to grain size, and 378 form friction, related to bedform size. According to this predictor, on average, 97% of the 379 total amount of friction is attributed to form friction in the experiments, indicating that 380 bed composition is less important for hydraulic roughness than bedform geometry. The 381 roughness predictor of Van Rijn (1984) yields on average a Manning's n of 0.030, which is 382 11% lower than the measured friction based on the Law of the Wall. 383

³⁸⁴ 4 Discussion

385

4.1 A shift in transport stage due to addition of fines

The transport stage-based dune height predictor of Venditti and Bradley (2022) pro-386 vides a way to visualize the experimental results and assess deviations from expected heights 387 caused by the sediment mixtures (Figure 11). The predictor implies a parabolic relationship 388 between bedform height and transport stage, as well as confidence levels for data variability (Bradley and Venditti, 2017). The parabolic relation can be interpreted as follows. As the 390 transport stage increases, the transport mode changes from bed load to mixed load (w_s / u^* 391 decreases), and dune height increases. This corresponds to our low and medium-discharge 392 experiments. As the transport stage increases further, bedforms start to become washed-393 out, thus reducing the bedform height. This corresponds to our high-discharge experiments 394 (Yalin, 1972; Nagshband et al., 2014). 395

Although this framework is generally associated with a change in flow strength (Shields 396 number, θ), it can also be used to frame the experimental data using changes in sediment 397 mobility (critical Shields number, θ_c) caused by the addition of fine material to a coarser base 398 sediment (Figure 11). During the medium-discharge experiments, adding non-cohesive fine 399 sand and coarse silt led to an increase in dune height and length. When comparing this to 400 the expected change based on the predictor of Venditti and Bradley (2022) due to a decrease 401 in D_{50} resulting from the addition of fine sediment, the change in bedform geometry was 402 larger than expected. We attribute the increase in bedform size to an increase in mobility of 403 the bed material (i.e. a decrease in θ_c), leading to a larger change in transport stage (Section 404 4.2) than expected based on the change in D_{50} (Supplementary Table S1). Therefore, adding 405 fine, non-cohesive material leads to a shift to the right on the bedform height - transport 406 stage diagram (Figure 11). In contrast, adding fine, weakly cohesive material to the bed 407 decreases the mobility of the sediment (Section 4.3), and therefore decreases the transport 408 stage, resulting in a decrease in bedform size, leading to a shift to the left on the diagram 409 in Figure 11. Furthermore, the large variability in bedform geometry at the high transport 410 stages is attributed to instabilities that occur when the system moves towards upper-stage 411 plane bed (Section 4.4). Finally, the ripples formed at low discharge do not fit within the 412 transport stage diagram, since ripple size is only dependent on grain size and not on flow 413 velocity (Baas, 1994; Baas, 1999; Soulsby et al., 2012). Below, these changes are discussed 414 in more detail. 415

416 417

4.2.1 Hiding-exposure effect

⁴¹⁸ During the medium-discharge experiments, we observed an increase in dune size with ⁴¹⁹ larger fractions of fine non-cohesive material (fine sand and coarse silt) mixed into the base ⁴²⁰ material. This may be attributed to an increased mobility of the coarse sediment. In ⁴²¹ mixed sediments, differently sized grains interact with the flow and with each other in a ⁴²² different way than in equally sized sediments (McCarron et al., 2019), leading to selective ⁴²³ entertainment. This is called the hiding-exposure effect, where small grains are hidden

4.2 Impact of non-cohesive fine sediment (sand and coarse silt)



Figure 11. Conceptual diagram of non-dimensionalized dune height against transport stage, indicating the impact of adding non-cohesive and cohesive fine sediment to the bed material at relatively low transport stages, and the increased variability of bedform height due to flow instabilities at high transport stages. The dark grey shading indicates the 5 and 95-percentiles of data aggregated from Venditti et al. (2016) and Bradley and Venditti (2019). No data are available for the light grey shaded area. The dashed lines show the estimated course of the confidence intervals.

from the flow between the coarser grains. This does not only result in a more difficult mobilization of the fines (hiding), but also in an increased mobility of the larger grains (exposure) (Einstein, 1950) (see Section 4.2.2).

The hiding-exposure effect is mostly dependent on the ratio between the fraction of 427 interest D_i (here, the coarse fraction) and the D_{50} . Hill et al. (2017) tested the influence of 428 this ratio for gravel-sand mixtures. They found that if the two mixed sediments had similar 429 grain sizes, $(D_{coarse} / D_{fines} < 2)$, the bed aggregated without preferentially mobilizing the 430 coarser fraction, and the fines became part of the bed structure (Frings et al., 2008). For 431 intermediate particle ratios (2 < D_{coarse} / D_{fines} < 20), the fine sediment filled or bridged 432 the pores of the coarser base matrix, resulting in increased mobility of the coarse fraction 433 (Section 4.2.2). For large ratios ($D_{coarse} / D_{fines} > 20$), the fine sediment percolated 434 through the base sediment. The subsurface became clogged, but the fines were not present 435 in the surface layer, because all free fines were entrained and transported in suspension. 436

In the present experiments, the ratios between the coarse and fine fractions were 1.5, 437 6.9 and 15 for fine sand, coarse silt and fine silt, respectively. Following Hill et al. (2017), 438 this implies that the fine sand aggregated the bed structure, whereas the coarse and fine silt 439 bridged or filled the pores of the coarse fraction. For the silts, the hiding-exposure effect 440 should have played a role, increasing the mobility of the coarse fraction, whereas, for the fine 441 sand, the increased size distribution might have resulted in increased mobility of the entire 442 sediment bed due to an increase in grain protrusion and a decreased friction angle (Kirchner 443 et al., 1990; Buffington et al., 1992). However, this effect may have been smaller than the 444 mobility increase caused by the hiding-exposure effect by coarse silt, which is indicated by 445 the increased lengthening of dunes in a bed with coarse silt compared to fine sand. Increased 446 mobility means an increased transport stage, hence an increased dune length (Section 4.1). 447

Various methods have been developed to correct the initiation of motion of sediments for the hiding-exposure effect (see McCarron et al. (2019) for a review). Generally, the correction factor lowers the critical Shields number, θ_c , for the coarse fraction $(D_i > D_{50})$, and increases it for the fine fraction $(D_i < D_{50})$. The correction factor, ζ , commonly takes this form (Einstein, 1950; Wilcock, 1993):

$$\zeta = \alpha \left(\frac{D_i}{D_{50}}\right)^{-\beta} \tag{15}$$

where D_i is the grain size of the fraction of interest, β controls the strength of the hiding-exposure effect (Buffington and Montgomery, 1997; McCarron et al., 2019), and $\alpha =$ 1 for sediments with the same density. Exponent β has been approximated using σ_g , as a measure for sorting (Patel et al., 2013; McCarron et al., 2019): $\beta = 0.96$ for $\sigma_g < 2.85$ and $\beta = 2.67e^{-0.37\sigma_g}$ for $\sigma_g \geq 2.85$, where σ_g is determined with equation (4).

Applying this correction factor to the experimental data shows that adding a larger 458 fraction of fine material results in a larger increase in mobility of the coarse material. For 459 example, replacing 50% of the base material by fine sand causes θ_c of the base material to 460 decrease from 0.021 to 0.019 (-11%) and to 0.016 for 50% coarse silt (-31%) (Supplementary 461 Table S1). Applying this adjusted critical Shields number to our data reduces the root-462 mean-square error of the observed normalized dune height by 0.019 (-9%) and 0.032 (-15%) 463 for fine sand and coarse silt, respectively, when evaluated against the predictor of Venditti 464 and Bradley (2022). In contrast, the same adjustment increases the root-mean-square error 465 for the experiments with fine silt by 0.011 (+6%) and causes the variability for the high 466 discharge runs to remain high, with a root-mean-square error of 0.31. These results are 467 discussed in Sections 4.3 and 4.4, respectively. 468

469

4.2.2 The hiding-exposure effect in mixed gravel-sand and sand-silt beds

The hiding-exposure effect is not commonly recognized in studies focused on sand-silt 470 mixtures, and is mainly based on experiments in gravel-sand mixtures. McCarron et al. 471 (2019) described an increase in mobility in gravel-sand experiments based on a decrease 472 in θ_c by 64% compared to well-sorted sediment of a similar size (2.14 mm). Frings et al. 473 (2008) speculated that hiding-exposure could result in a more mobile coarse fraction than 474 a fine fraction in the downstream part of sand-bed rivers. Our observations with sand-silt 475 mixtures show many parallels to gravel-sand mixtures, but on a smaller grain-size scale. 476 We therefore infer from our experiments that the hiding-exposure effect also plays a role in 477 sand-silt mixtures. 478

Mechanisms explaining the increased mobility of gravel in sand-gravel mixtures were 479 suggested by Ikeda (1984) and subsequently built on in later studies (e.g. Li and Komar 480 1986; Whiting et al. 1988; Dietrich et al. 1989; Wilcock 1993; Venditti et al. 2010). Firstly, 481 by filling pores with fine grains, the pivoting angle of large grains is reduced, thus facilitating 482 entrainment (Li and Komar, 1986). Secondly, there is a lower probability that particles in 483 transport are caught in the wake of protruding particles and deposit, since particles protrude 484 less far into the flow. Finally, filling pores with fine material results in a smoother bed, thus 485 resulting in lower drag, which in turn increases the near-bed velocity. These suggestions were built upon by Venditti et al. (2010), who suggested that the infilling of the pores causes 487 dampening of small wakes in the lee of particles, resulting in acceleration of the near-bed 488 flow, which in turn mobilizes the larger particles. Our experimental results suggest that 489 this acceleration of near-bed velocity is reflected in an increase in dune length and height 490 at medium discharge (Figure 9d). 491

The observation that the sediment mobility increases when adding coarse silt to the bed is in line with what can be expected from experiments with gravel-sand mixtures, but opposes previous observations in laboratory experiments with sand-silt mixtures. Bartzke

et al. (2013) and Yao et al. (2022) observed that non-cohesive silt stabilizes the sediment 495 bed, but at different concentrations ($\sim 1.4\%$ silt and >35%, respectively), whereas, in our 496 experiments, even at 50% coarse silt the mobility of the sediment was increased. Interest-497 ingly, Bartzke et al. (2013), whose experiments fall in the range of pore bridging (D_{coarse} / $D_{fines} = 5.5$), explained the filling of pore space as a reason for increased stability of the 499 bed due to reduced hyporheic flow, rather than a reason for increased mobility of the coarse 500 fraction as found in gravel-sand experiments (Section 4.2.1). The reason for these opposing 501 effects could lie in the different experimental setups: the highest flow velocity tested in these 502 experiments was 0.35 m s^{-1} , which is comparable to our lowest flow velocity. It is therefore 503 likely that the supposed stabilizing effect of silt is overruled by a large bed shear stress and 504 the development of bedforms in our experiments. 505

Ma et al. (2020) studied the mobility of silt-sized sediment and the effects of sorting 506 in laboratories and rivers world-wide, and found a high-mobility sediment transport regime 507 related to the size and sorting of the bed sediment. Bed sediments of $D_{50} < 88 \ \mu m$ and 508 poorly sorted sediments within a range of 88 $\mu m < D_{50} < 153 \mu m$ were found to be more 509 mobile than expected from the sediment transport rate equations of Engelund and Hansen 510 (1967), whereas sediments with $D_{50} > 153 \ \mu m$ confirmed these equations. In other words, 511 poorly sorted sediments in the transitional range of very fine to fine sand are more easily 512 mobilized than narrowly distributed sediments. This agrees with equation (15), where the 513 strength of the hiding-exposure effect is related to the sorting of the material. Although 514 Ma et al. (2020) did not explicitly mention the hiding-exposure effect, and related their 515 observation to the change from mixed load to suspended-load dominated transport, the 516 hiding-exposure effect may have played a role to achieve this change. 517

4.3 Impact of weakly cohesive fine silt

518

⁵¹⁹ Contrary to the increase in mobility observed when adding non-cohesive fine material, ⁵²⁰ the mixing of fine silt into the bed reduced both the height and length of the bedforms. ⁵²¹ This can be attributed to the weakly cohesive character of the 17 μ m-sized silt, because ⁵²² cohesive sediments such as clay are known to limit or suppress bedform growth (Schindler ⁵²³ et al., 2015; Parsons et al., 2016) through London-van der Waals forces and by interparticle ⁵²⁴ electrostatic bonding (Mehta, 2014), consequently increasing θ_c .

The fine silt used in our experiments exhibited weakly cohesive properties, confirmed 525 by visual stickiness of slurries of the fine silt and an increased angle of repose. Therefore, 526 fine silt might have imparted similar attractive forces as clay, although to a lesser extent. 527 Schindler et al. (2015) and Parsons et al. (2016) performed experiments with fine sand (D_{50} 528 = 239 μ m) at a mean velocity $u = 0.8 \text{ m s}^{-1}$, and observed an inverse linear relationship 529 between dune height and clay percentage, with a lack of dunes at a clay percentage of 15%. 530 The sharp decline in bedform height with clay content as observed in their experiments, 531 was not evident in the present experiments, and the bed remained mobile up to 30% fine 532 silt. Nevertheless, in the medium-discharge experiments, the dune heights and lengths for 533 fine silt were significantly reduced, as opposed to the increase for coarse silt and fine sand, 534 likely due to decreased mobility of the entire bed. In the low-discharge experiments, the 535 ripple size was reduced too, but, as shown below, this could be a result of decreased grain 536 size rather than decreased mobility. 537

Wu et al. (2022) recorded a decrease in ripple height with increasing clay percentage 538 under wave-current conditions ($D_{coarse} / D_{fines} \sim 51$). Below 11% clay, the clay was win-539 nowed out of the bed, allowing clean-sand ripples of similar size to develop. Above 11%, 540 the cohesiveness of the bed was large enough to limit bed mobility, and only small rip-541 ples formed. In our experiments, this effect did not occur, as even at small percentages of 542 fine silt ($\sim 2\%$) bedform height decreased, as in the current-ripple experiments with mixed 543 clay-sand of Baas et al. (2013). During the medium-discharge experiments, cohesion im-544 peded dune formation, and only small bedforms formed. In the high-discharge experiments, 545

dunes did form, but their planform was more similar to the dunes formed in the mediumdischarge experiments with fine sand and coarse silt than to those in the high-discharge runs (Supplementary Figure S2 and S3), indicating cohesion-induced hampered mobility.

In summary, the formation of relatively small bedforms in our experiments with fine silt can be attributed to reduced mobility, caused by the weakly cohesive properties of fine silt. This effect is less pronounced than in previous experiments with more strongly cohesive clay, in which the mobility was limited more strongly. The decreased mobility leads to an increase in the critical Shields number, and a shift to the left in the transport-stage diagram of Figure 11.

4.4 Instabilities at high discharges

555

The present study shows that any impact of fine sediment on bed geometry at high transport stages is swamped by the inherent variability of dune geometry (Figure 11). This variability encompasses three bed configurations, without any apparent relationship with the type or fraction of fines: a dune-covered bed; a flat bed with one large dune (cf. Saunderson and Lockett (1983) and Naqshband et al. (2016)); and a completely flat bed.

The variability in bedform geometry and the presence of multiple bed configurations 561 have been described before in literature. Saunderson and Lockett (1983) performed experi-562 ments around the transition from dunes to upper-stage plane bed and found four different 563 bed states: asymmetrical dunes; convex dunes; humpback dunes (comparable to the single 564 large dune configuration in this study); and a flat bed. These bedform states were seen to 565 transform into one another. Saunderson and Lockett (1983) dedicated this behavior to the 566 close position of the bed to the phase boundary between dunes and upper-stage plane bed, 567 but did not provide a physical explanation. Venditti et al. (2016) observed three phases in 568 high-velocity experiments: a plane bed with washed-out dunes; a field of large dunes; and 569 a field of small dunes. The water depth, shear stresses and water surface slope co-varied 570 with the changes in bed configuration. During the plane-bed phase, intense localized erosion 571 was followed by the formation of small or large bedforms, which then washed out to form 572 a new flat bed. These cycles lasted from several minutes to more than half an hour, with 573 transitions between individual bedform types happening in seconds or minutes. Similarly, 574 Bradley and Venditti (2019) stated a 'tremendous variability' between bed states at a high 575 transport stage, and reasoned that numerous observations of the bed are needed to get an 576 average bed state that scales with the transport states described by equations (8) and (9). 577

However, none of these studies provided an explanation for the large variability in dune 578 height at high transport stages. de Lange et al. (2023) reanalyzed the data of Venditti et al. 579 (2016) and Bradley and Venditti (2019), and found a bimodal dune height distribution at 580 high transport stages. They attributed this to a critical transition, exhibiting flickering 581 between a high and low alternative stable state. Our current observations support the idea 582 of these alternative stable states. The large variability in bed configurations explains the 583 lack of a predictable succession of bed states with increasing amounts of fine sediment in 584 the current study. This variability is so large that all bed states can occur at any moment, 585 independent of the bed composition. However, the upper stage plane bed condition was 586 not observed in the high-discharge experiments with fine silt, which once again shows a 587 decreased mobility as a result of the cohesiveness of the sediment, leading to a shift to the 588 left on the bedform-transport stage diagram, preventing flattening of the bed. 589

4.5 Ripples at low discharges

Ripples formed in the low discharge experiments. Ripple height and length are a product of the size of the bed material, and are independent of flow velocity (Baas, 1994; Baas, 1999; Soulsby et al., 2012). Therefore, the transport stage framework as suggested above for dunes is not relevant for ripples. The height and width of the ripples, and to a lesser degree their ⁵⁹⁵ length, decreased with an increasing amount of coarse and fine silt. The decrease in height ⁵⁹⁶ is most apparent at silt concentrations above 20%, the same percentage at which the D_{10} ⁵⁹⁷ of the sediment distribution drops considerably (Figure 3).

Adding fine sand to the base material led to a decrease in height of about 15%, a similar 598 decrease as expected based on Soulsby's ripple predictor (equation (10)). This suggests that 599 the change in grain size dominated the change in ripple height, and the hiding-exposure effect 600 was small. However, adding coarse silt to the base material had a larger decreasing effect on 601 height and length than fine sand. In the run with 50% coarse silt, both the height and the 602 length were at, or close to the predicted values of 8 mm and 95 mm, respectively, suggesting 603 that equilibrium was reached in this run. Hence, adding coarse silt increases the development 604 rate of the ripples compared to fine sand. This may be caused by three processes; a) a 605 mobility increase induced by the hiding-exposure effect; b) a shorter equilibrium time for 606 coarse silt ripples at the same Shields stress; c) a larger relative effect of coarse silt than 607 fine sand, as a 50% increase in weight of the finer fraction involves a much larger number of 608 coarse silt than fine sand particles (in the same volume, there are 331 times more coarse silt 609 particles than medium sand particles, as opposed to 3 times for fine sand). Finally, adding 610 fine silt to the base material shows the effect of cohesion by reducing the ripple height. 611 However, the effect of particle size cannot be distinguished with confidence from that of 612 cohesion. The decrease in ripple height with increasing fraction of fine silt is larger than for 613 coarse sand, which might be at least partly caused by the cohesive properties of the fine silt. 614

It should be emphasized that the response of ripples to an increase of fine bed sediment is different from the response of dunes. Whereas dune geometry gets adjusted by the increased mobility of the non-cohesive bed sediment, ripple geometry mainly results directly from the particle size distribution of the material.

619

4.6 The impact of bed sediment on hydraulic roughness

We confirm that for relatively steep dunes, roughness is related to the steepness of the 620 leeside, consistent with findings of Kwoll et al. (2016) and Lefebvre and Winter (2016). At 621 the leeside of the dune, flow separation generates turbulence, resulting in energy dissipation 622 in the turbulent wake, which constitutes the main source of dune-related roughness (Lefebvre 623 et al., 2014; Venditti and Bennett, 2000). In our experiments, the bedforms had on average 624 a leeside angle of 10° with a relatively steep section (mean slip-face angle 20°), resulting in 625 intermittent flow separation (Lefebvre and Cisneros, 2023). The presence of flow separation 626 can also be determined using the defect Reynolds number (Baas and Best, 2000), Re_d (Re_d 627 $=\frac{\Delta u^*}{u}$). In all our experiments, Re_d is far larger than 4.5, which indicates the presence of 628 flow separation (Williams and Kemp, 1971; Best and Bridge, 1992; Gyr and Müller, 1996). 629

Previous research suggested that the composition of the sediment bed has only a small influence on hydraulic roughness (Smith and McLean, 1977). This corresponds with our findings and equation (13) as far as skin friction is concerned; only 3% of the total roughness is attributed to skin friction in the present experiments. However, the bed composition strongly impacts the bed geometry, thereby influencing form roughness.

635

4.7 Wider implications

Our results show that the presence of fines affects sediment mobility, even if the fines only slightly change the D_{50} of the sediment. Therewith, fine material influences bedform properties and hydraulic roughness, which is worth accounting for in bedform size predictors. Moreover, the interaction of fine silt and sand with coarser sand is relevant for channel nourishment aimed at preventing incision (Czapiga et al., 2022).

To adequately determine bedform geometry, some measure of bimodality or sorting may be included in future predictors. This measure could focus on the fine fraction, such as the D_{10} . Additionally, the bed geometries for added fine and coarse silt differ notably, ⁶⁴⁴ if the fine silt fraction is cohesive. Hence, assessing the cohesive properties of silt, such as ⁶⁴⁵ yield stress and viscosity, is crucial, and lumping fines into one fraction, with a cut-off at 63 ⁶⁴⁶ μ m (e.g. Rijn (2020)) is to be avoided.

⁶⁴⁷ 5 Conclusions

654

655

668

669

We performed 52 laboratory experiments, in which the bed composition was varied using three different sediment mixtures (medium sand with fine sand, coarse silt and fine silt) in different ratios, for three different discharges (low, medium, high). We measured the bed morphology at the end of the experiments to assess the effect of bed composition on bedform geometry, and used this to indirectly assess sediment mobility and transport stage. The main conclusions of the research are:

- Bedform response to the addition of fine material depends, amongst others, on transport capacity, bimodality-impacted bed mobility, and cohesion.
- In the dune regime, adding fine sand or coarse silt to medium sand increases the mobility of coarser material. This leads to an increase in transport stage, θ/θ_c , an increase in dune length, and an increase or decrease in dune height, depending on the initial value of θ/θ_c .
- The increase in mobility of medium sand is inferred to be caused by the hidingexposure effect, with the filling of pores by coarse silt leading to a larger near-bed flow velocity. Fine sand is too coarse to fit in the pores, which causes an increase in grain protrusion and a decrease in friction angle, and therefore increased sediment mobility.
- Adding weakly cohesive fine silt to medium sand has a similar effect to adding cohesive clay (Schindler et al., 2015), by causing a decrease in transport stage and inhibiting dune growth.
 - In the ripple regime, adding fine material leads to a decrease in ripple height, which responds directly to the decreased particle size.
- In the transitional regime from dune to upper-stage plane bed, bed geometries may flicker between alternative stable bed states, complicating the relation between bedform height and length and fine sediment fraction.
- The composition of the sediment bed does not significantly influence hydraulic roughness from skin friction drag, but it alters the bed morphology, and thus indirectly changes the hydraulic roughness through form drag.

676 Appendix A Bedform geometry predictors

The dune height and length predictions based on Van Rijn (1984) follow equation (6) and (7) in which T is Van Rijn (1984)'s definition of the transport stage.

$$T_{vRijn} = \frac{(u^*)^2 - (u^*_c)^2}{(u^*_c)^2}$$
(A1)

where u^* is the shear velocity (m s⁻¹), and u_c^* is the critical shear velocity (m s⁻¹). Both the shear velocity and the critical shear velocity are unknown, but can be expressed in known parameters. The shear velocity can be expressed via:

$$u^* = u \frac{g^{0.5}}{C'}$$
 (A2)

in which u is the time and depth-averaged velocity (m s⁻¹) derived from the measurements with the UB-LAB 2C and C' is the grain-related Chézy parameter (m^{0.5} s⁻¹), which can be expressed as:

$$C' = 18\log \frac{12R_h}{3D_{90}}$$
(A3)

- Herein, R_h is the hydraulic radius, which is equal to the cross-sectional area (A) divided by the wetted perimeter (P = width + 2h).
- ⁶⁸⁷ The critical shear velocity can be calculated as:

$$u_c^* = \sqrt{\frac{\tau_c}{\rho_w}} \tag{A4}$$

In turn, the critical shear stress can calculated using the critical Shields number θ_c :

$$\tau_c = \theta_c (\rho_s - \rho_w) g D_{50} \tag{A5}$$

and θ_c is obtained from (Parker et al., 2003):

$$\theta_c = 0.5 \left(0.22 R e_p^{-0.6} + 0.06 * 10^{(-7.7 R e_p^{-0.6})} \right)$$
(A6)

In which the particle Reynolds number, Re_p (-), is defined as:

$$Re_p = D_{50}^{3/2} \frac{\sqrt{\rho_r g}}{\nu} \tag{A7}$$

⁶⁹¹ Venditti and Bradley (2022)'s empirical equation for predicting dune height and length ⁶⁹² can be found in equation (8) and (9). The dimensionless shear stress θ is derived by calcu-⁶⁹³ lating the shear stress τ from the shear velocity (via equation (A4), replacing τ for τ_c). The ⁶⁹⁴ critical shear stress θ_c is calculated via equation (A6).

The geometry of ripples is predicted based on Soulsby et al. (2012) via equation (10) and (11) in which D^* (-) is given by:

$$D^* = D_{50} \left(\frac{g(\frac{\rho_s}{\rho_w} - 1)}{\nu^2} \right)^{1/3}$$
(A8)

⁶⁹⁷ Appendix B Hydraulic roughness determination

For a water column that satisfies equation (12), the equation can be rewritten into:

$$\overline{u}(\sigma_d) = \frac{u^*}{\kappa} (ln(\sigma_d) + 1) + U$$
(B1)

699

688

in which U is the depth-mean velocity, and σ_d is the dimensionless depth using:

$$\sigma_d = \frac{z+h}{h} \tag{B2}$$

The value of u^* can be derived from the slope of a linear regression line through the data points of \overline{u} versus $(\ln(\sigma_d)+1)$. The average velocity $\overline{u}(\sigma_d)$ was determined as the average streamwise velocity during a single measurement. The averaging time window of 30 minutes was narrowed down to cover an integer number of bedforms, defined from top to top. The σ_d -coordinate was defined such that $\sigma_d=0$ coincides with the top of the highest

bedform during a measurement (the 95-percentile of the measured bed elevation was chosen, 705 to exclude outliers as a result of backscatter spikes). The σ_d =1-coordinate is located at the 706 top of the vertical measuring range, which corresponds to the elevation of the UB-Lab-2C 707 transducer. The time-averaged relation between \overline{u} and $ln(\sigma_d)$ was consistently linear at the 708 middle half of the measured profile (between -0.175 $< \sigma_d < -0.625$), so this part of the 709 profile was used for determining u^* (Supplementary Figure S6). The goodness of the linear 710 fit of the log-profiles had on average a R^2 -value of 0.96. Following Hoitink et al. (2009), the 711 roughness length z_0 (m) can be calculated using: 712

$$z_0 = \frac{h}{e^{\left(\frac{\kappa U}{u^*}\right)} + 1} \tag{B3}$$

Finally, Manning's n, n_{man} (s m^{-1/3}) can be calculated in the following steps (Pope, 2000; Chow, 1959):

$$k_b = 30 * z_0 \tag{B4}$$

$$n_{man} = \frac{k_b^{\frac{1}{6}}}{25} \tag{B5}$$

in which k_b is the total roughness height (m).

Roughness height can also be approximated indirectly based on the predictor of Van Rijn (1984) with equation (13), resulting in the dimensionless Darcy-Weisbach friction factor, \hat{f} . Herein, k_s consists of form roughness height k_{sf} and grain roughness height k_{sg} :

$$k_s = k_{sg} + k_{sf} \tag{B6}$$

$$k_{sq} = 3D_{90} \tag{B7}$$

$$k_{sf} = 1.1\gamma_d \Delta (1 - e^{\frac{-25\Delta}{\lambda}}) \tag{B8}$$

where the calibration constant γ_d is taken as 1 in laboratory conditions (Van Rijn, 1984).

The friction factor, \hat{f} , can be converted to Manning's n (n_{man}) via the Chézy coefficient C $(m^{1/2}s^{-1})$ (Manning, 1891; Silberman et al., 1963).

$$C = \frac{R_h^{1/6}}{n_{man}} \tag{B9}$$

$$\hat{f} = \frac{8g}{C^2} \tag{B10}$$

722 **Open Research Section**

The data and code used to generate the results in this study will be made available through the public repository of 4TU upon acceptance, with doi: 10.4121/dde430c4-7f9f-4d7b-bff1-d4792e0031f2.

726 Acknowledgments

SdL and TH were funded by the Netherlands Organization for Scientific Research (NWO), 727 within Vici project "Deltas out of shape: regime changes of sediment dynamics in tide-728 influenced deltas" (Grant NWO-TTW 17062). IN is funded by the Dutch Ministry of 729 Infrastructure and Water under the research program "Rivers2Morrow". This work is based 730 on the MSc thesis of SV and JL. We would like to thank Maarten Kleinhans and Jeremy 731 Venditti for their help with data interpretation, Nick Wallerstein for the technical and 732 practical help in the laboratory, and finally all fellow colleagues that helped shovelling 733 sediment in and out of the flume. 734

735 **References**

751

752

753

- Allen, J. R.L. (1978). "Computational models for dune time-lag: calculations using Stein's rule for dune height". In: *Sedimentary Geology* 20.C, pp. 165–216. ISSN: 00370738. DOI: 10.1016/0037-0738(78)90054-4.
- ASCE Task Force (2002). "Flow and transport over dunes". In: Journal of Hydraulic Engineering 127, pp. 726–728.
- Baas, J.H. and H. de Koning (1995). "Washed-Out Ripples: Their Equilibrium Dimensions, Migration Rate, and Relation to Suspended-Sediment Concentration in Very Fine Sand". In: SEPM Journal of Sedimentary Research Vol. 65A. ISSN: 1527-1404.
 DOI: 10.1306/D42680E5-2B26-11D7-8648000102C1865D.
- Baas, Jaco H. (1994). "A flume study on the development and equilibrium morphology of current ripples in very fine sand". In: Sedimentology 41.2, pp. 185–209. ISSN: 13653091.
 DOI: 10.1111/j.1365-3091.1994.tb01400.x.
- (Feb. 1999). "An empirical model for the development and equilibrium morphology of current ripples in fine sand". In: *Sedimentology* 46.1, pp. 123–138. ISSN: 00370746.
 DOI: 10.1046/j.1365-3091.1999.00206.x.
 - Baas, Jaco H. and James L. Best (Aug. 2000). "Ripple formation induced by biogenic mounds—comment". In: *Marine Geology* 168.1-4, pp. 145–151. ISSN: 00253227. DOI: 10.1016/S0025-3227(00)00040-2.
- Baas, Jaco H., Alan G. Davies, and Jonathan Malarkey (Jan. 2013). "Bedform development in mixed sand-mud: The contrasting role of cohesive forces in flow and bed". In: *Geomorphology* 182, pp. 19–32. ISSN: 0169555X. DOI: 10.1016/j.geomorph.2012.10
 .025.
- Bartzke, Gerhard et al. (2013). "On the stabilizing influence of silt on sand beds". In: Journal of Sedimentary Research 83.8, pp. 691–703. ISSN: 15271404. DOI: 10.2110/jsr.2013
 .57.
- Berg, J.H. van den and A. van Gelder (1993). "A new bedform stability diagram, with
 emphasis on the transiton of ripples to plane bed in flows over fine sand and silt". In:
 Spec. Publs Int. Ass. Sediment 17, pp. 11–21.
- Best, Jim (2005). "The fluid dynamics of river dunes: A review and some future research directions". In: Journal of Geophysical Research: Earth Surface 110.4, pp. 1–21. ISSN: 21699011. DOI: 10.1029/2004JF000218.
- Best, Jim and John Bridge (1992). "The morphology and dynamics of low amplitude bedwaves upon upper stage plane beds and the preservation of planar laminae". In: Sed-*imentology* 39.5, pp. 737–752. ISSN: 13653091. DOI: 10.1111/j.1365-3091.1992
 .tb02150.x.
- Bradley, Ryan W. and Jeremy G. Venditti (Feb. 2017). Reevaluating dune scaling relations.
 DOI: 10.1016/j.earscirev.2016.11.004.
- (2019). "Transport Scaling of Dune Dimensions in Shallow Flows". In: Journal of Geophysical Research: Earth Surface 124.2, pp. 526–547. ISSN: 21699011. DOI: 10.1029/ 2018JF004832.
- Buffington, John M., William E. Dietrich, and James W. Kirchner (Feb. 1992). "Friction
 angle measurements on a naturally formed gravel streambed: Implications for crit-

778	ical boundary shear stress". In: Water Resources Research 28.2, pp. 411–425. ISSN:
779	00431397. DOI: 10.1029/91WR02529.
780	Buffington, John M. and David R. Montgomery (Aug. 1997). "A systematic analysis of eight
781	decades of incipient motion studies, with special reference to gravel-bedded rivers".
782	In: Water Resources Research 33.8, pp. 1993–2029. ISSN: 00431397. DOI: 10.1029/
783	96WR03190.
784	Chow, V.T. (1959). Open-channel hydraulics. McGraw-Hill Book Company, USA. ISBN:
785	ISBN 0-07- 085906-X.
786	Czapiga, Matthew J., Astrid Blom, and Enrica Viparelli (June 2022). "Sediment Nourish-
787	ments to Mitigate Channel Bed Incision in Engineered Rivers". In: Journal of Hydraulic
788	Engineering 148.6. ISSN: 0733-9429. DOI: 10.1061/(ASCE)HY.1943-7900.0001977.
789	Dade, W. Brian and Peter F. Friend (Nov. 1998). "Grain-Size, Sediment-Transport Regime,
790	and Channel Slope in Alluvial Rivers". In: The Journal of Geology 106.6, pp. 661–676.
791	ISSN: 0022-1376. DOI: 10.1086/516052.
792	de Lange, S.I. et al. (Dec. 2023). "Alternative stable river bed states at high flow". In: ESS
793	Open Archive. DOI: 10.22541/essoar.170317282.22054327/v1.
794	Dietrich, William E. (Dec. 1982). "Settling velocity of natural particles". In: Water Re-
795	sources Research 18.6, pp. 1615–1626. ISSN: 00431397. DOI: 10.1029/WR018i006p01615.
796	Dietrich, William E. et al. (July 1989). "Sediment supply and the development of the coarse
797	surface layer in gravel-bedded rivers". In: Nature 340.6230, pp. 215–217. ISSN: 0028-
798	0836. DOI: 10.1038/340215a0.
799	Einstein, H. A. (1950). "The bed-load function for sediment transportation in open chan-
800	nel flows". In: Technical Bulletins 156389. United States Department of Agriculture.
801	Economic Research Service.
802	Engelund, F. and E. Hansen (1967). "Monograph on Sediment Transport". In: Technisk
803	Forlag. Copenhagen. Denmark.
804	Ferguson, R I and M Church (2004). A simple universal equation for grain settling velocity.
805	Tech. rep. 6. pp. 933-937. URL: http://pubs.geoscienceworld.org/sepm/isedres/
806	article-pdf/74/6/933/2821499/933.pdf.
807	Frings, Roy M., Maarten G. Kleinhans, and Stefan Vollmer (Dec. 2008). "Discriminating
808	between pore-filling load and bed-structure load: A new porosity-based method, ex-
809	emplified for the river Rhine". In: Sedimentology 55.6, pp. 1571–1593. ISSN: 13653091.
810	DOI: 10.1111/j.1365-3091.2008.00958.x.
811	Greene, H. Gary, Matthew Baker, and John Aschoff (2020). "A dynamic bedforms habitat
812	for the forage fish Pacific sand lance, San Juan Islands, WA, United States". In: Seafloor
813	Geomorphology as Benthic Habitat. Elsevier, pp. 267–279. DOI: 10.1016/B978-0-12
814	-814960-7.00014-2.
815	Gyr, A. and A. Müller (1996). "The role of coherent structures in developing bedforms
816	during sediment transport". In: Coherent flow structures in open channels, pp. 227-
817	235.
818	Healy, T., Y. Wang, and J.A. Healy (2002). Muddy Coasts of the World: Processes. Deposits
819	and Function. 1st ed. Amsterdam: Elsevier.
820	Hill, Kimberly M. et al. (Jan. 2017). "Experimental study of the effect of grain sizes in a
821	bimodal mixture on bed slope, bed texture, and the transition to washload". In: Water
822	Resources Research 53.1, pp. 923–941. ISSN: 19447973. DOI: 10.1002/2016WR019172.
823	Hoitink, A. J.F., F. A. Buschman, and B. Vermeulen (2009). "Continuous measurements of
824	discharge from a horizontal acoustic Doppler current profiler in a tidal river". In: Water
825	Resources Research 45.11, pp. 1–13, ISSN: 00431397, DOI: 10.1029/2009WR007791.
826	Hurther, D. and U. Lemmin (2001). "A Correction Method for Turbulence Measurements
827	with a 3D Acoustic Doppler Velocity Profiler". In: Journal of Atmospheric and Oceanic
828	Technology, pp. 446–458, DOI: https://doi.org/10.1175/1520-0426(2001)
829	018<0446:ACMFTM>2.0.CD;2.
830	Ikeda, H. (1984). "Flume experiments on the superior mobility of sediment mixtures". In:
831	Ann. Rep. Inst. Geosci. 10. Univ. of Tsukuba. Tsukuba. Japan. pp. 53–56.
	· · · · · · · · · · · · · · · · · · ·

832	Karim, F. (1995). "Bed configuration and hydraulic resistance in alluvial-channel flows". In:
833	Journal of Hydraulic Engineering 121.1, pp. 15–25.
834	Kirchner, JAMES W. et al. (Aug. 1990). "The variability of critical shear stress, friction an-
835	gle, and grain protrusion in water-worked sediments". In: Sedimentology 37.4, pp. 647–672, ISSN: 0037-0746, DOI: 10.1111/j.1365-3091.1990, tb00627.x
927	Kwoll E et al (Mar 2016) "Flow structure and resistance over subaquaeous high- and
030	low-angle dunes" In: Journal of Geophysical Research: Earth Surface 121.3 pp. 545-
838	564 ISSN: 21600011 DOI: https://doi.org/10.1002/2015 IE003637
839	Lafabura Alice and Julia Cigneros (July 2023) "The influence of dune les side shape on
840	time averaged velocities and turbulence" In: Earth Surface Duramice 11.4, pp. 575-
841	591. ISSN: 2196-632X. DOI: 10.5194/esurf-11-575-2023.
843	Lefebvre, Alice, Andries J. Paarlberg, and Christian Winter (Feb. 2014). "Flow separation
844	and shear stress over angle-of-repose bed forms: A numerical investigation". In: Water
845	Resources Research 50.2, pp. 986–1005. ISSN: 00431397. DOI: 10.1002/2013WR014587.
846	Lefebvre, Alice and Christian Winter (2016). "Predicting bed form roughness: the influence
847	of lee side angle". In: Geo-Marine Letters 36.2, pp. 121–133. ISSN: 14321157. DOI:
848	10.1007/S00307-010-0430-0.
849	for applications to calculate antrainment of gravel in a summent. In: <i>Codimental care</i> 22.2
850	for applications to selective entrainment of graver in a current \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in the selective entrainment of graver in a current \cdot in the selective entrainment of graver in the selective entrainment of graver in a current \cdot in the selective entrainment of graver in the selective entrainmen
851	pp. 415-425. ISSN: 0057-0740. DOI: 10.1111/j.1305-3091.1980.tb00545.X.
852	tener, Every La State Velley, Chine, Chine, La Colones, Advances, 25, pp. 1, 8, 1999
853	22752548 DOI: 10.1106 (acia day 1602114)
854	Ma Hongho et al. (2020). "Universal relation with regime transition for addiment transport
855	in fine graphed rivers" In: Precedings of the National Academy of Sciences of the
856	United States of America 117.1 pp. 171–176 ISSN: 10016400 DOI: 10. 1072/pp.
857	1011025116
858	Manning R (1801) "On the flow of water in open channels and pipes" In: Transactions
859	of the Institution of Civil engineers of Ireland
860	Mark C E van der and A Blom (2007) A new and widely annlicable tool for determining
801	the geometric properties of hedforms Tech rep. University of Twente
002	McCarron Connor I et al (Apr 2019) "The hiding-exposure effect revisited: A method to
864	calculate the mobility of bimodal sediment mixtures" In: Marine Geology 410 pp 22–
265	31 ISSN: 00253227 DOI: 10.1016/j margeo 2018.12.001
865	Mehta A.I. (2014) An Introduction to Hudraulics of Fine Sediment Transport Ed by N. I.
867	Hackensack World Scientific
868	Mignot E. D. Hurther and E. Bartelemy (Nov. 2009) "On the structure of shear stress and
860	turbulent kinetic energy flux across the roughness layer of a gravel-bed channel flow"
970	In: Journal of Fluid Mechanics 638 pp 423–452 ISSN: 0022-1120 DOI: 10 1017/
971	S0022112009990772
972	Nagshband S. J.S. Ribberink and S.J.M.H. Hulscher (2014) "Using both free surface effect
873	and sediment transport mode parameters in defining the morphology of river dunes
874	and their evolution to upper stage plane beds" In: Journal of Hudraulic Engineering
875	140.6 pp 1–6 ISSN: 19437900 DOI: 10.1061/(ASCE)HY 1943–7900.0000873
876	Nagshband S et al (2016) "Modeling river dune development and dune transition to upper
877	stage plane bed". In: Earth Surface Processes and Landforms 41.3, pp. 323–335, ISSN:
878	10969837 DOI: 10.1002/esp.3789
879	Parker, Garv et al. (2003), "Effect of Floodwater Extraction on Mountain Stream Morphol-
880	ogy". In: Journal of Hudraulic Engineering 129.11. pp. 885–895. ISSN: 0733-9429. DOI:
881	10.1061/(asce)0733-9429(2003)129:11(885)
882	Parsons, Daniel R. et al. (2016). "The role of biophysical cohesion on subaqueous bed form
883	size". In: Geophysical Research Letters 43.4. pp. 1566–1573. ISSN: 19448007 DOI: 10
884	.1002/2016GL067667.
885	Patel, Shaileshkumar B, Prem Lal Patel, and Prakash Devidas (2013). Threshold for initi-
886	ation of motion of unimodal and bimodal sediments. Tech. rep. 1, pp. 24–33.

-29-

- Perillo, Mauricio M., James L. Best, and Marcelo H. Garcia (2014). "A new phase diagram for combined-flow bedforms". In: *Journal of Sedimentary Research* 84.4, pp. 301–313.
 ISSN: 15271404. DOI: 10.2110/jsr.2014.25.
- Pope, Stephen B (2000). *Turbulent Flows*. Cambridge University Press.

897

898

899

900

901 902

903

904

905

906

907

908

909

910

914

915

916

921

922

923

- Prokocki, Eric W. et al. (June 2022). "The morphology of fluvial-tidal dunes: Lower Columbia
 River, Oregon/Washington, USA". In: *Earth Surface Processes and Landforms* 47.8,
 pp. 2079–2106. ISSN: 10969837. DOI: 10.1002/esp.5364.
- Rijn, Leo C. van (Jan. 2020). "Erodibility of Mud–Sand Bed Mixtures". In: Journal of Hydraulic Engineering 146.1. ISSN: 0733-9429. DOI: 10.1061/(asce)hy.1943-7900
 .0001677.
 - Ruijsscher, T.V. de et al. (2018). "Application of a Line Laser Scanner for Bed Form Tracking in a Laboratory Flume". In: Water Resources Research 54.3, pp. 2078–2094. ISSN: 19447973. DOI: 10.1002/2017WR021646.
 - Saunderson, Houston C and Francis P J Lockett (1983). "Flume experiments on bedforms and structures at the dune-plane bed transition". In: Spec Publs. int. Ass Sediment 6, pp. 49–58.
 - Schindler, Robert J. et al. (2015). "Sticky stuff: Redefining bedform prediction in modern and ancient environments". In: *Geology* 43.5, pp. 399–402. ISSN: 19432682. DOI: 10 .1130/G36262.1.
 - SICK (2012). Ranger E/D reference manual MultiScan 3D camera with Gigabit Ethernet (E), 3D camera with Gigabit Ethernet (D). Tech. rep. Waldkirch, Germany: SICK Sensor Intelligence.
 - Silberman, E. et al. (1963). "Friction factors in open channels". In: J. Hydraul. Eng. 89.HY2, pp. 97–143.
- Smith, J. Dungan and S. R. McLean (Apr. 1977). "Spatially averaged flow over a wavy surface". In: *Journal of Geophysical Research* 82.12, pp. 1735–1746. ISSN: 01480227. DOI: 10.1029/JC082i012p01735.
 - Soulsby, R. L., R. J.S. Whitehouse, and K. V. Marten (Apr. 2012). "Prediction of timeevolving sand ripples in shelf seas". In: *Continental Shelf Research* 38, pp. 47–62. ISSN: 02784343. DOI: 10.1016/j.csr.2012.02.016.
- Southard, John B and Lawrence A Boguchwal (1990). "Bed configurations in steady unidirectional water flows, part 2. Synthsis of flume data." In: 60.5, pp. 658–679.
- Van Rijn, L.C. (1984). "Sediment transport, part III: Bedforms". In: Journal of Hydraulic Engineering 110.12, pp. 1733–1754.
 - Venditti, J. G. et al. (July 2010). "Mobilization of coarse surface layers in gravel-bedded rivers by finer gravel bed load". In: Water Resources Research 46.7. ISSN: 19447973. DOI: 10.1029/2009WR008329.
- Venditti, Jeremy G. and Sean J. Bennett (Sept. 2000). "Spectral analysis of turbulent flow and suspended sediment transport over fixed dunes". In: *Journal of Geophysical Research: Oceans* 105.C9, pp. 22035–22047. ISSN: 0148-0227. DOI: 10.1029 / 2000JC900094.
- Venditti, Jeremy G. and Ryan W. Bradley (Jan. 2022). "Bedforms in Sand Bed Rivers".
 In: *Treatise on Geomorphology*. Elsevier, pp. 222–254. ISBN: 9780128182352. DOI: 10
 .1016/B978-0-12-409548-9.12519-9.
- Venditti, Jeremy G., C. Y. Martin Lin, and Moslem Kazemi (June 2016). "Variability in
 bedform morphology and kinematics with transport stage". In: Sedimentology 63.4,
 pp. 1017-1040. ISSN: 13653091. DOI: 10.1111/sed.12247.
- Warmink, J. J. et al. (2013). "Quantification of uncertainty in design water levels due to uncertain bed form roughness in the Dutch river Waal". In: *Hydrological Processes* 27.11, pp. 1646–1663. ISSN: 08856087. DOI: 10.1002/hyp.9319.
- Whiting, P.J. et al. (1988). "Bedload sheets in hetrogeneous sediment". In: *Geology* 16.2, pp. 105–108. DOI: https://doi.org/10.1130/0091-7613(1988)016{\%}3C0105:
 BSIHS{\%}3E2.3.C0;2.

- Wilcock, Peter R. (Apr. 1993). "Critical Shear Stress of Natural Sediments". In: Journal of Hydraulic Engineering 119.4, pp. 491–505. ISSN: 0733-9429. DOI: 10.1061/(ASCE) 0733-9429(1993)119:4(491).
- Williams, Philip B. and Patrick H. Kemp (Apr. 1971). "Initiation of Ripples on Flat Sedi ment Beds". In: *Journal of the Hydraulics Division* 97.4, pp. 505–522. ISSN: 0044-796X.
 DOI: 10.1061/JYCEAJ.0002932.
- Wolanski, Eric (2007). Estuarine Ecohydrology. Elsevier Science. ISBN: 9780444530660. DOI:
 10.1016/B978-0-444-53066-0.X5001-6.
- Wu, Yongsheng et al. (2022). "Tidal propagation in the Lower Fraser River, British Columbia, Canada". In: *Estuarine, Coastal and Shelf Science* 264.November 2021, p. 107695. ISSN:
 02727714. DOI: 10.1016/j.ecss.2021.107695. URL: https://doi.org/10.1016/j
 .ecss.2021.107695.
- Yalin, M.S. (1964). "Geometrical Properties of Sand Wave". In: Journal of Hydraulic Engineering 90, pp. 105–119.
- ⁹⁵⁴ (1972). Mechanics of Sediment Transport. Oxford: Pergamon Press.
- Yao, Peng et al. (Sept. 2022). "Erosion Behavior of Sand-Silt Mixtures: Revisiting the Ero sion Threshold". In: Water Resources Research 58.9. ISSN: 19447973. DOI: 10.1029/
 2021WR031788.

Fine sediment in mixed sand-silt environments impact bedform geometry by altering sediment mobility

S.I. de Lange¹, I. Niesten¹, S.H.J. van de Veen¹, J.H. Baas², J. Lammers¹, K. Waldschläger¹, D. Boelee¹, A.J.F. Hoitink¹

¹Wageningen University, Department of Environmental Sciences, Hydrology and Environmental Hydraulics, Wageningen, the Netherlands ²School of Ocean Sciences, Bangor University, Menai Bridge, United Kingdom

Key Points:

1

2

3

4

5

6

8

9	• Adding finer, non-cohesive material to a sand bed increases the mobility of the
10	sand, resulting in an increased dune length.
11	• Adding finer, weakly-cohesive silt to a sand bed, decreases the mobility of the sand,
12	which hampers dune formation and growth.
13	• Sediment bed composition does not directly impact total hydraulic roughness, but
14	indirectly affects it via altering the bed morphology.

Corresponding author: Sjoukje de Lange, sjoukje.delange@wur.nl

15 Abstract

Geometric characteristics of subaqueous bedforms, such as height, length and leeside an-16 gle, are crucial for determining hydraulic form roughness and interpreting sedimentary 17 records. Traditionally, bedform existence and geometry predictors are primarily based 18 on uniform, cohesionless sediments. However, mixtures of sand, silt and clay are com-19 mon in deltaic, estuarine, and lowland river environments, where bedforms are ubiqui-20 tous. Therefore, we investigate the impact of fine sand and silt in sand-silt mixtures on 21 bedform geometry, based on laboratory experiments conducted in a recirculating flume. 22 We systematically varied the content of sand and silt for different discharges, and uti-23 lized a UB-Lab 2C (a type of acoustic Doppler velocimeter) to measure flow velocity pro-24 files. The final bed geometry was captured using a line laser scanner. Our findings re-25 veal that the response of bedforms to an altered fine sediment percentage is ambiguous, 26 and depends on, among others, bimodality-driven bed mobility and sediment cohesive-27 ness. When fine, non-cohesive material (fine sand or coarse silt) is mixed with the base 28 material (medium sand), the hiding-exposure effect comes into play, resulting in enhanced 29 mobility of the coarser material and leading to an increase in dune height and length. 30 However, the addition of weakly-cohesive fine silt reduces the mobility, suppressing dune 31 height and length. Finally, in the transition from dunes to upper stage plane bed, the 32 bed becomes unstable and bedform heights vary over time. The composition of the bed 33 34 material does not significantly impact the hydraulic roughness, but mainly affects roughness via the bed morphology, especially the leeside angle. 35

³⁶ Plain Language Summary

Underwater bedforms, such as dunes, are often found on the bed of rivers and deltas. 37 These rhythmic undulations have specific shapes and sizes, and they affect how water 38 flows. When the bed of the river is made up of sand, we can predict the dune height and 39 length. However, mixtures of different-sized sediments are common in rivers, and it is 40 unknown how this impacts the geometry of the dunes. Therefore, we did experiments 41 in a flume, a laboratory facility to simulate a river, and we tested different sediment bed 42 mixtures. We found that adding non-cohesive fine particles to the base material caused 43 the base material to be more mobile, leading to longer dunes. However, when adding weakly-44 cohesive fine particles, the effect was the opposite, and the dunes became shorter due 45 to the limited mobility of the sediment. Finally, we observed that under high flow con-46 ditions, the bed became unstable and different dune shapes occurred. We found that the 47 friction the water experiences is not directly impacted by the sediment bed mixtures, but 48 is mostly affected by the shape of the bedforms. 49

50 1 Introduction

River bedforms are ubiquitous in low-land rivers, and they are known to impact the river 51 by altering its hydraulics, ecology, and sediment balance. The geometry of river bedforms, 52 especially dunes, impacts the fairway depth (ASCE Task Force, 2002; Best, 2005), adds to 53 the form roughness of the river bed (Warmink et al., 2013; Venditti and Bradley, 2022), and 54 determines suitable foraging places for fish (Greene et al., 2020). It is therefore useful to 55 predict the geometry of bedforms without having to perform regular field measurements. In 56 non-supply limited conditions, river dunes may scale with flow depth (Allen, 1978). However, 57 more recent studies have reinstated the observations by Yalin (1964), Van Rijn (1984), 58 and Karim (1995), indicating a relation between bedform geometry and some measure of 59 transport stage (Bradley and Venditti, 2019; Venditti and Bradley, 2022), where transport 60 stage represents the ratio between flow strength and the mobility of the bed material. Dune 61 length increases with transport stage, while dune height increases with transport stage until 62 a maximum is reached, whereafter the height decreases and the bedforms start to wash out 63 (Baas and Koning, 1995; Bradley and Venditti, 2019). This framework effectively predicts 64

dune height and length, despite considerable variability, which can be up to two-orders of magnitude (Bradley and Venditti, 2017). This variability may in part be attributed to the influence of bed composition on bedform geometry.

The bed composition, i.e. the grain size distribution of the bed sediment, is one of 68 the primary determinants for bedform existence and size. Measures of grain size appear 69 in almost all existing phase diagrams (Southard and Boguchwal, 1990; Berg and Gelder, 70 1993; Perillo et al., 2014), with the median grain size D_{50} as general parameterization. 71 However, this simplification poses challenges when dealing with natural sediment mixtures 72 73 characterized by complex, multimodal sediment size distributions, which are common in deltaic, estuarine and coastal environments featuring sediment mixtures of mud (i.e. clay 74 and silt) and sand (Healy et al., 2002). 75

Recent research has focused on understanding how cohesive clay affects bedform geometry. It has been observed that even a small percentage of cohesive clay in sand-clay mixtures
can effectively suppress bed mobility, resulting in a reduced bedform height (Schindler et al.,
2015; Parsons et al., 2016) and limited bedform growth (Wu et al., 2022). It is, however,
unknown what the impact of non- and weakly cohesive fine materials (silts and fine sands)
is on dune morphology, despite their abundance in downriver environments.

A few studies explored the influence of silt on erodibility of the sediment bed. For 82 instance, Bartzke et al. (2013) examined the behavior of sand (300 μ m)-silt (50 μ m) beds 83 in an annular laboratory flume. They found that an increasing silt content, even at low 84 percentages (as little as 0.18% silt), contributed to bed stabilization through a reduction 85 in water inflow, attributed to pore-space plugging by silt. Yao et al. (2022) also reported 86 increased stability (i.e., increased erosion threshold) with increasing silt content in their 87 laboratory experiments, although stabilization only occurred at a silt content of >35%, 88 when a stable silt skeleton could be formed. Opposing Bartzke et al. (2013), a change in 89 bed stability was not observed at lower silt contents. 90

Additionally, Ma et al. (2017) and Ma et al. (2020) studied a silt-rich sediment bed 91 $(D_{50} = 15 - 150 \ \mu m)$ with low dunes in the Yellow River. Ma et al. (2020) showed that 92 the presence of fine sediment (silt) led to a shift from a low-efficiency sediment transport 93 regime (following the Engelund-Hansen equations (Engelund and Hansen, 1967)) to a high-94 efficiency regime. The high-efficiency regime prevailed for sediment beds with a medium 95 grain size smaller than 88 μ m, and, in the transitional range (88 μ m < D₅₀ < 153 μ m), 96 the existence of this regime depended on sorting of the material $(\sqrt{D_{84}/D_{16}})$. They argued 97 that the shift from a low- to a high-efficiency transport regime resulted from the transition 98 from mixed load to suspended sediment transport, caused by the presence of silt. 99

Yet, none of these studies discussed the potential impact of silt content on bedforms. 100 This is an important research gap, because an increase in bed stability, as observed by 101 Bartzke et al. (2013) and Yao et al. (2022), could theoretically reduce bedform formation 102 and growth due to a decrease in sediment transport, whilst Ma et al. (2020)'s suspension-103 load dominated high-efficiency regime would also mean suppression of bedform formation 104 and growth, but then because bedload transport gets increasingly replaced by suspended 105 load transport, which is incapable of forming bedforms. Clearly, the effect of silt in sand-silt 106 mixtures on the resulting bedform geometry is largely unexplored. Therefore, our research 107 seeks to address the following question: What is the influence of the fraction non-cohesive 108 and weakly cohesive fine sediment in sand-silt mixtures on the dynamic equilibrium bedform 109 geometry and the resulting hydraulic roughness? 110

To answer this question, we conducted 52 laboratory experiments in a recirculating flume, in which the influence of fine sand and silt percentage in sand-silt mixtures on bedform geometry was studied. For three flow velocities, three different sediment mixtures, largely falling within the studied range of Ma et al. (2020), were tested by systematically mixing various fractions of fine sand, coarse silt and fine silt with a coarser base material of



Figure 1. Schematic drawing of the experimental setup. The flume recirculates both water and sediment.

medium sand. These experiments allowed us to assess how different sizes of fine sediment 116 in a sand-silt mixture affect the transport stage and the resulting bedform geometry under 117 different flow conditions. In the following sections, we provide a detailed description of the 118 experimental setup, after which we discuss the different equilibrium bedform geometries 119 that resulted from the experiments. We argue that the hiding-exposure effect enhances the 120 mobility of the coarser fraction, whereas cohesion from fine silt decreases the bed mobility, 121 leading to deviations from the expected relationship between transport stage and bedform 122 dimensions. 123

124 2 Methods

125

2.1 Experimental setup

The experiments were conducted in a tilting flume with recirculation facilities for both 126 water and sediment in the Kraijenhoff van de Leur Laboratory for Water and Sediment 127 Dynamics of Wageningen University and Research (Figure 1 and 2). The flume has an 128 internal width of 1.20 m, a length of 14.4 m, and a height of 0.5 m. The water level is 129 controlled by adjusting a downstream weir. A diffuser (Figure 2a) at the upstream part 130 ensures that the inflow is distributed over the entire width of the flume. The diffuser is 131 followed by a stacked pile of PVC tubes that serve as a laminator, suppressing turbulence 132 at the inflow section. At the end of the flume, a funnel was installed to channel bedload 133 material to a lower reservoir (Figure 1), and to prevent deposition in front of the weir. A 134 continuously running sediment scraper ensures that the sediment stays in suspension in the 135 lower reservoir, upon being pumped back to the inflow of the flume. At the end of one 136 experiment (35% fine sand, medium discharge) the sediment funnel was clogged and the 137 sediment was not fully recirculated. This run was excluded from the analysis. 138

The flow depth was set to 15 cm, measured from the initial flat sediment bed, and it was kept the same for all experimental runs by adjusting the weir height. The slope was set to 0.01 m m⁻¹. Experimental runs were performed for different discharges (low: 45 L s⁻¹; medium: 80 L s⁻¹; high: 100 L s⁻¹), to be able to distinguish the effects of different trans-


Figure 2. Pictures of the laboratory flume and the instrumentation. a) Flume with flatbed, facing upstream, including the upstream-located diffuser. b) Bed covered with small bedforms, facing downstream, including the downstream-located weir. c) UB-Lab 2C flow velocity profiler. d) Dune-covered bed, facing upstream. e) Dune-covered bed, facing downstream, with the UB-Lab 2C in background. f) Line laser scanner.

port stages on bedform morphology. The discharge was monitored and regulated with an 143 electromagnetic flow meter. The corresponding calculated width- and depth-averaged flow 144 velocities were 0.25, 0.44 and 0.56 m s⁻¹, the corresponding depth-averaged flow velocities 145 in the middle of the flume (measured with an UB-Lab 2C, see section 2.2) were slightly 146 larger due to a side-wall effect (0.30, 0.45 and 0.58 m s⁻¹, respectively). The experiments 147 were run for 12, 5 and 3 hours for the low, medium, and high discharges, respectively. Based 148 on the ripple size predictor of Soulsby et al. (2012), the medium-sand ripples formed in the 149 low-discharge experiments reached about 80% of their equilibrium height and length after 150 12 hours. Their planform at this development stage was linguoid, which agrees with the 151 planform predicted by ripple development model of Baas (1999). Nagshband et al. (2016) 152 studied the dune equilibrium time for medium sand (290 μ m). Their equilibrium dimen-153 sions were reached after 3 hours for the experiments with a flow velocity of 0.64 m s^{-1} and 154 after 1.5 hours for 0.80 m s^{-1} . This suggests that the dunes formed at medium and high 155 discharges in the present experiments reached equilibrium size. 156

The flow was sub-critical and turbulent during all experiments, determined by the Froude number, Fr (-), being smaller than 1 (0.30, 0.54 and 0.69, respectively) and the Reynolds number, Re (-), being larger than 4000 (38000, 67000, 83000, respectively), calculated with:

$$Fr = \frac{u}{\sqrt{gh}} \tag{1}$$

$$Re = \frac{hu}{\nu} \tag{2}$$

where u is the time and depth-averaged flow velocity (m s⁻¹), g is the gravitational acceleration (9.81 m s⁻²), h is the water depth (0.15 m), and ν is the kinematic viscosity (m² s⁻¹), which is weakly dependent on water temperature, t (°C), as $\nu = 4 * 10^{-5}/(20+t)$. Here, $\nu = 1.05 * 10^{-6}$ m² s⁻¹ for 18 °C is used.



Figure 3. a) Grain-size distributions of the sediments used in the experiments. b) D_{10} , D_{50} and D_{90} of the tested mixtures, in which the finer material (fine sand, coarse silt or fine silt) is mixed with the base material (medium sand).

A sediment bed with a thickness of 0.10 m was applied, which consisted of a mixture of 165 two grain sizes: a base sediment of medium sand (median size, $D_{50} = 256 \ \mu$ m), mixed with 166 fine sand $(D_{50} = 170 \ \mu\text{m})$, coarse silt $(D_{50} = 37 \ \mu\text{m})$ or fine silt $(D_{50} = 17 \ \mu\text{m})$ (Figure 3a 167 and Supplementary Figure S1 for images of the sediment). All sediments were composed of 168 silica (SiO_2) . The particle size distribution of the original sediments was measured with a 169 Mastersizer 3000 (Figure 3). The fine sand and coarse silt are non-cohesive, whereas the fine 170 silt could be classified as weakly-cohesive (Wolanski, 2007), confirmed by visual observation 171 of the sticky fine silt slurry and a significantly higher submerged angle of repose (40° instead 172 of 30° for sand). No visible flocculation of the silt fraction occurred during the experiments. 173

The weight percentage of finer material mixed with the base material ranged from 0 to 175 100 wt% for fine sand, to 51 wt% for coarse silt (with 49 wt% medium sand) and to 30 wt% 176 for fine silt (with 70 wt% medium sand). In total, 17 different mixtures were tested, which 177 were all exposed to the low, medium and high discharge. In Table 1, an overview of the 178 experimental mixtures is given. The D_{50} and 90th-percentile, D_{90} , values of the mixtures 179 hardly changed when adding finer material, but the 10th-percentile, D_{10} , values dropped 180 significantly when adding coarse or fine silt (Figure 3b).

2.2 Instrumentation

181

A line laser and 3D camera (Figure 2f), equipped with Gigabit Ethernet (SICK, 2012), was used to scan the bed topography. The devices were mounted on a measurement carriage that moved on fixed rails along the flume. After every experimental run, the flume was slowly drained, and an area of 7 x 1 m was recorded in three parallel, partially overlapping, swaths, with a resolution of 0.1 mm. See Ruijsscher et al. (2018) for a detailed description of the line laser scanner.

During the first and last 30 minutes of an experimental run, an UB-Lab 2C (UBER-TONE) (Figure 2c) was deployed to measure flow velocity profiles. The UB-Lab 2C is an ADVP (acoustic Doppler velocity profiler, e.g. Hurther and Lemmin (2001) and Mignot et al. (2009)), which measures a two-component velocity profile at high spatial (1.5 mm) and temporal resolution, here 10 to 15 Hz. An acoustic signal is transmitted along a single beam and received by two receivers under different observation angles. The resulting 2-component

Table 1. Overview of the performed experiments. Seventeen different sediment mixtures were tested, in which the type and percentage of fine material relative to the coarse material (base material) varied per experimental run. Each experiment with a distinct mixture was conducted for low, medium and high discharge, resulting in 51 experiments. * the experiment with medium discharge was excluded from analysis because of clogging of the pumps.

base experiment						
1	0/100					
experiments with	ith fine sand					
2-4	$35/65^{*}$					
5-7	51/49					
8-10	65/35					
11-13	82/18					
15-18	100/0					
experiments wi	th coarse silt					
19-21	2/98					
22-24	5/95					
25-27	11/89					
28-30	22/78					
31-33	32/68					
34-36	51/49					
experiments with fine silt						
37-39	2/98					
40-42	4/96					
43-45	9/91					
46-48	23/77					
49-51	30/70					

experiment number % fine / % coarse

vector is than projected to yield the 2-dimensional velocity in the streamwise direction (u)and vertical direction (w) along the beam (1D-profile). The emission frequency was set to 1 MHz with a bin size of 1.5 mm. The pulse repetition frequency ranged from 1200 to 1800 Hz for low and high discharge, respectively.

¹⁹⁸ 2.3 Data analysis

¹⁹⁹ 2.3.1 Sediment characterization

The behavior of the sediment in the experiments was estimated from the span value of the sediment-size distribution and the dominant way of sediment transport. This information was later used to interpret the observed bedform patterns.

The span value of the tested mixtures was used as a measure of distribution width, and was defined as:

$$SV = \frac{D_{90} - D_{10}}{D_{50}} \tag{3}$$

²⁰⁵ The sorting was determined as:

$$\sigma_g = \sqrt{\frac{D_{84}}{D_{16}}} \tag{4}$$

To determine the dominant way of transport, the ratio between the settling velocity of a particle, w_s , and the shear velocity, u^* , was calculated. If this ratio is larger than 3, the dominant transport mode is expected to be bedload, and if the ratio is smaller than 0.3, the dominant mode is expected to be suspended load (Dade and Friend, 1998). In between these values, the transport mode is mixed.

The settling velocity of a particle was approximated with (Ferguson and Church, 2004; Dietrich, 1982):

$$w_s = \frac{\rho_r g D_{50}^2}{C_1 \nu + \sqrt{0.75 C_2 R g D_{50}^3}} \tag{5}$$

where ρ_r is the relative submerged density $= (\rho_s - \rho_w)/\rho_w$, and $C_1 = 18$ and $C_2 = 1$ for natural grains (Ferguson and Church, 2004). The D_{50} of the original sediments was used rather than the D_{50} of the mixture, giving a transport mode for the base sediment and the finer fraction separately. This approximation was verified by visual observation through a window in the side of the flume.

2.3.2 Bedform geometry

218

Final bed configurations were determined from the bed elevation data obtained with 219 the line laser scanner. Five longitudinal transects were constructed across the width of 220 the flume, with an interspacing of 200 mm. The resulting transects served as input for 221 the bedform tracking tool of Mark and Blom (2007), which gives bedform geometry based 222 on specific detrending lengths, used to differentiate between bedform scales. Two bedform 223 length scales were identified: 150 ± 100 mm (hereafter referred to as small bedforms), and 224 1100 ± 400 mm (referred to as large bedforms). Small bedforms were observed in the 225 low-discharge experiments, whilst larger bedforms were observed in the medium and high-226 discharge experiments, and the bedform tracking tool was applied accordingly. Only if the 227 bedform occurred in at least two profiles of a bed scan, bedform statistics were calculated. 228

Bedform characteristics (Figure 4) in this study included bedform height, Δ (m), the vertical distance between crest and downstream trough; bedform length, λ (m), the horizon-



Figure 4. Definition of the bedform characteristics, showing the bedform height (Δ), the length (λ), the total length of the stoss side (λ_{stoss}) and the length of the stoss side at 0.5* Δ ($\lambda_{0.5stoss}$), the leeside angle (*LSA*), in which the upper and lower 1/6th of the leeside is excluded, the stoss-side angle (*SSA*), also excluding the upper and lower 1/6th of the stoss side, and the slip-face angle (*SFA*), which is the steepest part (95-percentile) of the leeside. The steepest part of the leeside is indicated with a small purple marker, and the location of the upper and lower 1/6th of the lee and stoss side are indicated with a small black marker.

tal distance between two subsequent crests; lees
ide angle, LSA (°), the slope angle derived 231 from a linear fit of the bedform's lesside, excluding the upper and lower 1/6 of the bed-232 form height; stoss-side angle, SSA (°), calculated similarly to the leeside angle; and the 233 slip-face angle, SFA (°), the steepest part of the leeside, calculated as the 95-percentile of 234 the distribution of angles along the leeside. The bedform roundness index, BRI, of the small 235 bedforms was defined as the ratio between the length from the dune crest to the stoss side at 236 0.5 times the dune height ($\lambda_{0.5stoss}$) and the length of the stoss side (λ_{stoss}) (Perillo et al., 237 2014; Prokocki et al., 2022). A bedform was classified as rounded if $BRI \ge 0.6$. Finally, the 238 bedform width, W (m), was derived by constructing six cross-sectional profiles transverse 239 to the flow, with an interspacing of 1000 mm. Next, the same bedform tracking tool was 240 applied using the same settings as for the longitudinal profiles. The bedform width was 241 calculated only for the low-discharge experiments, where the width of the bedforms was 242 considerably smaller than the width of the flume. 243

244 2.3.3 Bedform geometry predictors

Various bedform geometry predictors were tested based on our data. The selected predictors for dune height and length included a measure of flow strength (Van Rijn, 1984; Venditti and Bradley, 2022), and the predictor of Soulsby et al. (2012) was used for the height and length of ripples.

Van Rijn (1984) developed an empirical dune height and length predictor, the former being dependent on the transport stage, T_{vRijn} , as measure of flow strength.

$$\Delta_{vRijn} = 0.11h \left(\frac{D_{50}}{h}\right)^{0.3} (1 - e^{-0.5T_{vRijn}})(25 - T_{vRijn}) \tag{6}$$

$$\lambda_{vRijn} = 7.3h\tag{7}$$

 T_{vRijn} depends on shear stress and critical shear stress. See Appendix A for a full explanation. ²⁵³ Venditti and Bradley (2022) developed an empirical equation based on a different trans-²⁵⁴ port stage, T_{VB} , defined as $\frac{\theta}{\theta_c}$, which is the ratio of the dimensionless shear stress, θ , and ²⁵⁵ critical shear stress, θ_c . The equations suitable for laboratory flows with a water depth less ²⁵⁶ than 0.25 m are:

$$\Delta_{VB} = h \left(-0.00100 (\frac{\theta}{\theta_c} - 17.7)^2 + 0.417 \right)$$
(8)

$$\lambda_{VB} = h \left(0.0192 (\frac{\theta}{\theta_c} - 8.46)^2 + 6.23 \right)$$
(9)

The geometry of ripples is only dependent on a measure of grain size (D^*) and independent of transport stage (Baas, 1994; Baas, 1999). According to the equations of Soulsby et al. (2012), their geometry can be predicted with:

$$\Delta_{Souslby} = D_{50} 202 D^{*-0.554} \tag{10}$$

$$\lambda_{Soulsby} = D_{50}(500 + 1881D^{*-1.5}) \tag{11}$$

All definitions and symbols are given in Appendix A.

261 2.3.4 Roughness characterization

Hydraulic roughness was estimated following two methods. Firstly, the measured velocity profiles were used, following the method of Hoitink et al. (2009). Secondly, an indirect hydraulic roughness predictor of Van Rijn (1984) was used, based on bed geometry and sediment characteristics.

The first method is based on the Law of the Wall:

$$\frac{\overline{u}(z)}{u^*} = \frac{1}{\kappa} ln(\frac{z+h}{z_0}) \tag{12}$$

where \overline{u} is the mean velocity (m s⁻¹), $\kappa = 0.4$ is the Von Karman constant, h is the mean water depth (m), z is the height above the bed (m), and z_0 is roughness length (m).

For a water column that satisfies equation (12), i.e. where the velocity profiles are logarithmic (Supplementary Figure S3), the shear velocity can be determined from the slope of the velocity versus dimensionless depth σ_d (equation (B2)). This, in turn, can be used to derive roughness length and, ultimately, Manning's n, n_{man} (s m^{-1/3}). See Appendix B for an elaborate definition. Experiments 13-18 were excluded from analysis, since erroneous mounting caused invalid profiles.

Roughness was also approximated indirectly based on the predictor of Van Rijn (1984). The total predicted hydraulic roughness, expressed as friction factor, \hat{f} , results from form friction and grain friction (Einstein, 1950). The total hydraulic roughness was predicted as in Van Rijn (1984):

$$\hat{f} = \frac{8g}{(18\log(\frac{12h}{k_s}))^2}$$
(13)

where k_s is a measure of roughness both consisting of form roughness and grain roughness. See Appendix B for the corresponding equations. Friction factor f can be converted to n_{man} via (Manning, 1891; Silberman et al., 1963):

$$n_{man} = \frac{R_h^{1/6}}{\sqrt{\frac{8g}{\hat{f}}}} \tag{14}$$

where R_h is the hydraulic radius, which is equal to the cross-sectional area (A) divided by the wetted perimeter (P = width + 2h).

284 3 Results

281

285

289

302

3.1 Observed bed geometries

The bed geometries in the experiments were dependent on discharge (Figure 5a-c, see Supplementary Figures S2-S4 for the bed geometry of all runs), and on the addition of fine material. Below, we show the results separately for low, medium and high discharge.

3.1.1 Low discharge bed geometries

At low discharge, only small bedforms appeared on the bed (Figure 5a). The small bedforms had an average height of 0.011 m, an average length of 0.12 m and a non-rounded shape with a slip-face angle of 22°.

Bedform height and width both decreased with the addition of coarse silt and fine silt, 293 which is especially pronounced at a silt percentage above 20% (Figure 6a). The bedform 294 height decreased by 38% for coarse silt and 28% for fine silt compared to the experiment with 295 pure medium sand. The corresponding decrease in length was considerably smaller (14% 296 and 4%, respectively). This decrease in bedform height was not visible in the experiments 297 with fine sand. Similarly, bedform width decreased by 11% and 23% for coarse and fine silt 298 (Figure 6c), indicating that the bedforms became more three-dimensional in shape. The 299 LSA, SFA and BRI of these bedforms were independent of the type and percentage of finer 300 material added (Figure 6d-f). 301

3.1.2 Medium discharge bed geometries

The bedforms generated during medium discharge were generally larger than those 303 that emerged during low discharge, with an average height of 0.027 m, a length of 0.54 m, 304 and a slightly lower slip-face angle of 20° . Those bedforms followed two general trends. 305 Firstly, the runs with an increasing amount of fine sand and coarse silt showed an increase 306 in bedform height and length (Figure 5b). Especially for the coarse-silt runs, the increase 307 in bedform length was considerable (Figure 7b). The bedform length in these runs was on 308 average 0.59 m for the experiments with 20% coarse silt or less, and increased to 1.1 m for 309 the experiments with a higher coarse-silt percentage in the bed. This increase in bedform 310 length was accompanied by a smaller increase in bedform height from 0.032 m to 0.043 m 311 (Figure 7a). Bedform heights and lengths for the experiments with fine sand were smaller 312 than for the experiments with coarse silt (on average $\Delta = 0.026$ m and $\lambda = 0.54$ m for fine 313 sand, and $\Delta = 0.035$ m and $\lambda = 0.73$ m for coarse silt). The lee-face angles varied per 314 experiment, but the slip-face angles remained relatively constant, lacking a consistent trend 315 with increasing content of fine material (Figure 7c and d). 316

The experiments with fine silt revealed smaller bedforms that were larger than the bedforms in the low-discharge experiments, but comparable in planform (Figure 5d), despite the clear increase in depth-averaged flow velocity. The mean bedform length was 0.38 m, which is significantly smaller than for the experiments with fine sand and coarse silt. However, at 0.025 m, the mean bedform height is comparable to the runs with fine sand. A decrease in length and height was observed for the runs with 0 to 30% fine silt (23% decrease



Figure 5. Dynamic equilibrium bed morphologies at the end of selected experiments. All images represent a 1 m wide and 7 m long section of flume. a) Bed morphologies at low discharge. b) Bed morphologies at medium discharge, showing increasing dune length with increasing finer material. c) Bed morphologies with large variability at high discharge. d) Impact of fine silt on bed morphology. Scans in (c) show small two-dimensional ripples superimposed on larger bedforms and flat beds. These ripples are artifacts caused by draining the flume over an almost flat bed (see Supplementary Figure S5 for verification).



Figure 6. Bedform geometries at low discharge (45 L s⁻¹). a) Bedform height. Δ . b) Bedform length, λ . c) Bedform width, W. d) Bedform roundness index, *BRI*, where *BRI* < 0.6 indicates non-rounded bedforms. e) Leeside angle, *LSA*. f) Slip-face angle, *SFA*.



Figure 7. Bedform geometries at medium discharge (80 L s⁻¹). a) Bedform height, Δ . b) Bedform length, λ . c) Leeside angle, *LSA*. d) Slip-face angle, *SFA*.

in bedform height, 51% decrease in bedform length). Leeside angles were 28% larger than in the experiments with fine sand and coarse silt, but the slip-face angles were comparable.

3.1.3 High discharge bed geometries

The bedforms formed at high discharge were on average slightly larger than during 326 medium discharge (Figure 8), with an average height of 0.029 m and length of 0.72 m. 327 The slip-face angle was 18° , which was slightly lower than at medium discharge. However, 328 the geometrical parameters were highly variable, with a standard deviation of 1.6 cm, 39329 cm, 4.6° for bedform height, length and slip-face angle, respectively, and without a clear 330 relationship with the amount of fine material. The experiments with fine silt resulted on 331 average shorter bedform lengths and higher leeside angles than the experiments with coarse 332 silt and fine sand, which agrees with the observations at medium discharge. 333

The high discharge experiments were conducted close to the suspension threshold (w_s / $u^* < 0.3$), and the bedforms started to wash out towards upper stage plane bed, when three alternating bed states were observed (Figure 5c): an almost flat bed with one or two large, steep bedforms; a bed covered with dunes; and a flat bed.

338 3.2 Bedform variability

325

Relationships between bedform geometry and transport stage, θ/θ_c , are evident from the experimental data. Bedform length increased, and leeside and slip-face angle decreased with increasing transport stage, whereas the relationship between bedform height and transport stage approached a parabola (Figure 9a-d). Additionally, the variability in bedform geometry increased with increasing transport stage, indicated by the gray shaded band in Figure 9a-d.

The near-bed velocity $U_{0.2}$, which is the time-averaged velocity at the dimensionless height above the bed of $\sigma_d = 0.2$ and directly measured with the UB-Lab 2C, is a repre-



Figure 8. Bedform geometries at high discharge (100 L s⁻¹). a) Bedform height, Δ . b) Bedform length, λ . c) Leeside angle, LSA. d) Slip-face angle, SFA. Zero values indicate a flat bed.

sentation of the near-bed conditions influencing and being influenced by the bed geometry. The near-bed velocity shows a strong relation with the dimensionless bedform length (R^2 = 0.66) (Figure 9e).

The bedform height and length predictions for dunes based on Van Rijn (1984) and 350 Venditti and Bradley (2022) are shown in Figure 9a-b. For the low-discharge runs, these 351 predictions overestimate the measured bedform dimensions significantly. However, the rip-352 ple predictor of Soulsby et al. (2012) performs relatively well, with root-mean-square errors 353 of 0.001 m for height and 0.02 m for length. The bedforms can therefore be classified as 354 ripples. For the medium and high discharge runs, the Soulsby et al. (2012) equation for 355 ripples underpredicts the bedform size significantly. These bedforms are therefore classified 356 as dunes. The predictor of Van Rijn (1984) performs reasonably well for medium transport 357 stages, but it mostly underpredicts bedform heights for high transport stages. The predic-358 tor of Venditti and Bradley (2022) slightly overpredicts bedform height, but the measured 359 values are still within their margins of error. The bedform length predictor of Van Rijn 360 (1984), which is purely based on water depth, does not capture the trend of increasing dune 361 length with increasing transport stage. The predictor of Venditti and Bradley (2022) largely 362 overestimates bedform length for medium transport stages, but performs better for the high 363 transport stages by capturing the observed increase in length. 364

365 3.3 Hydraulic roughness

Hydraulic roughness, expressed as the depth-independent Manning's n and calculated 366 via the Law of the Wall based on the velocity profiles (equation (12)), averaged 0.038. 367 Manning's n increased with increasing leeside angle $(R^2 = 0.31)$ and decreasing bedform 368 length $(R^2 = 0.40)$ (Figure 10c-d). The relation with lenside angle stands out (Figure 10c), 369 since the ripples and dunes are both part of the linear correlation, whereas no relation 370 between ripple length and roughness was observed. Generally, the roughness was larger 371 during the experiments with fine silt (Figure 10) and the experiments with a rippled bed 372 (on average 0.039). The larger roughness is likely to be related to the relatively high leeside 373 angle of the bedforms observed in those experiments. 374



Figure 9. Increasing variability in bedform geometry with increasing flow strength, expressed as transport stage (θ/θ_c) in (a-d) and as non-dimensionalized velocity at 20% above the bed in (e). a) Bedform height divided by water depth. b) Bedform length divided by water depth. c) Leeside angle. d) Slip-face angle. e) Bedform length divided by water depth. Grey shading indicates one standard deviation from the mean value, in which the standard deviation is calculated from all bedforms in either low, medium or high discharge experiments. The base runs are indicated with black markers (medium sand). In (a) and (b), the predicted values by Venditti and Bradley (2022) and Van Rijn (1984) are shown.



Figure 10. The relation between the hydraulic roughness n_{man} , calculated with the Law of the Wall, and a) Bedform height, Δ . b) Fraction finer material within the base material. c) Leeside angle, LSA. d) Bedform length, λ . Significant linear relations are shown in c and d.

Counter-intuitively, hydraulic roughness does not exhibit a statistically significant re-375 lationship with dune height and the fraction of added finer material (Figure 10a-b). The 376 lack of a relationship with added fine material is consistent with the roughness predictor 377 of Van Rijn (1984), which differentiates between skin friction, related to grain size, and 378 form friction, related to bedform size. According to this predictor, on average, 97% of the 379 total amount of friction is attributed to form friction in the experiments, indicating that 380 bed composition is less important for hydraulic roughness than bedform geometry. The 381 roughness predictor of Van Rijn (1984) yields on average a Manning's n of 0.030, which is 382 11% lower than the measured friction based on the Law of the Wall. 383

³⁸⁴ 4 Discussion

385

4.1 A shift in transport stage due to addition of fines

The transport stage-based dune height predictor of Venditti and Bradley (2022) pro-386 vides a way to visualize the experimental results and assess deviations from expected heights 387 caused by the sediment mixtures (Figure 11). The predictor implies a parabolic relationship 388 between bedform height and transport stage, as well as confidence levels for data variability (Bradley and Venditti, 2017). The parabolic relation can be interpreted as follows. As the 390 transport stage increases, the transport mode changes from bed load to mixed load (w_s / u^* 391 decreases), and dune height increases. This corresponds to our low and medium-discharge 392 experiments. As the transport stage increases further, bedforms start to become washed-393 out, thus reducing the bedform height. This corresponds to our high-discharge experiments 394 (Yalin, 1972; Nagshband et al., 2014). 395

Although this framework is generally associated with a change in flow strength (Shields 396 number, θ), it can also be used to frame the experimental data using changes in sediment 397 mobility (critical Shields number, θ_c) caused by the addition of fine material to a coarser base 398 sediment (Figure 11). During the medium-discharge experiments, adding non-cohesive fine 399 sand and coarse silt led to an increase in dune height and length. When comparing this to 400 the expected change based on the predictor of Venditti and Bradley (2022) due to a decrease 401 in D_{50} resulting from the addition of fine sediment, the change in bedform geometry was 402 larger than expected. We attribute the increase in bedform size to an increase in mobility of 403 the bed material (i.e. a decrease in θ_c), leading to a larger change in transport stage (Section 404 4.2) than expected based on the change in D_{50} (Supplementary Table S1). Therefore, adding 405 fine, non-cohesive material leads to a shift to the right on the bedform height - transport 406 stage diagram (Figure 11). In contrast, adding fine, weakly cohesive material to the bed 407 decreases the mobility of the sediment (Section 4.3), and therefore decreases the transport 408 stage, resulting in a decrease in bedform size, leading to a shift to the left on the diagram 409 in Figure 11. Furthermore, the large variability in bedform geometry at the high transport 410 stages is attributed to instabilities that occur when the system moves towards upper-stage 411 plane bed (Section 4.4). Finally, the ripples formed at low discharge do not fit within the 412 transport stage diagram, since ripple size is only dependent on grain size and not on flow 413 velocity (Baas, 1994; Baas, 1999; Soulsby et al., 2012). Below, these changes are discussed 414 in more detail. 415

416 417

4.2.1 Hiding-exposure effect

⁴¹⁸ During the medium-discharge experiments, we observed an increase in dune size with ⁴¹⁹ larger fractions of fine non-cohesive material (fine sand and coarse silt) mixed into the base ⁴²⁰ material. This may be attributed to an increased mobility of the coarse sediment. In ⁴²¹ mixed sediments, differently sized grains interact with the flow and with each other in a ⁴²² different way than in equally sized sediments (McCarron et al., 2019), leading to selective ⁴²³ entertainment. This is called the hiding-exposure effect, where small grains are hidden

4.2 Impact of non-cohesive fine sediment (sand and coarse silt)



Figure 11. Conceptual diagram of non-dimensionalized dune height against transport stage, indicating the impact of adding non-cohesive and cohesive fine sediment to the bed material at relatively low transport stages, and the increased variability of bedform height due to flow instabilities at high transport stages. The dark grey shading indicates the 5 and 95-percentiles of data aggregated from Venditti et al. (2016) and Bradley and Venditti (2019). No data are available for the light grey shaded area. The dashed lines show the estimated course of the confidence intervals.

from the flow between the coarser grains. This does not only result in a more difficult mobilization of the fines (hiding), but also in an increased mobility of the larger grains (exposure) (Einstein, 1950) (see Section 4.2.2).

The hiding-exposure effect is mostly dependent on the ratio between the fraction of 427 interest D_i (here, the coarse fraction) and the D_{50} . Hill et al. (2017) tested the influence of 428 this ratio for gravel-sand mixtures. They found that if the two mixed sediments had similar 429 grain sizes, $(D_{coarse} / D_{fines} < 2)$, the bed aggregated without preferentially mobilizing the 430 coarser fraction, and the fines became part of the bed structure (Frings et al., 2008). For 431 intermediate particle ratios (2 < D_{coarse} / D_{fines} < 20), the fine sediment filled or bridged 432 the pores of the coarser base matrix, resulting in increased mobility of the coarse fraction 433 (Section 4.2.2). For large ratios ($D_{coarse} / D_{fines} > 20$), the fine sediment percolated 434 through the base sediment. The subsurface became clogged, but the fines were not present 435 in the surface layer, because all free fines were entrained and transported in suspension. 436

In the present experiments, the ratios between the coarse and fine fractions were 1.5, 437 6.9 and 15 for fine sand, coarse silt and fine silt, respectively. Following Hill et al. (2017), 438 this implies that the fine sand aggregated the bed structure, whereas the coarse and fine silt 439 bridged or filled the pores of the coarse fraction. For the silts, the hiding-exposure effect 440 should have played a role, increasing the mobility of the coarse fraction, whereas, for the fine 441 sand, the increased size distribution might have resulted in increased mobility of the entire 442 sediment bed due to an increase in grain protrusion and a decreased friction angle (Kirchner 443 et al., 1990; Buffington et al., 1992). However, this effect may have been smaller than the 444 mobility increase caused by the hiding-exposure effect by coarse silt, which is indicated by 445 the increased lengthening of dunes in a bed with coarse silt compared to fine sand. Increased 446 mobility means an increased transport stage, hence an increased dune length (Section 4.1). 447

Various methods have been developed to correct the initiation of motion of sediments for the hiding-exposure effect (see McCarron et al. (2019) for a review). Generally, the correction factor lowers the critical Shields number, θ_c , for the coarse fraction $(D_i > D_{50})$, and increases it for the fine fraction $(D_i < D_{50})$. The correction factor, ζ , commonly takes this form (Einstein, 1950; Wilcock, 1993):

$$\zeta = \alpha \left(\frac{D_i}{D_{50}}\right)^{-\beta} \tag{15}$$

where D_i is the grain size of the fraction of interest, β controls the strength of the hiding-exposure effect (Buffington and Montgomery, 1997; McCarron et al., 2019), and $\alpha =$ 1 for sediments with the same density. Exponent β has been approximated using σ_g , as a measure for sorting (Patel et al., 2013; McCarron et al., 2019): $\beta = 0.96$ for $\sigma_g < 2.85$ and $\beta = 2.67e^{-0.37\sigma_g}$ for $\sigma_g \geq 2.85$, where σ_g is determined with equation (4).

Applying this correction factor to the experimental data shows that adding a larger 458 fraction of fine material results in a larger increase in mobility of the coarse material. For 459 example, replacing 50% of the base material by fine sand causes θ_c of the base material to 460 decrease from 0.021 to 0.019 (-11%) and to 0.016 for 50% coarse silt (-31%) (Supplementary 461 Table S1). Applying this adjusted critical Shields number to our data reduces the root-462 mean-square error of the observed normalized dune height by 0.019 (-9%) and 0.032 (-15%) 463 for fine sand and coarse silt, respectively, when evaluated against the predictor of Venditti 464 and Bradley (2022). In contrast, the same adjustment increases the root-mean-square error 465 for the experiments with fine silt by 0.011 (+6%) and causes the variability for the high 466 discharge runs to remain high, with a root-mean-square error of 0.31. These results are 467 discussed in Sections 4.3 and 4.4, respectively. 468

469

4.2.2 The hiding-exposure effect in mixed gravel-sand and sand-silt beds

The hiding-exposure effect is not commonly recognized in studies focused on sand-silt 470 mixtures, and is mainly based on experiments in gravel-sand mixtures. McCarron et al. 471 (2019) described an increase in mobility in gravel-sand experiments based on a decrease 472 in θ_c by 64% compared to well-sorted sediment of a similar size (2.14 mm). Frings et al. 473 (2008) speculated that hiding-exposure could result in a more mobile coarse fraction than 474 a fine fraction in the downstream part of sand-bed rivers. Our observations with sand-silt 475 mixtures show many parallels to gravel-sand mixtures, but on a smaller grain-size scale. 476 We therefore infer from our experiments that the hiding-exposure effect also plays a role in 477 sand-silt mixtures. 478

Mechanisms explaining the increased mobility of gravel in sand-gravel mixtures were 479 suggested by Ikeda (1984) and subsequently built on in later studies (e.g. Li and Komar 480 1986; Whiting et al. 1988; Dietrich et al. 1989; Wilcock 1993; Venditti et al. 2010). Firstly, 481 by filling pores with fine grains, the pivoting angle of large grains is reduced, thus facilitating 482 entrainment (Li and Komar, 1986). Secondly, there is a lower probability that particles in 483 transport are caught in the wake of protruding particles and deposit, since particles protrude 484 less far into the flow. Finally, filling pores with fine material results in a smoother bed, thus 485 resulting in lower drag, which in turn increases the near-bed velocity. These suggestions were built upon by Venditti et al. (2010), who suggested that the infilling of the pores causes 487 dampening of small wakes in the lee of particles, resulting in acceleration of the near-bed 488 flow, which in turn mobilizes the larger particles. Our experimental results suggest that 489 this acceleration of near-bed velocity is reflected in an increase in dune length and height 490 at medium discharge (Figure 9d). 491

The observation that the sediment mobility increases when adding coarse silt to the bed is in line with what can be expected from experiments with gravel-sand mixtures, but opposes previous observations in laboratory experiments with sand-silt mixtures. Bartzke

et al. (2013) and Yao et al. (2022) observed that non-cohesive silt stabilizes the sediment 495 bed, but at different concentrations ($\sim 1.4\%$ silt and >35%, respectively), whereas, in our 496 experiments, even at 50% coarse silt the mobility of the sediment was increased. Interest-497 ingly, Bartzke et al. (2013), whose experiments fall in the range of pore bridging (D_{coarse} / $D_{fines} = 5.5$), explained the filling of pore space as a reason for increased stability of the 499 bed due to reduced hyporheic flow, rather than a reason for increased mobility of the coarse 500 fraction as found in gravel-sand experiments (Section 4.2.1). The reason for these opposing 501 effects could lie in the different experimental setups: the highest flow velocity tested in these 502 experiments was 0.35 m s^{-1} , which is comparable to our lowest flow velocity. It is therefore 503 likely that the supposed stabilizing effect of silt is overruled by a large bed shear stress and 504 the development of bedforms in our experiments. 505

Ma et al. (2020) studied the mobility of silt-sized sediment and the effects of sorting 506 in laboratories and rivers world-wide, and found a high-mobility sediment transport regime 507 related to the size and sorting of the bed sediment. Bed sediments of $D_{50} < 88 \ \mu m$ and 508 poorly sorted sediments within a range of 88 $\mu m < D_{50} < 153 \mu m$ were found to be more 509 mobile than expected from the sediment transport rate equations of Engelund and Hansen 510 (1967), whereas sediments with $D_{50} > 153 \ \mu m$ confirmed these equations. In other words, 511 poorly sorted sediments in the transitional range of very fine to fine sand are more easily 512 mobilized than narrowly distributed sediments. This agrees with equation (15), where the 513 strength of the hiding-exposure effect is related to the sorting of the material. Although 514 Ma et al. (2020) did not explicitly mention the hiding-exposure effect, and related their 515 observation to the change from mixed load to suspended-load dominated transport, the 516 hiding-exposure effect may have played a role to achieve this change. 517

4.3 Impact of weakly cohesive fine silt

518

⁵¹⁹ Contrary to the increase in mobility observed when adding non-cohesive fine material, ⁵²⁰ the mixing of fine silt into the bed reduced both the height and length of the bedforms. ⁵²¹ This can be attributed to the weakly cohesive character of the 17 μ m-sized silt, because ⁵²² cohesive sediments such as clay are known to limit or suppress bedform growth (Schindler ⁵²³ et al., 2015; Parsons et al., 2016) through London-van der Waals forces and by interparticle ⁵²⁴ electrostatic bonding (Mehta, 2014), consequently increasing θ_c .

The fine silt used in our experiments exhibited weakly cohesive properties, confirmed 525 by visual stickiness of slurries of the fine silt and an increased angle of repose. Therefore, 526 fine silt might have imparted similar attractive forces as clay, although to a lesser extent. 527 Schindler et al. (2015) and Parsons et al. (2016) performed experiments with fine sand (D_{50} 528 = 239 μ m) at a mean velocity $u = 0.8 \text{ m s}^{-1}$, and observed an inverse linear relationship 529 between dune height and clay percentage, with a lack of dunes at a clay percentage of 15%. 530 The sharp decline in bedform height with clay content as observed in their experiments, 531 was not evident in the present experiments, and the bed remained mobile up to 30% fine 532 silt. Nevertheless, in the medium-discharge experiments, the dune heights and lengths for 533 fine silt were significantly reduced, as opposed to the increase for coarse silt and fine sand, 534 likely due to decreased mobility of the entire bed. In the low-discharge experiments, the 535 ripple size was reduced too, but, as shown below, this could be a result of decreased grain 536 size rather than decreased mobility. 537

Wu et al. (2022) recorded a decrease in ripple height with increasing clay percentage 538 under wave-current conditions ($D_{coarse} / D_{fines} \sim 51$). Below 11% clay, the clay was win-539 nowed out of the bed, allowing clean-sand ripples of similar size to develop. Above 11%, 540 the cohesiveness of the bed was large enough to limit bed mobility, and only small rip-541 ples formed. In our experiments, this effect did not occur, as even at small percentages of 542 fine silt ($\sim 2\%$) bedform height decreased, as in the current-ripple experiments with mixed 543 clay-sand of Baas et al. (2013). During the medium-discharge experiments, cohesion im-544 peded dune formation, and only small bedforms formed. In the high-discharge experiments, 545

dunes did form, but their planform was more similar to the dunes formed in the mediumdischarge experiments with fine sand and coarse silt than to those in the high-discharge runs (Supplementary Figure S2 and S3), indicating cohesion-induced hampered mobility.

In summary, the formation of relatively small bedforms in our experiments with fine silt can be attributed to reduced mobility, caused by the weakly cohesive properties of fine silt. This effect is less pronounced than in previous experiments with more strongly cohesive clay, in which the mobility was limited more strongly. The decreased mobility leads to an increase in the critical Shields number, and a shift to the left in the transport-stage diagram of Figure 11.

4.4 Instabilities at high discharges

555

The present study shows that any impact of fine sediment on bed geometry at high transport stages is swamped by the inherent variability of dune geometry (Figure 11). This variability encompasses three bed configurations, without any apparent relationship with the type or fraction of fines: a dune-covered bed; a flat bed with one large dune (cf. Saunderson and Lockett (1983) and Naqshband et al. (2016)); and a completely flat bed.

The variability in bedform geometry and the presence of multiple bed configurations 561 have been described before in literature. Saunderson and Lockett (1983) performed experi-562 ments around the transition from dunes to upper-stage plane bed and found four different 563 bed states: asymmetrical dunes; convex dunes; humpback dunes (comparable to the single 564 large dune configuration in this study); and a flat bed. These bedform states were seen to 565 transform into one another. Saunderson and Lockett (1983) dedicated this behavior to the 566 close position of the bed to the phase boundary between dunes and upper-stage plane bed, 567 but did not provide a physical explanation. Venditti et al. (2016) observed three phases in 568 high-velocity experiments: a plane bed with washed-out dunes; a field of large dunes; and 569 a field of small dunes. The water depth, shear stresses and water surface slope co-varied 570 with the changes in bed configuration. During the plane-bed phase, intense localized erosion 571 was followed by the formation of small or large bedforms, which then washed out to form 572 a new flat bed. These cycles lasted from several minutes to more than half an hour, with 573 transitions between individual bedform types happening in seconds or minutes. Similarly, 574 Bradley and Venditti (2019) stated a 'tremendous variability' between bed states at a high 575 transport stage, and reasoned that numerous observations of the bed are needed to get an 576 average bed state that scales with the transport states described by equations (8) and (9). 577

However, none of these studies provided an explanation for the large variability in dune 578 height at high transport stages. de Lange et al. (2023) reanalyzed the data of Venditti et al. 579 (2016) and Bradley and Venditti (2019), and found a bimodal dune height distribution at 580 high transport stages. They attributed this to a critical transition, exhibiting flickering 581 between a high and low alternative stable state. Our current observations support the idea 582 of these alternative stable states. The large variability in bed configurations explains the 583 lack of a predictable succession of bed states with increasing amounts of fine sediment in 584 the current study. This variability is so large that all bed states can occur at any moment, 585 independent of the bed composition. However, the upper stage plane bed condition was 586 not observed in the high-discharge experiments with fine silt, which once again shows a 587 decreased mobility as a result of the cohesiveness of the sediment, leading to a shift to the 588 left on the bedform-transport stage diagram, preventing flattening of the bed. 589

4.5 Ripples at low discharges

Ripples formed in the low discharge experiments. Ripple height and length are a product of the size of the bed material, and are independent of flow velocity (Baas, 1994; Baas, 1999; Soulsby et al., 2012). Therefore, the transport stage framework as suggested above for dunes is not relevant for ripples. The height and width of the ripples, and to a lesser degree their ⁵⁹⁵ length, decreased with an increasing amount of coarse and fine silt. The decrease in height ⁵⁹⁶ is most apparent at silt concentrations above 20%, the same percentage at which the D_{10} ⁵⁹⁷ of the sediment distribution drops considerably (Figure 3).

Adding fine sand to the base material led to a decrease in height of about 15%, a similar 598 decrease as expected based on Soulsby's ripple predictor (equation (10)). This suggests that 599 the change in grain size dominated the change in ripple height, and the hiding-exposure effect 600 was small. However, adding coarse silt to the base material had a larger decreasing effect on 601 height and length than fine sand. In the run with 50% coarse silt, both the height and the 602 length were at, or close to the predicted values of 8 mm and 95 mm, respectively, suggesting 603 that equilibrium was reached in this run. Hence, adding coarse silt increases the development 604 rate of the ripples compared to fine sand. This may be caused by three processes; a) a 605 mobility increase induced by the hiding-exposure effect; b) a shorter equilibrium time for 606 coarse silt ripples at the same Shields stress; c) a larger relative effect of coarse silt than 607 fine sand, as a 50% increase in weight of the finer fraction involves a much larger number of 608 coarse silt than fine sand particles (in the same volume, there are 331 times more coarse silt 609 particles than medium sand particles, as opposed to 3 times for fine sand). Finally, adding 610 fine silt to the base material shows the effect of cohesion by reducing the ripple height. 611 However, the effect of particle size cannot be distinguished with confidence from that of 612 cohesion. The decrease in ripple height with increasing fraction of fine silt is larger than for 613 coarse sand, which might be at least partly caused by the cohesive properties of the fine silt. 614

It should be emphasized that the response of ripples to an increase of fine bed sediment is different from the response of dunes. Whereas dune geometry gets adjusted by the increased mobility of the non-cohesive bed sediment, ripple geometry mainly results directly from the particle size distribution of the material.

619

4.6 The impact of bed sediment on hydraulic roughness

We confirm that for relatively steep dunes, roughness is related to the steepness of the 620 leeside, consistent with findings of Kwoll et al. (2016) and Lefebvre and Winter (2016). At 621 the leeside of the dune, flow separation generates turbulence, resulting in energy dissipation 622 in the turbulent wake, which constitutes the main source of dune-related roughness (Lefebvre 623 et al., 2014; Venditti and Bennett, 2000). In our experiments, the bedforms had on average 624 a leeside angle of 10° with a relatively steep section (mean slip-face angle 20°), resulting in 625 intermittent flow separation (Lefebvre and Cisneros, 2023). The presence of flow separation 626 can also be determined using the defect Reynolds number (Baas and Best, 2000), Re_d (Re_d 627 $=\frac{\Delta u^*}{u}$). In all our experiments, Re_d is far larger than 4.5, which indicates the presence of 628 flow separation (Williams and Kemp, 1971; Best and Bridge, 1992; Gyr and Müller, 1996). 629

Previous research suggested that the composition of the sediment bed has only a small influence on hydraulic roughness (Smith and McLean, 1977). This corresponds with our findings and equation (13) as far as skin friction is concerned; only 3% of the total roughness is attributed to skin friction in the present experiments. However, the bed composition strongly impacts the bed geometry, thereby influencing form roughness.

635

4.7 Wider implications

Our results show that the presence of fines affects sediment mobility, even if the fines only slightly change the D_{50} of the sediment. Therewith, fine material influences bedform properties and hydraulic roughness, which is worth accounting for in bedform size predictors. Moreover, the interaction of fine silt and sand with coarser sand is relevant for channel nourishment aimed at preventing incision (Czapiga et al., 2022).

To adequately determine bedform geometry, some measure of bimodality or sorting may be included in future predictors. This measure could focus on the fine fraction, such as the D_{10} . Additionally, the bed geometries for added fine and coarse silt differ notably, ⁶⁴⁴ if the fine silt fraction is cohesive. Hence, assessing the cohesive properties of silt, such as ⁶⁴⁵ yield stress and viscosity, is crucial, and lumping fines into one fraction, with a cut-off at 63 ⁶⁴⁶ μ m (e.g. Rijn (2020)) is to be avoided.

⁶⁴⁷ 5 Conclusions

654

655

668

669

We performed 52 laboratory experiments, in which the bed composition was varied using three different sediment mixtures (medium sand with fine sand, coarse silt and fine silt) in different ratios, for three different discharges (low, medium, high). We measured the bed morphology at the end of the experiments to assess the effect of bed composition on bedform geometry, and used this to indirectly assess sediment mobility and transport stage. The main conclusions of the research are:

- Bedform response to the addition of fine material depends, amongst others, on transport capacity, bimodality-impacted bed mobility, and cohesion.
- In the dune regime, adding fine sand or coarse silt to medium sand increases the mobility of coarser material. This leads to an increase in transport stage, θ/θ_c , an increase in dune length, and an increase or decrease in dune height, depending on the initial value of θ/θ_c .
- The increase in mobility of medium sand is inferred to be caused by the hidingexposure effect, with the filling of pores by coarse silt leading to a larger near-bed flow velocity. Fine sand is too coarse to fit in the pores, which causes an increase in grain protrusion and a decrease in friction angle, and therefore increased sediment mobility.
- Adding weakly cohesive fine silt to medium sand has a similar effect to adding cohesive clay (Schindler et al., 2015), by causing a decrease in transport stage and inhibiting dune growth.
 - In the ripple regime, adding fine material leads to a decrease in ripple height, which responds directly to the decreased particle size.
- In the transitional regime from dune to upper-stage plane bed, bed geometries may flicker between alternative stable bed states, complicating the relation between bedform height and length and fine sediment fraction.
- The composition of the sediment bed does not significantly influence hydraulic roughness from skin friction drag, but it alters the bed morphology, and thus indirectly changes the hydraulic roughness through form drag.

676 Appendix A Bedform geometry predictors

The dune height and length predictions based on Van Rijn (1984) follow equation (6) and (7) in which T is Van Rijn (1984)'s definition of the transport stage.

$$T_{vRijn} = \frac{(u^*)^2 - (u^*_c)^2}{(u^*_c)^2}$$
(A1)

where u^* is the shear velocity (m s⁻¹), and u_c^* is the critical shear velocity (m s⁻¹). Both the shear velocity and the critical shear velocity are unknown, but can be expressed in known parameters. The shear velocity can be expressed via:

$$u^* = u \frac{g^{0.5}}{C'}$$
 (A2)

in which u is the time and depth-averaged velocity (m s⁻¹) derived from the measurements with the UB-LAB 2C and C' is the grain-related Chézy parameter (m^{0.5} s⁻¹), which can be expressed as:

$$C' = 18\log \frac{12R_h}{3D_{90}}$$
(A3)

- Herein, R_h is the hydraulic radius, which is equal to the cross-sectional area (A) divided by the wetted perimeter (P = width + 2h).
- ⁶⁸⁷ The critical shear velocity can be calculated as:

$$u_c^* = \sqrt{\frac{\tau_c}{\rho_w}} \tag{A4}$$

In turn, the critical shear stress can calculated using the critical Shields number θ_c :

$$\tau_c = \theta_c (\rho_s - \rho_w) g D_{50} \tag{A5}$$

and θ_c is obtained from (Parker et al., 2003):

$$\theta_c = 0.5 \left(0.22 R e_p^{-0.6} + 0.06 * 10^{(-7.7 R e_p^{-0.6})} \right)$$
(A6)

In which the particle Reynolds number, Re_p (-), is defined as:

$$Re_p = D_{50}^{3/2} \frac{\sqrt{\rho_r g}}{\nu} \tag{A7}$$

⁶⁹¹ Venditti and Bradley (2022)'s empirical equation for predicting dune height and length ⁶⁹² can be found in equation (8) and (9). The dimensionless shear stress θ is derived by calcu-⁶⁹³ lating the shear stress τ from the shear velocity (via equation (A4), replacing τ for τ_c). The ⁶⁹⁴ critical shear stress θ_c is calculated via equation (A6).

The geometry of ripples is predicted based on Soulsby et al. (2012) via equation (10) and (11) in which D^* (-) is given by:

$$D^* = D_{50} \left(\frac{g(\frac{\rho_s}{\rho_w} - 1)}{\nu^2} \right)^{1/3}$$
(A8)

⁶⁹⁷ Appendix B Hydraulic roughness determination

For a water column that satisfies equation (12), the equation can be rewritten into:

$$\overline{u}(\sigma_d) = \frac{u^*}{\kappa} (ln(\sigma_d) + 1) + U$$
(B1)

699

688

in which U is the depth-mean velocity, and σ_d is the dimensionless depth using:

$$\sigma_d = \frac{z+h}{h} \tag{B2}$$

The value of u^* can be derived from the slope of a linear regression line through the data points of \overline{u} versus $(\ln(\sigma_d)+1)$. The average velocity $\overline{u}(\sigma_d)$ was determined as the average streamwise velocity during a single measurement. The averaging time window of 30 minutes was narrowed down to cover an integer number of bedforms, defined from top to top. The σ_d -coordinate was defined such that $\sigma_d=0$ coincides with the top of the highest

bedform during a measurement (the 95-percentile of the measured bed elevation was chosen, 705 to exclude outliers as a result of backscatter spikes). The σ_d =1-coordinate is located at the 706 top of the vertical measuring range, which corresponds to the elevation of the UB-Lab-2C 707 transducer. The time-averaged relation between \overline{u} and $ln(\sigma_d)$ was consistently linear at the 708 middle half of the measured profile (between -0.175 $< \sigma_d < -0.625$), so this part of the 709 profile was used for determining u^* (Supplementary Figure S6). The goodness of the linear 710 fit of the log-profiles had on average a R^2 -value of 0.96. Following Hoitink et al. (2009), the 711 roughness length z_0 (m) can be calculated using: 712

$$z_0 = \frac{h}{e^{\left(\frac{\kappa U}{u^*}\right)} + 1} \tag{B3}$$

Finally, Manning's n, n_{man} (s m^{-1/3}) can be calculated in the following steps (Pope, 2000; Chow, 1959):

$$k_b = 30 * z_0 \tag{B4}$$

$$n_{man} = \frac{k_b^{\frac{1}{6}}}{25} \tag{B5}$$

in which k_b is the total roughness height (m).

Roughness height can also be approximated indirectly based on the predictor of Van Rijn (1984) with equation (13), resulting in the dimensionless Darcy-Weisbach friction factor, \hat{f} . Herein, k_s consists of form roughness height k_{sf} and grain roughness height k_{sg} :

$$k_s = k_{sg} + k_{sf} \tag{B6}$$

$$k_{sq} = 3D_{90} \tag{B7}$$

$$k_{sf} = 1.1\gamma_d \Delta (1 - e^{\frac{-25\Delta}{\lambda}}) \tag{B8}$$

where the calibration constant γ_d is taken as 1 in laboratory conditions (Van Rijn, 1984).

The friction factor, \hat{f} , can be converted to Manning's n (n_{man}) via the Chézy coefficient C $(m^{1/2}s^{-1})$ (Manning, 1891; Silberman et al., 1963).

$$C = \frac{R_h^{1/6}}{n_{man}} \tag{B9}$$

$$\hat{f} = \frac{8g}{C^2} \tag{B10}$$

722 **Open Research Section**

The data and code used to generate the results in this study will be made available through the public repository of 4TU upon acceptance, with doi: 10.4121/dde430c4-7f9f-4d7b-bff1-d4792e0031f2.

726 Acknowledgments

SdL and TH were funded by the Netherlands Organization for Scientific Research (NWO), 727 within Vici project "Deltas out of shape: regime changes of sediment dynamics in tide-728 influenced deltas" (Grant NWO-TTW 17062). IN is funded by the Dutch Ministry of 729 Infrastructure and Water under the research program "Rivers2Morrow". This work is based 730 on the MSc thesis of SV and JL. We would like to thank Maarten Kleinhans and Jeremy 731 Venditti for their help with data interpretation, Nick Wallerstein for the technical and 732 practical help in the laboratory, and finally all fellow colleagues that helped shovelling 733 sediment in and out of the flume. 734

735 **References**

751

752

753

- Allen, J. R.L. (1978). "Computational models for dune time-lag: calculations using Stein's rule for dune height". In: *Sedimentary Geology* 20.C, pp. 165–216. ISSN: 00370738. DOI: 10.1016/0037-0738(78)90054-4.
- ASCE Task Force (2002). "Flow and transport over dunes". In: Journal of Hydraulic Engineering 127, pp. 726–728.
- Baas, J.H. and H. de Koning (1995). "Washed-Out Ripples: Their Equilibrium Dimensions, Migration Rate, and Relation to Suspended-Sediment Concentration in Very Fine Sand". In: SEPM Journal of Sedimentary Research Vol. 65A. ISSN: 1527-1404.
 DOI: 10.1306/D42680E5-2B26-11D7-8648000102C1865D.
- Baas, Jaco H. (1994). "A flume study on the development and equilibrium morphology of current ripples in very fine sand". In: Sedimentology 41.2, pp. 185–209. ISSN: 13653091.
 DOI: 10.1111/j.1365-3091.1994.tb01400.x.
- (Feb. 1999). "An empirical model for the development and equilibrium morphology of current ripples in fine sand". In: *Sedimentology* 46.1, pp. 123–138. ISSN: 00370746.
 DOI: 10.1046/j.1365-3091.1999.00206.x.
 - Baas, Jaco H. and James L. Best (Aug. 2000). "Ripple formation induced by biogenic mounds—comment". In: *Marine Geology* 168.1-4, pp. 145–151. ISSN: 00253227. DOI: 10.1016/S0025-3227(00)00040-2.
- Baas, Jaco H., Alan G. Davies, and Jonathan Malarkey (Jan. 2013). "Bedform development in mixed sand-mud: The contrasting role of cohesive forces in flow and bed". In: *Geomorphology* 182, pp. 19–32. ISSN: 0169555X. DOI: 10.1016/j.geomorph.2012.10
 .025.
- Bartzke, Gerhard et al. (2013). "On the stabilizing influence of silt on sand beds". In: Journal of Sedimentary Research 83.8, pp. 691–703. ISSN: 15271404. DOI: 10.2110/jsr.2013
 .57.
- Berg, J.H. van den and A. van Gelder (1993). "A new bedform stability diagram, with
 emphasis on the transiton of ripples to plane bed in flows over fine sand and silt". In:
 Spec. Publs Int. Ass. Sediment 17, pp. 11–21.
- Best, Jim (2005). "The fluid dynamics of river dunes: A review and some future research directions". In: Journal of Geophysical Research: Earth Surface 110.4, pp. 1–21. ISSN: 21699011. DOI: 10.1029/2004JF000218.
- Best, Jim and John Bridge (1992). "The morphology and dynamics of low amplitude bedwaves upon upper stage plane beds and the preservation of planar laminae". In: Sed-*imentology* 39.5, pp. 737–752. ISSN: 13653091. DOI: 10.1111/j.1365-3091.1992
 .tb02150.x.
- Bradley, Ryan W. and Jeremy G. Venditti (Feb. 2017). Reevaluating dune scaling relations.
 DOI: 10.1016/j.earscirev.2016.11.004.
- (2019). "Transport Scaling of Dune Dimensions in Shallow Flows". In: Journal of Geophysical Research: Earth Surface 124.2, pp. 526–547. ISSN: 21699011. DOI: 10.1029/ 2018JF004832.
- Buffington, John M., William E. Dietrich, and James W. Kirchner (Feb. 1992). "Friction
 angle measurements on a naturally formed gravel streambed: Implications for crit-

778	ical boundary shear stress". In: Water Resources Research 28.2, pp. 411–425. ISSN:
779	00431397. DOI: 10.1029/91WR02529.
780	Buffington, John M. and David R. Montgomery (Aug. 1997). "A systematic analysis of eight
781	decades of incipient motion studies, with special reference to gravel-bedded rivers".
782	In: Water Resources Research 33.8, pp. 1993–2029. ISSN: 00431397. DOI: 10.1029/
783	96WR03190.
784	Chow, V.T. (1959). Open-channel hydraulics. McGraw-Hill Book Company, USA. ISBN:
785	ISBN 0-07- 085906-X.
786	Czapiga, Matthew J., Astrid Blom, and Enrica Viparelli (June 2022). "Sediment Nourish-
787	ments to Mitigate Channel Bed Incision in Engineered Rivers". In: Journal of Hydraulic
788	Engineering 148.6. ISSN: 0733-9429. DOI: 10.1061/(ASCE)HY.1943-7900.0001977.
789	Dade, W. Brian and Peter F. Friend (Nov. 1998). "Grain-Size, Sediment-Transport Regime,
790	and Channel Slope in Alluvial Rivers". In: The Journal of Geology 106.6, pp. 661–676.
791	ISSN: 0022-1376. DOI: 10.1086/516052.
792	de Lange, S.I. et al. (Dec. 2023). "Alternative stable river bed states at high flow". In: ESS
793	Open Archive. DOI: 10.22541/essoar.170317282.22054327/v1.
794	Dietrich, William E. (Dec. 1982). "Settling velocity of natural particles". In: Water Re-
795	sources Research 18.6, pp. 1615–1626. ISSN: 00431397. DOI: 10.1029/WR018i006p01615.
796	Dietrich, William E. et al. (July 1989). "Sediment supply and the development of the coarse
797	surface layer in gravel-bedded rivers". In: Nature 340.6230, pp. 215–217. ISSN: 0028-
798	0836. DOI: 10.1038/340215a0.
799	Einstein, H. A. (1950). "The bed-load function for sediment transportation in open chan-
800	nel flows". In: Technical Bulletins 156389, United States Department of Agriculture,
801	Economic Research Service.
802	Engelund, F. and E. Hansen (1967). "Monograph on Sediment Transport". In: Technisk
803	Forlag, Copenhagen, Denmark.
804	Ferguson, R I and M Church (2004). A simple universal equation for grain settling velocity.
805	Tech. rep. 6, pp. 933-937. URL: http://pubs.geoscienceworld.org/sepm/jsedres/
806	article-pdf/74/6/933/2821499/933.pdf.
807	Frings, Roy M., Maarten G. Kleinhans, and Stefan Vollmer (Dec. 2008). "Discriminating
808	between pore-filling load and bed-structure load: A new porosity-based method, ex-
809	emplified for the river Rhine". In: Sedimentology 55.6, pp. 1571–1593. ISSN: 13653091.
810	DOI: 10.1111/j.1365-3091.2008.00958.x.
811	Greene, H. Gary, Matthew Baker, and John Aschoff (2020). "A dynamic bedforms habitat
812	for the forage fish Pacific sand lance, San Juan Islands, WA, United States". In: Seafloor
813	Geomorphology as Benthic Habitat. Elsevier, pp. 267–279. DOI: 10.1016/B978-0-12
814	-814960-7.00014-2.
815	Gyr, A. and A. Müller (1996). "The role of coherent structures in developing bedforms
816	during sediment transport". In: Coherent flow structures in open channels, pp. 227-
817	235.
818	Healy, T., Y. Wang, and J.A. Healy (2002). Muddy Coasts of the World: Processes, Deposits
819	and Function. 1st ed. Amsterdam: Elsevier.
820	Hill, Kimberly M. et al. (Jan. 2017). "Experimental study of the effect of grain sizes in a
821	bimodal mixture on bed slope, bed texture, and the transition to washload". In: Water
822	Resources Research 53.1, pp. 923–941. ISSN: 19447973. DOI: 10.1002/2016WR019172.
823	Hoitink, A. J.F., F. A. Buschman, and B. Vermeulen (2009). "Continuous measurements of
824	discharge from a horizontal acoustic Doppler current profiler in a tidal river". In: Water
825	Resources Research 45.11, pp. 1–13. ISSN: 00431397. DOI: 10.1029/2009WR007791.
826	Hurther, D. and U. Lemmin (2001). "A Correction Method for Turbulence Measurements
827	with a 3D Acoustic Doppler Velocity Profiler". In: Journal of Atmospheric and Oceanic
828	<i>Technology</i> , pp. 446-458. DOI: https://doi .org/10 .1175/1520 -0426(2001)
829	018<0446:ACMFTM>2.0.CD;2.
830	Ikeda, H. (1984). "Flume experiments on the superior mobility of sediment mixtures". In:
831	Ann. Rep. Inst. Geosci. 10. Univ. of Tsukuba, Tsukuba, Japan, pp. 53–56.

832	Karim, F. (1995). "Bed configuration and hydraulic resistance in alluvial-channel flows". In:
833	Journal of Hydraulic Engineering 121.1, pp. 15–25.
834	Kirchner, JAMES W. et al. (Aug. 1990). "The variability of critical shear stress, friction an-
835	gle, and grain protrusion in water-worked sediments". In: Sedimentology 37.4, pp. 647–672, ISSN: 0037-0746, DOI: 10.1111/j.1365-3091.1990, tb00627.x
927	Kwoll E et al (Mar 2016) "Flow structure and resistance over subaquaeous high- and
030	low-angle dunes" In: Journal of Geophysical Research: Earth Surface 121.3 pp. 545-
838	564 ISSN: 21600011 DOI: https://doi.org/10.1002/2015 IE003637
839	Lafabura Alice and Julia Cigneros (July 2023) "The influence of dune les side shape on
840	time averaged velocities and turbulence" In: Earth Surface Duramice 11.4, pp. 575-
841	591. ISSN: 2196-632X. DOI: 10.5194/esurf-11-575-2023.
843	Lefebvre, Alice, Andries J. Paarlberg, and Christian Winter (Feb. 2014). "Flow separation
844	and shear stress over angle-of-repose bed forms: A numerical investigation". In: Water
845	Resources Research 50.2, pp. 986–1005. ISSN: 00431397. DOI: 10.1002/2013WR014587.
846	Lefebvre, Alice and Christian Winter (2016). "Predicting bed form roughness: the influence
847	of lee side angle". In: Geo-Marine Letters 36.2, pp. 121–133. ISSN: 14321157. DOI:
848	10.1007/S00307-010-0430-0.
849	for applications to calculate antrainment of gravel in a summent. In: <i>Codimental care</i> 22.2
850	for applications to selective entrainment of graver in a current \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in: <i>Selective entrainment of graver in a current</i> \cdot in the selective entrainment of graver in a current \cdot in the selective entrainment of graver in the selective entrainment of graver in a current \cdot in the selective entrainment of graver in the selective entrainmen
851	pp. 415-425. ISSN: 0057-0740. DOI: 10.1111/j.1305-3091.1980.tb00545.X.
852	tener, Every La State Velley, Chine, Chine, La Colones, Advances, 25, pp. 1, 8, 1999
853	22752548 DOI: 10.1106 (acia day 1602114)
854	Ma Hongho et al. (2020). "Universal relation with regime transition for addiment transport
855	in fine graphed rivers" In: Precedings of the National Academy of Sciences of the
856	United States of America 117.1 pp. 171–176 ISSN: 10016400 DOI: 10. 1072/pp.
857	1011025116
858	Manning R (1801) "On the flow of water in open channels and pipes" In: Transactions
859	of the Institution of Civil engineers of Ireland
860	Mark C E van der and A Blom (2007) A new and widely annlicable tool for determining
801	the geometric properties of hedforms Tech rep. University of Twente
002	McCarron Connor I et al (Apr 2019) "The hiding-exposure effect revisited: A method to
864	calculate the mobility of bimodal sediment mixtures" In: Marine Geology 410 pp 22–
265	31 ISSN: 00253227 DOI: 10.1016/j margeo 2018.12.001
865	Mehta A.I. (2014) An Introduction to Hudraulics of Fine Sediment Transport Ed by N. I.
867	Hackensack World Scientific
868	Mignot E. D. Hurther and E. Bartelemy (Nov. 2009) "On the structure of shear stress and
860	turbulent kinetic energy flux across the roughness layer of a gravel-bed channel flow"
970	In: Journal of Fluid Mechanics 638 pp 423–452 ISSN: 0022-1120 DOI: 10 1017/
971	S0022112009990772
972	Nagshband S. J.S. Ribberink and S.J.M.H. Hulscher (2014) "Using both free surface effect
972	and sediment transport mode parameters in defining the morphology of river dunes
874	and their evolution to upper stage plane beds" In: Journal of Hudraulic Engineering
875	140.6 pp 1–6 ISSN: 19437900 DOI: 10.1061/(ASCE)HY 1943–7900.0000873
876	Nagshband S et al (2016) "Modeling river dune development and dune transition to upper
877	stage plane bed" In: Earth Surface Processes and Landforms 41.3 pp. 323–335 ISSN:
878	10969837 DOI: 10.1002/esp.3789
879	Parker, Garv et al. (2003), "Effect of Floodwater Extraction on Mountain Stream Morphol-
880	ogy". In: Journal of Hudraulic Engineering 129 11 pp. 885–895 ISSN: 0733-0429 DOI:
881	10.1061/(asce)0733-9429(2003)129:11(885)
882	Parsons Daniel R et al. (2016) "The role of biophysical cohesion on subaqueous bed form
883	size". In: Geophysical Research Letters 43.4. pp. 1566–1573. ISSN: 19448007 DOI: 10
884	.1002/2016GL067667.
885	Patel, Shaileshkumar B, Prem Lal Patel, and Prakash Devidas (2013). Threshold for initi-
886	ation of motion of unimodal and bimodal sediments. Tech. rep. 1, pp. 24–33.

-29-

- Perillo, Mauricio M., James L. Best, and Marcelo H. Garcia (2014). "A new phase diagram for combined-flow bedforms". In: *Journal of Sedimentary Research* 84.4, pp. 301–313.
 ISSN: 15271404. DOI: 10.2110/jsr.2014.25.
- Pope, Stephen B (2000). *Turbulent Flows*. Cambridge University Press.

897

898

899

900

901 902

903

904

905

906

907

908

909

910

914

915

916

921

922

923

- Prokocki, Eric W. et al. (June 2022). "The morphology of fluvial-tidal dunes: Lower Columbia
 River, Oregon/Washington, USA". In: *Earth Surface Processes and Landforms* 47.8,
 pp. 2079–2106. ISSN: 10969837. DOI: 10.1002/esp.5364.
- Rijn, Leo C. van (Jan. 2020). "Erodibility of Mud–Sand Bed Mixtures". In: Journal of Hydraulic Engineering 146.1. ISSN: 0733-9429. DOI: 10.1061/(asce)hy.1943-7900
 .0001677.
 - Ruijsscher, T.V. de et al. (2018). "Application of a Line Laser Scanner for Bed Form Tracking in a Laboratory Flume". In: Water Resources Research 54.3, pp. 2078–2094. ISSN: 19447973. DOI: 10.1002/2017WR021646.
 - Saunderson, Houston C and Francis P J Lockett (1983). "Flume experiments on bedforms and structures at the dune-plane bed transition". In: Spec Publs. int. Ass Sediment 6, pp. 49–58.
 - Schindler, Robert J. et al. (2015). "Sticky stuff: Redefining bedform prediction in modern and ancient environments". In: *Geology* 43.5, pp. 399–402. ISSN: 19432682. DOI: 10 .1130/G36262.1.
 - SICK (2012). Ranger E/D reference manual MultiScan 3D camera with Gigabit Ethernet (E), 3D camera with Gigabit Ethernet (D). Tech. rep. Waldkirch, Germany: SICK Sensor Intelligence.
 - Silberman, E. et al. (1963). "Friction factors in open channels". In: J. Hydraul. Eng. 89.HY2, pp. 97–143.
- Smith, J. Dungan and S. R. McLean (Apr. 1977). "Spatially averaged flow over a wavy surface". In: *Journal of Geophysical Research* 82.12, pp. 1735–1746. ISSN: 01480227. DOI: 10.1029/JC082i012p01735.
 - Soulsby, R. L., R. J.S. Whitehouse, and K. V. Marten (Apr. 2012). "Prediction of timeevolving sand ripples in shelf seas". In: *Continental Shelf Research* 38, pp. 47–62. ISSN: 02784343. DOI: 10.1016/j.csr.2012.02.016.
- Southard, John B and Lawrence A Boguchwal (1990). "Bed configurations in steady unidirectional water flows, part 2. Synthsis of flume data." In: 60.5, pp. 658–679.
- Van Rijn, L.C. (1984). "Sediment transport, part III: Bedforms". In: Journal of Hydraulic Engineering 110.12, pp. 1733–1754.
 - Venditti, J. G. et al. (July 2010). "Mobilization of coarse surface layers in gravel-bedded rivers by finer gravel bed load". In: Water Resources Research 46.7. ISSN: 19447973. DOI: 10.1029/2009WR008329.
- Venditti, Jeremy G. and Sean J. Bennett (Sept. 2000). "Spectral analysis of turbulent flow and suspended sediment transport over fixed dunes". In: *Journal of Geophysical Research: Oceans* 105.C9, pp. 22035–22047. ISSN: 0148-0227. DOI: 10.1029 / 2000JC900094.
- Venditti, Jeremy G. and Ryan W. Bradley (Jan. 2022). "Bedforms in Sand Bed Rivers".
 In: *Treatise on Geomorphology*. Elsevier, pp. 222–254. ISBN: 9780128182352. DOI: 10
 .1016/B978-0-12-409548-9.12519-9.
- Venditti, Jeremy G., C. Y. Martin Lin, and Moslem Kazemi (June 2016). "Variability in
 bedform morphology and kinematics with transport stage". In: Sedimentology 63.4,
 pp. 1017-1040. ISSN: 13653091. DOI: 10.1111/sed.12247.
- Warmink, J. J. et al. (2013). "Quantification of uncertainty in design water levels due to uncertain bed form roughness in the Dutch river Waal". In: *Hydrological Processes* 27.11, pp. 1646–1663. ISSN: 08856087. DOI: 10.1002/hyp.9319.
- Whiting, P.J. et al. (1988). "Bedload sheets in hetrogeneous sediment". In: *Geology* 16.2, pp. 105–108. DOI: https://doi.org/10.1130/0091-7613(1988)016{\%}3C0105:
 BSIHS{\%}3E2.3.C0;2.

- Wilcock, Peter R. (Apr. 1993). "Critical Shear Stress of Natural Sediments". In: Journal of Hydraulic Engineering 119.4, pp. 491–505. ISSN: 0733-9429. DOI: 10.1061/(ASCE) 0733-9429(1993)119:4(491).
- Williams, Philip B. and Patrick H. Kemp (Apr. 1971). "Initiation of Ripples on Flat Sedi ment Beds". In: *Journal of the Hydraulics Division* 97.4, pp. 505–522. ISSN: 0044-796X.
 DOI: 10.1061/JYCEAJ.0002932.
- Wolanski, Eric (2007). Estuarine Ecohydrology. Elsevier Science. ISBN: 9780444530660. DOI:
 10.1016/B978-0-444-53066-0.X5001-6.
- Wu, Yongsheng et al. (2022). "Tidal propagation in the Lower Fraser River, British Columbia, Canada". In: *Estuarine, Coastal and Shelf Science* 264.November 2021, p. 107695. ISSN:
 02727714. DOI: 10.1016/j.ecss.2021.107695. URL: https://doi.org/10.1016/j
 .ecss.2021.107695.
- Yalin, M.S. (1964). "Geometrical Properties of Sand Wave". In: Journal of Hydraulic Engineering 90, pp. 105–119.
- ⁹⁵⁴ (1972). Mechanics of Sediment Transport. Oxford: Pergamon Press.
- Yao, Peng et al. (Sept. 2022). "Erosion Behavior of Sand-Silt Mixtures: Revisiting the Ero sion Threshold". In: Water Resources Research 58.9. ISSN: 19447973. DOI: 10.1029/
 2021WR031788.

Supporting Information for "Fine sediment in mixed sand-silt environments impact bedform geometry by altering sediment mobility"

S.I. de Lange¹, I. Niesten¹, S.H.J. van de Veen¹, J.H. Baas², J. Lammers¹, K.

Waldschläger¹, D. Boelee¹, A.J.F. Hoitink¹

¹Wageningen University, Department of Environmental Sciences, Hydrology and Environmental Hydraulics, Wageningen, the

Netherlands

 $^2 \mathrm{School}$ of Ocean Sciences, Bangor University, Menai Bridge, United Kingdom

Contents of this file

- 1. Text S1 S5
- 2. Figures S1 S6
- 3. Table S1

Introduction In these supplementary materials, we provide additional figures and a table belonging to the manuscript "Fine sediment in mixed sand-silt environments impact bedform geometry by altering sediment mobility". We show an images of the sediment used (Figure S1), and the bed scans from all experiments, as interpolated DEMS, hillshade figures, and via profiles (Text S2). In Text S3 and the corresponding figure we extent on the difference between developed and incipient ripples. Text S4 (Figure S6) show the logarithmic velocity profiles of the experiments used to determine the hydraulic roughness via the Law of the Wall (equation 12 in manuscript), and finally, Text S5 (Table S1) shows the critical shear stress calculated with and without correction factor for the hiding exposure effect (equation 14 and A6 in the manuscript).

Х - 2

Text S1: Sediments

see Figure S1

Text S2: Bed elevation profiles

see Figure S2, S3 and S4

Text S3: Ripples on high discharge runs

Linguoid 3D ripples indicate an equilibrium state, while straight 2D ripples are an indication of non-equilibrium (Baas, 1994). Additionally, the size of the 2D ripples is significantly smaller (Figure S5). This, together with visual observation from the authors, shows that the 2D ripples visible on the hillshade figures of some high discharge runs, are artifacts formed by drainage of the flume.

:

Text S4: Logarithmic velocity profiles

see Figure S6

Text S5: Corrected critical shear stress for hiding-exposure effect

see Table S1 $\,$

references.bib

References

- Baas, Jaco H. (1994). "A flume study on the development and equilibrium morphology of current ripples in very fine sand". In: Sedimentology 41.2, pp. 185–209. ISSN: 13653091.
 DOI: 10.1111/j.1365-3091.1994.tb01400.x.
- Parker, Gary et al. (2007). "Physical basis for quasi-universal relations describing bank-full hydraulic geometry of single-thread gravel bed rivers". In: Journal of Geophysical Research: Earth Surface 112.4, pp. 1–21. ISSN: 21699011. DOI: 10.1029/2006JF000549.
- Patel, Shaileshkumar B, Prem Lal Patel, and Prakash Devidas (2013). Threshold for initiation of motion of unimodal and bimodal sediments. Tech. rep. 1, pp. 24–33.



Figure S1. Microscope images of the sediments used in this research. a) medium sand $(D_{50} = 256 \ \mu\text{m})$, b) fine sand $(D_{50} = 170 \ \mu\text{m})$, c) coarse silt $(D_{50} = 37 \ \mu\text{m})$, d) fine silt $(D_{50} = 17 \ \mu\text{m})$.



Figure S2. Hillshade figures of the final bed geometry of each experiment



Figure S3. Bed elevation models of the final bed geometry of each experiment

0.25 m/s fine sand

-

Fine sand (150 µm)

	2000 3000 4000 6000 6000 7000 8000	0.348
Ê	- Marthall Marthalan all Martin and Marthal	
150 µn		
and (1		
Fine s		
	coarse silt	coarse silt
(m		
50 µ	Marken Marken Marken Marken Marken	
e silt (
Coarse	200 100 200 200 200 200 200 200	
•		
	na <mark>bula Alabula Antara an an</mark>	
	fine silt	fine silt
		elinesister and a state of the
Ê.		

0.44 m/s

fine sand o and mailed and the state of the

0.56 m/s



			0				
00 000000		Jancon		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		- martin	
some	Cont		Sec. 1	the second	- Again	Com	2
0-				×			9
2000	3000	4000	5000	6000	7000	8000	_
			0.01	r			
00	CONTRACTOR OF		And a state of the	n -	man	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	n
50-				7 June	And a start of	wood	26
0-							
2000	3000	4000	5000	4000	2000	8000	_
			0.05				
00			-turd				
- partico	and a construction of the	annos 1	100000	Charles and a		weeks to the second second	100
50-		m	No and	~~~~~			
ملي			nuw.				_
5000	3000	4000	5000	6000	7000	18000	
erit and	como a	10					
1000	Carrille	ACCOR.	ATS A	man	marcal	Consort A	M.,
20-	- 10-	all we have	MAL. AN	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	NALTON	The	×4
2èt						12	_
2000	3000	4000	5000	6000	7000	8000	
00-			0.21	1			
Tiplotee	mannin	The second	V. Verseeling		Sector Sector	20000000000000	5007
50-							~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
							- 1
2000	3000	4000	5000	6000	7000	8000	_
			0.31	3			
	1 200	and the second second	110	-			
50				and the			
			$\neg \alpha$	g. y			
2000	3000	4000	5000	4000	2000	8000	-
			0.51				
201300							
00		-	-	The			
80-						-	-
75 <u>8.</u>					-		_
2000	3300	4000	5000	6000	7000	18000	

coarse sil



Profiles of the final bed geometry of each experiment, used to determine bedform Figure S4. geometry.



Figure S5. Example profiles with developed 3D ripples (experiment with 82% fine sand and low discharge) and incipient 2D ripples due to drainage (experiment with 51% fine sand and high discharge).

text. Experiment 13-18 are excluded from analysis, an mistake in the setup caused erroneous profiles. the calculations, is indicated bold red. Numbers indicated in the title refer to the experiment numbers as listed in Table 1 in the main Figure S6. Logarithmic velocity profiles for the all experiments. The logarithmic part of the time-averaged velocity profile as used in



Table S1. Characteristics of the sediment mixtures (D_{10}, D_{50}, D_{90}) and their mobility expressed as the critical shear stress θ_c according to Parker et al., 2007 (Par07), and corrected using equation 12 in the main manuscript (Patel et al., 2013) (Pat13).

	Fraction finer sediment in base material	D_{10} (μ m)	D_{50} $(\mu { m m})$	D_{90} $(\mu { m m})$	θ_c (-) (Par07)	$\theta_c \text{ sand } (-)$ (Pat13)	$\theta_c \text{ fines (-)} $ (Pat13)		
	Sec	limen	ts						
medium sand (base material)	1	172	255.8	378.1	0.021				
fine sand	1	100.6	169.6	284.2	0.031				
coarse silt	1	3.4	37	126.9	0.12				
fine silt	1	2.3	16.8	43.9	0.25				
Mixtures (adding finer sediment to base material)									
	0.35	131.1	228.2	357.8	0.024	0.02	0.041		
Fine sand and medium sand	0.51	118.8	213.3	343.3	0.025	0.019	0.038		
r me sand and medium sand	0.65	111.2	199.9	329.4	0.027	0.018	0.036		
	0.82	105.4	184.3	309.8	0.029	0.015	0.031		
	0.02	168	254	376.9	0.022	0.022	0.77		
	0.05	157.1	250.5	375.3	0.023	0.022	0.76		
Coarso silt and modium sand	0.11	112.8	243.1	371.7	0.023	0.021	0.75		
Coarse sitt and medium sand	0.22	32.2	228.8	364.7	0.024	0.020	0.69		
	0.32	17.9	211.6	355.8	0.026	0.019	0.58		
	0.51	8.8	151.8	331.2	0.034	0.016	0.28		
	0.02	166.8	253.8	376.8	0.022	0.022	3.3		
	0.04	158.5	251.3	375.6	0.022	0.022	3.3		
Fine silt and medium sand	0.09	131.3	245.7	373.1	0.023	0.021	3.3		
	0.23	14	226.1	363.6	0.024	0.02	1.6		
	0.3	9.8	213	357.2	0.025	0.02	1.0		