

# Cross-sectional Variables of Alluvial Channels

Bao-shan Fan<sup>1,2</sup>, Wan-guang Sun<sup>1,2</sup>, Yu-hang Liu<sup>1,2</sup>, and Cheng-zhen Li<sup>1,2</sup>

<sup>1</sup> China Water Northeastern Investigation, Design and Research Corporation Limited, Changchun, China.

<sup>2</sup> Research Center on Cold Region Engineering Ministry of Water Resources, Changchun 130061, China.

Corresponding authors: Bao-shan Fan (fanbaoshan@126.com), Wan-guang Sun ([sunwanguang@aliyun.com](mailto:sunwanguang@aliyun.com))

**Key words:** morphodynamics; fluvial process; regime equation; bedload transport; stream power conversion

## Key Points:

1) The cross-section dimension of an alluvial stream is determined by the water discharge and regime transportation length of sediment.

2) The stream width is determined by the water discharge and the energy conversion length.

3) The stream power expenditure (the energy conversion length) is relevant to Kolmogorov's microeddies in turbulence.

## Abstract

In the process of a fluvial evolution, the water discharge, sediment charge and stream energy expenditure dominant the channel patterns of a river. Given water and sediment, an alluvial channel is self-organizing, adjust to achieve a stable equilibrium state, and form a characteristic channel geometry (channel width, depth and slope). In the equilibrium condition which is also said to be in regime or graded, the flux of the water and sediment from the watershed should be equal to the flux of the downstream channel(s). By studying bed load transportation and stream power conversion on a steady and uniform stream, we suggest two characteristic parameters that are energy conversion length and regime transportation length of sediment. The regime equation and equations of fractal features are set here. All cross-section variables (stream width, depth and velocity) of a regime stream, who theoretically derived under the equilibrium

of sediment transportation and the conversion of stream power, are exclusively determined by the two lengths and the water discharge.

### **Plain Language Summary**

The dynamic characteristics of every river on the Earth are different. In order to grasp the principles of river evolution and changing processes, People have done a lot of exploration, but so far, no ideal results have been obtained. The disciplines of sediment transportation, stream energy conversion and channel fractal features are utilized, here, as constrain equations to study the crass-sectional variables of river evolution. We suggest two characteristic length that are the regime transportation length and the energy conversion length from stream power to turbulence energy. The bigger value of the regime transportation length means that the land of the basin is difficult to erode and the less sediment load is required for channel to transport. And the bigger value of the energy conversion length requires smaller bed area per unit stream reach (stream width  $B$ ) for converting stream power to turbulence energy. In the paradigm of Newtonian mechanics, the kinetic relationships among variables of a channel cross-section are theoretically given. These relationships can help us to understand the self-sculpting behavior of fluvial processes.

### **1 Introduction**

A river is a product of the interaction between its water flow and channel bed, which is achieved by means of sediment scouring and depositing on the bed. Sediment materials are sometimes as a component that takes part in the water flow or sometimes a component of the loose bed. The water flow acts on and shapes the loose bed. Meanwhile, the bed constrains the flow and affects the flowing structure. The water flow and the loose boundary are interdependent, inter-played, and mutually organized, and are always in the process of changing and adjusting. As long as the conditions of discharge and imposed sediment remain undischarged, there is an over-all tendency for the stream to approach a grade condition by self-adjustment. A stream in equilibrium, or graded, is also said to be in regime. Therefore, a regime stream is the outcomes of the self-organization and evolution according to certain dynamic principles. But there is no certainty that any stream ever has attained such an equilibrium condition in the past, and there are none at present.

However, for engineering purpose, there is extremely importance that the natural tendencies of the individual stream should be well understood the hydrologic and geomorphic reaction which it may develop when disturbed by human activities. The study on the basic principles of the self-organization of a fluvial process has a long history, and many hypotheses are proposed, of which some representatives are the

uniform distribution of energy dissipation and minimum total work in the system (Leopold, 1964), minimum variance (Langbein, 1964), minimum channel bed activity (Dou, 1964), minimum unit stream power (Yang , 1971), critical initiative condition (Li, 1976; Parker, 1978), minimum function of channel system(Chang, 1979), maximum energy dissipation rate (Huang, 1981), maximum sediment transport rate (White, 1982), maximum resistance coefficient (Davis, 1983) and so on. All these hypotheses derived a series of semi-theoretical and semi-empirical formulas, which cannot be proved rigorously and theoretically and may lead to conclusions incompatible with some observations. Therefore, the study of the principles of self-adjustment of the fluvial process is still a difficult task in river dynamics.

The geometric shape of a channel formed by self-organization is mainly determined by the factors such as water discharge, the rate of sediment supply and the debris size (Naito and Parker, 2019). For the case where the channel flow's intensity is greater than the sediment starting condition and less than the suspending condition, only the bed load exists. When the flow intensity is greater than the suspending condition of sediment, the rate of bed load and the rate of suspended load increase and decrease synchronously. So the bed load transport is accompanied all time with the fluvial process. Especially in the upstream part of a river basin, the transport of sediment is mainly bed load. The overall patterns of a river are principal components of the pool - riffle - bar unit and modes of bar development. In a fluvial process, the bar evolution is the essential connection between the episodic nature of bed material transport and the production of river morphology (Church and Ferguson, 2015). The bed load continuously takes part in the process of the river evolution and inherently deforms channel patterns laterally, such as straight, meandered or braided channels. And the channel morphology is an inevitable outcome of following the principles of self-organization, which is mainly trimmed and shaped by the bed load (Dodov and Foufoula-Georgiou, 2005).

Based on the above understanding, the study on the cross-sectional variables of river channels is implemented in combining the channel hydraulics of sediment transportation and stream power expenditure and fractal features of channels.

## **2 Bed load transport rate of an alluvial river**

### **2.1 Effective shear stress of sediment transport**

The stream power of an alluvial channel is usually consumed in three aspects, which overcomes the form resistance of the channel, the shear stress of transporting sediment and the shear stress acting on the stationary particles on the channel bed namely. The shear stress of the water flow acts on sediment particles is called the

103 effective shear stress in river dynamics. Einstein (1950) proposes that the effective  
 104 shear stress  $\tau'_b$  of water flow obeys the logarithmic law of turbulence

$$\frac{u}{u_*} = 2.5 \ln \left( 30.2 \frac{\chi y}{k_s} \right) \quad (2-1)$$

105 where  $u$  is the velocity of water flow;  $u_*$  is the shear velocity;  $k_s$  is the roughness  
 106 element dimension of river bed;  $\chi$  is the parameter for transition smooth-rough  
 107 (Einstein gives the calculation curve);  $y$  is the vertical distance from the bed.

108 For the convenience of calculation, Fan (1992, 1995) gives the fitting equations  
 109 of the calculation curve of  $\chi$  as

$$\begin{cases} \frac{k_s}{\delta} \leq 0.2, & \chi = 3.5 \frac{k_s}{\delta}; \\ 0.2 \leq \frac{k_s}{\delta} \leq 0.431, & \chi = 0.755 \ln \left( \frac{k_s}{\delta} \right) + 1.923; \\ 0.431 \leq \frac{k_s}{\delta} \leq 2.0, & \chi = 1.613 \cos \left( 0.767 \ln \frac{k_s}{\delta} \right); \\ \frac{k_s}{\delta} \geq 2.0, & \chi = 1.5 \left( \frac{k_s}{\delta} \right)^{-2} + 1.0 \end{cases} \quad (2-2)$$

110 where  $\delta = 11.6 \frac{\nu}{u_*}$  is the nominal thickness of the boundary layer,  $\nu$  is the  
 111 kinematic viscosity coefficient of water.

112 The roughness of the bed surface  $k_s$  in Eq. (2-1) is twice the particle size  $d$  of  
 113 the sediment on a river bed which is the median particle size of bed load material  $d_{50}$   
 114 (Jeremy et al, 2015). Averaging Eq. (2-1) along the water depth for the wide-channel  
 115 approximation, yields

$$\frac{U}{\sqrt{gHJ}} = 2.5 \ln \frac{11\chi H}{2d} \quad (2-3)$$

116 where  $U$  is the average velocity,  $H$  is the average water depth,  $J$  is the slope of water  
 117 flow, and  $g$  is the gravity acceleration.

118 According to Einstein's (1950) recommendation, the formula for calculating the  
 119 effective hydraulic radius  $R'_b$  of the effective shear stress  $\tau'_b$  can be obtained by  
 120 replacing  $H$  with  $R'_b$ . This becomes

$$\frac{U}{\sqrt{gR'_b J}} = 2.5 \ln \frac{11\chi R'_b}{2d} \quad (2-4)$$

121 In order to express simply, the effective shear stress  $\tau'_b$  is written in  
 122 dimensionless form  $\theta'_b$ . Consequently,

$$\theta'_b = \frac{\tau'_b}{(\gamma_s - \gamma)d} = \frac{u'^2_*}{\frac{\gamma_s - \gamma}{\gamma}gd} \quad (2-5)$$

123 where  $\gamma_s$  is the specific gravity of sediment particles;  $\gamma$  is the specific gravity of  
 124 water;  $u'_*$  is effective shear velocity .

125 The relationships among effective shear stress  $\tau'_b$ , effective shear velocity  $u'_*$ ,  
 126 and effective hydraulic radius  $R'_b$  are  $u'_* = \sqrt{\tau'_b / \rho} = \sqrt{gR'_b J}$  , in which  $\rho$  is the  
 127 density of the liquid.

128 In hydraulic calculations, the average water depth  $H$  of a channel is commonly  
 129 used, and does not appear in Eq. (2-4). But the slope  $J$  of water flow appears in the  
 130 equation which is not easy to determine and brings inconvenience to calculate the  
 131 effective shear stress. Alternatively, in order to utilize the average water depth  $H$  in  
 132 calculating the dimensionless effective shear stress  $\theta'_b$ , let Eq.(2-4) be changed into

$$\sqrt{\frac{U^2}{\frac{\gamma_s - \gamma}{\gamma}gd} \frac{1}{\theta'_b}} = 2.5 \ln \left( \frac{11\chi}{2} \frac{\gamma_s - \gamma}{\gamma} \frac{\theta'_b}{J} \right) \quad (2-6)$$

133 From Eq.(2-2), the smooth-rough transition parameter  $\chi$  is deduced as a

134 function of  $\frac{\omega d}{\nu} \sqrt{\theta'_b}$

$$\chi \sim \frac{k_s}{\delta} = \frac{2}{11.6} \frac{u'_* d}{\nu} = \frac{2}{11.6} \frac{\sqrt{\frac{\gamma_s - \gamma}{\gamma} g d d}}{\nu} \frac{u'_*}{\sqrt{\frac{\gamma_s - \gamma}{\gamma} g d}} \sim \frac{\omega d}{\nu} \sqrt{\theta'_b} \quad (2-7)$$

135 where  $\omega$  is the terminal settling velocity of a single sediment particle in still clear  
136 water. For the medium sediment particle, the settling velocity is suggested to be  
137 calculated by the formula of Zhang (1961), which is

$$\omega = \sqrt{\left(13.95 \frac{\nu}{d}\right)^2 + 1.09 \frac{\gamma_s - \gamma}{\gamma} g d} - 13.95 \frac{\nu}{d} \quad (2-8)$$

138 In accordance with Eq.(2-6) and Eq.(2-7), the dimensionless effective shear

139 stress  $\theta'_b$  is a function of  $\frac{\omega d}{\nu}$ ,  $\frac{U^2}{\frac{\gamma_s - \gamma}{\gamma} g d}$  and the slope  $J$ .

140 The well-known Manning formula reads

$$U = \frac{1}{n_m} R_b^{2/3} J^{1/2} \quad (2-9)$$

141 where  $n_m$  is Manning's roughness value;  $R_b$  (in meters, m) is the hydraulic radius that  
142 is about equal to the average depth  $H$  ( $R_b = H$ ) for wide channel approximation;  $U$  is in  
143 meters per second, m/s.

144 Eq. (2-9) can be changed into

$$J = \frac{n_m^2 U^2}{R_b^{4/3}} = \frac{n_m^2}{\nu^{4/3}} \left( \frac{\gamma_s - \gamma}{\gamma} g d \right)^{10/3} \left( \frac{U^2}{\frac{\gamma_s - \gamma}{\gamma} g d} \right)^{10/3} \left/ \left( \frac{U R_b}{\nu} \right)^{4/3} \right. \quad (2-10)$$

145 As Manning's roughness coefficient  $n_m$  is a function of the particle size  $d$  of the  
146 sediment on bed-surface in alluvial channel, it is considered that the term

147  $\frac{n_m^2}{\nu^{4/3}} \left( \frac{\gamma_s - \gamma}{\gamma} g d \right)^{10/3} \bigg/ \frac{\gamma_s - \gamma}{\gamma}$  is a function of  $\frac{\omega d}{\nu}$ . Thus, being deduced from Eq.

148 (2-6), Eq. (2-7) and Eq. (2-10), the dimensionless effective shear stress  $\theta'_b$  is a

149 function of  $\frac{\omega d}{\nu}$ ,  $\frac{U^2}{\frac{\gamma_s - \gamma}{\gamma} g d}$  and  $\left( \frac{U^2}{\frac{\gamma_s - \gamma}{\gamma} g d} \right)^{1.25} \bigg/ \sqrt{\frac{U R_b}{\nu}}$ . The symbol  $\frac{\omega d}{\nu}$

150 represents the dimensionless size of the sediment particle,  $\frac{U^2}{\frac{\gamma_s - \gamma}{\gamma} g d}$  the moving

151 capacity of the sediment particles and  $\frac{U R_b}{\nu}$  the strength of the flow turbulence. And

152 the empirical expression (Fan, 1992 and 1995) is simply given

$$\theta'_b = f' \left( \frac{\omega d}{\nu} \right) \cdot F_b^n \quad (2-11)$$

153 where  $n$  is the exponent that is given as

$$n = \begin{cases} 0.7; & \frac{\omega d}{\nu} < 1 \\ 0.8; & \frac{\omega d}{\nu} \geq 1 \end{cases} \quad (2-12)$$

154 the function  $f' \left( \frac{\omega d}{\nu} \right)$  is given as following

155

$$f' \left( \frac{\omega d}{\nu} \right) = \begin{cases} 0.145 \left( \frac{\omega d}{\nu} + 0.01 \right)^{0.152} ; & \frac{\omega d}{\nu} < 15 \\ 0.048 \left( \frac{\omega d}{\nu} - 8.8 \right)^{0.38} ; & \frac{\omega d}{\nu} \geq 15 \end{cases} \quad (2-13)$$

156

157 and  $F_b$  is the comprehensive capacity parameter for the alluvial channel flow, which is

$$F_b = \left( \frac{U^2}{\frac{\gamma_s - \gamma}{\gamma} g d} \right)^{1.5} / \sqrt{\frac{U R_b}{\nu}} \quad (2-14)$$

158 The curve of Eq. (2-11) has two parts that belong to smooth wall and rough wall  
 159 (Fan, 2017) of water flow respectively, which is disconsecutive at  $\frac{\omega d}{\nu} = 15$ .

## 160 2.2. The average velocity of bed load particles

161 According to Newton's law, the following relationship can be presented for a  
 162 design moving discrete particle with velocity  $v_s$

$$163 \quad \rho_s \frac{\pi}{6} d^3 \frac{dv_s}{dt} = F_D - F_f \quad (2-16)$$

164 where  $F_D$  is the tractive force acting on the moving discrete particle;  $F_f$  is the  
 165 frictional force for resisting the movement of the particle.

166 The tractive force can be expressed as

$$167 \quad F_D = \frac{C_D}{2} \frac{\pi}{4} d^2 \rho (u - v_s)^2 \quad (2-17)$$

168 where  $C_D$  is drag force coefficient  $C_D = 1.2$  (Cheng, 1997) for the stationary particles  
 169 on bed and  $C_D = 0.82$  for the moving particles (Zhang G., et al., 2016).

170 And the frictional force is

$$171 \quad F_f = C_f (\gamma_s - \gamma) \frac{\pi}{6} d^3 \quad (2-18)$$

172 where  $C_f$  is dynamic friction factor of submerged sediment particles  $C_f = 0.5$   
 173 (Engelund and Fredsoe 1976).

174 Combining Eqs. (2-16), (2-17) and (2-18), we get



$$\frac{dv_s}{dt} = \frac{C_f g}{V_0^2} \frac{\gamma_s - \gamma}{\gamma} \left[ (u - v_s)^2 - V_0^2 \right] \quad (2-19)$$

$$\text{where } V_0 = \sqrt{\frac{4C_f}{3C_D} \frac{\gamma_s - \gamma}{\gamma} g d} = 0.9 \sqrt{\frac{\gamma_s - \gamma}{\gamma} g d}.$$

It is observed on channel bed that sediment particles take action suddenly for moving or stopping, which means the acceleration time of a particle is negligible compared with its entire movement time. Let  $T$  is the movement period of the particle, getting

$$\frac{1}{T} \int_0^T \frac{dv_s}{dt} dt \approx 0 \quad (2-20)$$

Take Eq. (2-19) in time average and combine Eq. (2-20), yielding

$$v_s = u - V_0 \quad (2-21)$$

Since the thickness of the bed load layer is  $2d$  (Einstein, 1950), the average velocity of bed load particles is expressed as

$$V_s = \frac{1}{2d} \int_0^{2d} v_s dy \quad (2-22)$$

If Eqs. (2-1), (2-21) and (2-22) are combined, the average velocity of bed load particles is obtained

$$V_s = \varphi_0 u'_* - V_0 \quad (2-23)$$

where  $\varphi_0 = 2.5 \ln(11\chi)$  is the wall law coefficient of water flow.

### 2.3. The number of bed load particles

Following R. A. Bagnold's bed load mechanics (1966), the bed load layer is a water-sediment mixture flowing over a gravity bed. The effective shear stress  $\tau'_b$  of sediment transport is equal to two parts, viz.

$$\tau'_b = \tau'_c + T_s \quad (2-24)$$

where  $\tau'_c$  is the critical shear stress;  $T_s$  is the summing tractive force of flow in the  $2d$  thickness of bed load layer.

If there are  $N$  sediment particles in quantity moving on the channel bed per unit area, the summing tractive force  $T_s$ , acting on the moving discrete particles  $N$ , gives similar to Eq.(2-17)

$$T_s = N \frac{C_D}{2} \frac{\pi}{4} d^2 \rho (u - v_s)^2 \quad (2-25)$$

Substituting of Eq. (2-21) in Eq. (2-25), yields

$$T_s = NC_f \frac{\pi}{6} (\gamma_s - \gamma) d^3 \quad (2-26)$$

Substituting of Eq. (2-26) in Eq. (2-24), the number of sediment particles  $N$  is obtained

$$N = \frac{1}{C_f} \frac{\tau'_b - \tau'_c}{\frac{\pi}{6} (\gamma_s - \gamma) d^3} \quad (2-27)$$

207

#### 2.4. Bed load transport of channel flow

The amount of bed load transport per unit time is called the rate of bed load transport and represented by the symbol " $G_B$ " in kg/s or T/s. And the rate of bed load transport per unit width of a channel is commonly expressed in the symbol " $g_b$ " in kg/s/m or T/s/m. For the sediment particles per unit bed area  $N$  (in  $1/m^2$ ) along flowing direction with average velocity  $V_s$ , the bed load transport rate per unit width should be

$$g_b = \rho_s \frac{\pi}{6} d^3 N V_s \quad (2-28)$$

where  $\rho_s$  is the density of the liquid in  $T/m^3$ .

216 Combining Eqs. (2-23), (2-27) and (2-28), we obtain the rate of bed load  
 217 transport per unit width in dimensionless form which is quite similar to many other  
 218 sediment transport functions (Meyer-Peter and Mueller, 1948; Engelund and Fredsoe,  
 219 1976; Whipple and Tucker, 1999)

$$\Phi_b = 2(\theta'_b - \theta'_c)(\varphi_0 \sqrt{\theta'_b} - 0.9) \quad (2-29)$$

220 where  $\Phi_b = \frac{g_b}{\rho_s d \cdot \sqrt{\frac{\gamma_s - \gamma}{\gamma}} g d}$  is the dimensionless bed load transport rate per unit

221 width,  $\theta'_c = \frac{\tau'_c}{(\gamma_s - \gamma)d} = 0.045$  is the dimensionless critical shear stress (Jeremy et al.,

222 2015), the symbol  $\varphi_0$  is the same physical descriptor in Eq. (2-23).

### 223 **3 Features of steady uniform stream with equilibrium sediment transportation**

#### 224 **3.1. The geometry dimension of a stream cross-section**

225 If a channel has a movable boundary, however, then the stream width and depth  
 226 can change, along with the establishment of the channel slope. The adjusted  
 227 cross-section dimension will largely depend upon the ability of the flow to transport  
 228 its sediment charge.

229 For the bed load transportation of the stream, the sediment particles are big  
 230 enough that generally  $\frac{\omega d}{\nu} \geq 1$  is tenable, so  $n = 0.8$  in Eq. (2-11), namely

$$\theta'_b = f'\left(\frac{\omega d}{\nu}\right) \cdot F_b^{0.8} \quad (3-1)$$

231 When the effective dimensionless shear stress  $\theta'_b$  is much larger than the  
 232 dimensionless critical shear stress  $\theta'_b \geq \theta'_c$  in Eq. (2-29), as a reasonable  
 233 approximation, the non-dimensional bed load rate is simplified as

$$\Phi_b \approx 2\varphi_0 \theta'^{1.5}_b \quad (3-2)$$

234 The relationship between the bed load transport rate per unit width  $g_b$  and the rate  
 235 of bed load transport  $G_B$  of the stream is

$$g_b = \frac{G_B}{B} \quad (3-3)$$

236 where  $B$  is stream width.

237 The relationship between water discharge  $Q$  and the variables of a cross-section  
 238 (width, depth and velocity) is

$$Q = BHU \quad (3-4)$$

239 where  $H$  is the average depth and  $U$  the average velocity of the cross-section.

240 For the alluvial channel, the cross-sections are generally wider which are

241  $\frac{B}{H} > 10$ . The hydraulic radius  $R_b$  is approximately equal to the average depth  $H$  of the

242 stream. Substituting of Eq. (3-1) in Eq. (3-2) with combining Eqs. (2-14), (3-3), and  
 243 (3-4), yields

$$\frac{\sqrt{g}BH^{1.8}}{Qd^{0.3}} \left( \frac{G_B}{\gamma_s Q} \right)^{1/2} = \left( \frac{2\phi_0\gamma}{\gamma_s - \gamma} \right)^{1/2} \left[ f' \left( \frac{\omega d}{\nu} \right) \right]^{3/4} / \left( \frac{\sqrt{\frac{\gamma_s - \gamma}{\gamma}} g d \cdot d}{\gamma} \right)^{0.3} \quad (3-5)$$

244 When the particles of bed load materials are not very fine sand, for  $\frac{\omega d}{\nu} \geq 15$ ,

245 we obtain

$$\left[ f' \left( \frac{\omega d}{\nu} \right) \right]^{3/4} / \left( \frac{\sqrt{\frac{\gamma_s - \gamma}{\gamma}} g d \cdot d}{\gamma} \right)^{0.3} \approx 0.38 \quad (3-6)$$

246 For the full rough bed, the Einstein's parameter for transition smooth-rough is  
 247  $\chi = 1$ . The wall law coefficient is  $\phi_0 = 2.5 \ln(11) = 6$ . Therefore, Eq. (3-5) can be  
 248 approximately written as

$$\frac{\sqrt{g}BH^{1.8}}{Qd^{0.3}}\left(\frac{G_B}{\gamma_s Q}\right)^{1/2} = 1.0 \quad (3-7)$$

From Eq. (3-7), the geometric dimension of the stream can be obtained with response to the water discharge, sediment discharge and the debris size

$$BH^{1.8} = \left(\frac{\gamma_s Q}{G_B} d^{0.6}\right)^{1/2} \frac{Q}{\sqrt{g}} \quad (3-8)$$

The left side of Eq. (3-8) is the cross-section dimension  $BH^{1.8}$  of the stream. And the water discharge at left of the right side of the equation presents the scale of the stream. The physical meaning of Eq. (3-8) is that the cross-sectional dimension  $BH^{1.8}$  of the stream should meet the need of the conveyance of the water in term  $\frac{Q}{\sqrt{g}}$  and keep the flow ability for transporting sediment concentration  $\frac{G_B}{\gamma_s Q}$  with the debris size  $d$  that are delivered from its watershed.

As erosion occurs in a river basin, sediment enters its channel(s). A process of sediment transportation by a channel is the process that the channel adjusts its self to achieve a balance between sediment supply and sediment transportation. The charge ratio  $\frac{\gamma_s Q}{G_B}$  of water to sediment in Eq. (3-8) is the volume of runoff required to produce unit volume of sediment from the basin and is also the discharge required to transport the same (unit) volume of sediment to the downstream for the equilibrium of sediment transport. The bigger is the charge ratio  $\frac{\gamma_s Q}{G_B}$  and the debris size  $d$ , the stronger the resistance to land erosion of the basin. Therefore, the term  $\frac{\gamma_s Q}{G_B} d^{0.6}$  in Eq. (3-8) indicates the synthesized resistance to land erosion.

It is realized that parameterization of sediment transport must be an integral part of any rational description of river regime and morphodynamics (Church and Ferguson, 2015). And the term  $\frac{\gamma_s Q}{G_B} d^{0.6}$  in Eq. (3-8) is just such an integral part, thus, we suggest a synthesized parameter  $l_d$  in the unit of length

$$l_d = \left( \frac{\gamma_s Q}{G_B} \right)^{5/3} d \quad (3-9)$$

270 And Eq. (3-7) becomes

$$BH^{1.8} = l_d^{0.3} \frac{Q}{\sqrt{g}} \quad (3-10)$$

271 From the perspective of alluvial dynamics, Eq. (3-9) and Eq. (3-10) state that the  
 272 channel automatically adjusts its cross-section geometries to equilibrium conditions to  
 273 fit the transportation of the water discharge and sediment charge accompanied by its  
 274 debris size. Therefore, the synthesized parameter  $l_d$  is called regime transportation  
 275 length of sediment. And Eq. (3-10) is the regime equation for steady uniform streams  
 276 of alluvial channels.

### 277 3.2. Energy conversion of the stream

278 Practically, all problems involve non-uniform (or varied) flow in fluvial  
 279 processes. However, in order to simplifying researching, the alluvial channel  
 280 problems of a given reach can be treated in terms of an approximate solution based on  
 281 an assumption of steady uniform flow. The uniform flow has an equilibrium between  
 282 gravitational and frictional forces, that is, the gravitational component in the direction  
 283 of flow must balance the frictional resistance.

284 The frictional force is basic to the energy dissipation process in the turbulence  
 285 field of a channel flow. It makes the irrecoverable conversion of stream power into  
 286 turbulence energy, and finally into heat energy. In turbulence field, the players of the  
 287 turbulence energy transferring and dissipating are eddies with different scales. In the  
 288 continuous cycle of turbulent activities in the channel flow, large momentum bodies  
 289 with small-size eddies in the form of vortex clusters promote a series of bursting of  
 290 big eddies from the channel bed during the processes of sweeping the bed surface, and  
 291 make the transfer of momentum. The big eddies later split themselves into smaller  
 292 eddies step by step with energy consumption and momentum transfer. Very small-  
 293 size eddies diffuse and dissolve in the whole turbulence fluid finally. This cycling  
 294 movement of the vortex clusters and eddies provides the required energy for the  
 295 turbulence field, maintains the various functions of the channel flow, and ensures the  
 296 transportation of the water discharge and sediment charge with its composition.

297 Stream power quantifies the rate of potential energy expended by stream flow on  
 298 the bed and banks and dominates the transportation of sediment (Bagnold, 1966;

Whipple & Tucker, 1999; Eaton & Church, 2011). The stream power per unit stream length  $\gamma QJ$  is converting into turbulence energy at the wetted boundary of the channel. The surface of the wetted boundary is the platform where the stream power is turning into turbulence energy. For the alluvial channel flow, the bigger is the energy value  $\gamma QJ$ , the larger the wetted boundary area needed per unit stream length, or the longer the wetted perimeter needed.

The shear stress  $\tau_b$  is

$$\tau_b = \rho u_*^2 = \rho g R_b J \quad (3-11)$$

For wide channel approximation, the wetted perimeter is approximated to equal to the channel width  $B$ . The following expression can read

$$R_b = H \quad (3-12)$$

Eq. (3-4) can be changed as

$$\gamma QJ = \tau_b UB \quad (3-13)$$

The physical meaning of Eq. (3-13) is that the stream power  $\gamma QJ$  is converted into turbulent energy  $\tau_b UB$ .

For a reach in unit stream length, discharge  $Q$  is the only independent variable. But the other variables of Eq. (3-13) are all dependent variables. Therefore, the channel width  $B$  can be considered as a function of the water discharge  $Q$  in mathematical logic. It is given by Leopold & Maddock (1953) as following

$$B = \alpha_1 Q^{\beta_1} \quad (3-14)$$

where  $\alpha_1$ , who can be considered to be independent of channel width  $B$  in the point of mathematical logic, is a coefficient related to the stream energy transferring;  $\beta_1$  is an exponent.

### 3.3. The fractal features of alluvial channels

It has been noticed for a long time that the channel network of a river basin is similar to the branches of botanical trees (Mandelbrot, 1983). In fact, the morphology of channel networks is similar to that of tree roots which are all confluence growth and have fractal characteristics. Based on the fractal relationship between area and diameter, Mandelbrot(1983) introduces diameter exponent  $\Delta$ , which is expressed as

$$d_t^\Delta = d_{t1}^\Delta + d_{t2}^\Delta \quad (3-15)$$

where  $d_t$  is the diameter of botanical trees, and the exponent is  $\Delta=2$ .

If each of the fibers that constitute botanical trees has the same cross-section area  $a_f$  at every stage of its height, the total numbers of the fibers are  $n_f$ . And each area of tributaries is

$$A_t = \sum_{i=1}^{n_f} a_f, \quad A_{t1} = \sum_{i=1}^{n_{f1}} a_f, \quad A_{t2} = \sum_{i=1}^{n_{f2}} a_f$$

where  $A_t$  is the cross-section area of botanical trees;  $n_{f1}$  and  $n_{f2}$  are the numbers of  $n_f$  in the tributaries  $A_{t1}$  and  $A_{t2}$  respectively.

As  $n_f = n_{f1} + n_{f2}$ , thus the area relationship of botanical trees is

$$A_t = A_{t1} + A_{t2} \quad (3-16)$$

where  $A_t$  is the cross-section area of botanical trees.

Therefore

$$\frac{\pi}{4} d_t^2 = \frac{\pi}{4} d_{t1}^2 + \frac{\pi}{4} d_{t2}^2$$

And

$$d_t^2 = d_{t1}^2 + d_{t2}^2 \quad (3-17)$$

Thus, the exponent  $\Delta=2$  in Eq. (3-17) indicates that the area of every fiber along the tree trunk is unchanged.



Studying on the fractal features of the Mississippi River in the United States, Mandelbrot considers that the bankfull widths of the tributaries are also in accordance with Eq. (3-17), which the exponent  $\Delta=2$  is obtained for the widths of the channels of Mississippi River, which is the same as the diameter exponent of botanical trees.

For a steady uniform stream network in accordance with Eq. (3-17), it is considered that the streams of the network have the fractal feature in the following form (Mandelbrot,1983)

$$B^\Delta = \sum_{i=1}^n B_i^\Delta \quad (3-18)$$

where  $i = 1, 2, \dots, n$ ;  $n$  is the number of tributaries.

Let's simplify the stream network what two channels meet only, and marked by "1" and "2" for each. The water discharge of channel "1" is  $Q_1$ , and of channel "2"  $Q_2$ . The water discharge of the main channel downstream the confluence of the channel "1" and "2" is  $Q$ . According to the law of continuity and Eq. (3-18), yields

$$\begin{cases} Q = Q_1 + Q_2 \\ B^\Delta = B_1^\Delta + B_2^\Delta \end{cases} \quad (3-19)$$

If Eq. (3-19) does hold unconditionally, there must be

$$\frac{B^\Delta}{Q} = \frac{B_1^\Delta}{Q_1} = \frac{B_2^\Delta}{Q_2} = P_\epsilon \quad (3-20)$$

where  $P_\epsilon$  is a proportional parameter. Since channel "1" or "2" is arbitrary tributary, this parameter  $P_\epsilon$  is independent of channel width  $B$  and flow discharge  $Q$  in the point of mathematical logic.

Therefore

$$B^\Delta = P_\epsilon Q \quad (3-21)$$

This is another form of Eq. (3-14), thus, the proportional parameter  $P_\epsilon$  should be a related to the energy conversion of the stream because it represents the parameter  $\alpha_1$  of Eq. (3-14), which implies that the fractal features of Eq. (3-18) and Eq. (3-20)

are dominated by the energy conversion from stream power into turbulence energy per unit time.

Combining Eq. (3-10) of sediment transportation and Eq. (3-20) of the fractal feature, yields

$$\frac{B^{\Delta-1} l_d^{0.3}}{H^{1.8}} = \frac{B_1^{\Delta-1} l_{d1}^{0.3}}{H_1^{1.8}} = \frac{B_2^{\Delta-1} l_{d2}^{0.3}}{H_2^{1.8}} = \sqrt{g} P_\varepsilon \quad (3-22)$$

Thus

$$\frac{B^{\Delta-1}}{H^{1.8}} = \frac{\sqrt{g} P_\varepsilon}{l_d^{0.3}} \quad (3-23)$$

This fractal feature of Eq. (3-23) implies the embodiment of morphodynamic paradigms because the fractal feature of a cross-section is produced by the energy expenditure and sediment transportation of the stream. It shows the consistency of natural phenomenon and mechanism.

Due to the diversity of geological and geomorphological conditions and the hydrometeorological environment, channel networks in large river basins have formed various patterns. Only vary small catchments with a single river, the river may have a single stable form. Regardless of whether it is a large or a small river basin, rainfall and soil erosion in the catchments provide the river(s) with incoming water and sediment and the sediment composition. In order to match such conditions of the incoming water and sediment and sediment composition, the channels in the basins evolve into corresponding channel morphology for transporting the corresponding water and sediment. The geometric shape of the channel cross-section should be affected not only by sediment transportation as Eq. (3-10) showing, but also by stream energy expenditure as Eq. (3-14) stating. Thus, substituting Eq. (3-14) into Eq. (3-10), yields

$$H^{1.8} = \frac{l_d^{0.3}}{\alpha_1 \sqrt{g}} Q^{1-\beta_1} \quad (3-24)$$

Dividing Eq. (3-14) by Eq. (3-24), yields

$$\frac{B}{H^{1.8}} = \frac{\alpha_1^2 \sqrt{g}}{l_d^{0.3}} Q^{2\beta_1-1} \quad (3-25)$$

378 Here, the term  $\frac{B}{H^{1.8}}$  that reflects the cross-section shape of a channel is a  
 379 symbol not related to  $B$  because all factors at the right side of Eq.(3-25) are not  
 380 related to  $B$  where  $\alpha_1$  and  $\beta_1$  have been mentioned in Eq.(3-14).

381 Because the regime transportation length  $l_d$  of sediment is not related to  
 382 channel width  $B$ , all factors at the right side of Eq.(3-23) are irrelevant to channel  
 383 width  $B$ . Because Eq. (3-21) is another form of Eq. (3-14), Eq. (3-23) and Eq. (3-25)  
 384 should be the same. So there must be

$$\begin{cases} \Delta - 1 = 1 \\ 2\beta_1 - 1 = 0 \\ P_\varepsilon = \alpha_1^2 \end{cases} \quad (3-26)$$

385 In order to simply state the characteristics of the coefficients  $\alpha_1$  and  $P_\varepsilon$  on  
 386 energy converting from stream energy to turbulence energy, we suggest an factor  $l_\varepsilon$   
 387 in the dimension of length for the expression of  $\alpha_1$  and  $P_\varepsilon$  that can be written in  
 388 harmonious form of dimension

$$\alpha_1 = \sqrt{P_\varepsilon} = \left( \frac{1}{gl_\varepsilon} \right)^{1/4} \quad (3-27)$$

389 where  $l_\varepsilon$  is named energy conversion length.

390 The energy conversion length  $l_\varepsilon$  that is another integral part of the description  
 391 of river regime and morphodynamics, is also a parameterization of the stream power  
 392 expenditure, which is influenced by many factors, such as the shape of a channel, the  
 393 debris size on bed surface and the channel slope.

394 Combining Eq. (3-25), Eq. (3-26) and Eq. (3-27), yielding

$$\frac{B}{H^{1.8}} = \frac{1}{l_\varepsilon^{0.5}} \frac{1}{l_d^{0.3}} \quad (3-28)$$

If the channel boundary is consisted of sedimentation mainly, Eq. (3-28) presents that the channel shape  $\frac{B}{H^{1.8}}$  is determined by two factors, one is the transportation length  $l_d$ , the other is the energy conversion length  $l_\varepsilon$ .

Substituting Eq. (3-26) into Eq. (3-18), the width relationship between a channel stream and the tributaries is obtained

$$B^2 = \sum_{i=1}^n B_i^2 \quad (3-29)$$

Eq. (3-29) states two meanings. One shows the fractal relation of an alluvial channel network. The another presents dynamic relation of the bed area required per unit stream length for transferring stream power into turbulence energy.

Substituting Eq. (3-26) and Eq. (3-27) into the fractal formula of Eq. (3-21), yields

$$B = \left( \frac{1}{l_\varepsilon} \right)^{1/4} \left( \frac{Q}{\sqrt{g}} \right)^{1/2} \quad (3-30)$$

Under the aforementioned recognition, Eq. (3-14) presents the channel bed area per unit stream length for transferring stream power  $\gamma QJ$  to turbulence energy. By combining the stream power conversion formula Eq. (3-14) with Eq. (3-26) and Eq. (3-27), the resulting equation is Eq. (3-30), too. The same outcomes of the two methods of stream power conversion and fractal analyzing reveal the consistency between physical mechanism and natural phenomena.

For an equilibrium alluvial channel, or a channel graded, as the value  $B$  of stream width is the bed area per unit stream length, Eq. (3-30) implies this area is required for transferring stream power  $\gamma QJ$  to turbulence energy. The powers of the two terms

$\frac{1}{l_\varepsilon}$  and  $\frac{Q}{\sqrt{g}}$  are 1/4 and 1/2 respectively. And the bigger value of the energy

conversion length  $l_\varepsilon$  requires smaller place area per unit stream reach (stream width  $B$ ) for converting stream power to turbulence energy. In order to clarify the physical meaning, Eq. (3-30) is call energy conversion equation.

### 3.4. Cross-sectional hydraulic variables and relations

For a loose boundary channel, the ability of the flow to transport its sediment charge will largely dependent upon the flow velocity or/and slope. The adjusted flow velocity and slope are the outcomes of the stream power conversion and the equilibrium sediment transportation of a stream during fluvial processes.

According to the continuity formula Eq. (3-4), the equilibrium sediment transportation Eq. (3-10) can be changed into

$$U = \left( \frac{H}{l_d} \right)^{0.3} \sqrt{gH} \quad (3-31)$$

For a steady uniform and equilibrium sediment transportation stream, Eq. (3-31) gives the relation between the average velocity and the average water depth of the cross section of the stream.

Along with the establishment of a channel slope (graded channel), the stream width and depth can change on the loose channel bed. Then, the velocity of flow depends not only on discharge but also on the adjusted width and depth, and each of which also depends on discharge. Substituting Eq. (3-28) into Eq. (3-30), the relationship between water depth and flow discharge is yielding

$$H = l_d^{1/6} l_\varepsilon^{5/36} \left( \frac{Q}{\sqrt{g}} \right)^{5/18} \quad (3-32)$$

The area formula is

$$A = BH \quad (3-33)$$

where  $A$  is the cross-section area of the stream.

Combining Eq. (3-30), Eq. (3-32) and Eq. (3-33), the resulting equation is

$$A = \frac{l_d^{1/6}}{l_\varepsilon^{1/9}} \left( \frac{Q}{\sqrt{g}} \right)^{7/9} \quad (3-34)$$

Substituting Eq. (3-30) and Eq. (3-32) into Eq. (3-4), the velocity  $U$  is obtained

$$U = \frac{l_\varepsilon^{1/9}}{l_d^{1/6}} \sqrt{g} \left( \frac{Q}{\sqrt{g}} \right)^{2/9} \quad (3-35)$$

Eq. (3-30), Eq. (3-32), Eq. (3-34) and Eq. (3-35) reveal that the cross-section variables (width  $B$ , depth  $H$ , area  $A$  and average velocity  $U$ ) of a stream have a fixed exponential relationship with the water discharge as L. B. Leopold and T. Jr. Maddock (1953) state, of which stream width  $B$  is the only factor not impinged by the sediment transportation. The water depth  $H$  in Eq. (3-32), the cross-section area  $A$  in Eq. (3-34) and the stream velocity  $U$  in Eq. (3-35) are influenced by the energy conversion length and regime transportation length.

The ratio of width to depth is a parameter frequently used in river engineering. Dividing Eq. (3-30) by Eq. (3-32), yields

$$\frac{B}{H} = \left( \frac{1}{l_d} \right)^{1/6} \left( \frac{1}{l_\varepsilon} \right)^{7/18} \left( \frac{Q}{\sqrt{g}} \right)^{2/9} \quad (3-36)$$

Besides the regime transportation length  $l_d$  of a given river basin and the energy conversion length  $l_\varepsilon$ , Eq. (3-36) states the width-to-depth ratio  $\frac{B}{H}$  of alluvial stream directly proportional to the water discharge  $Q$  whose power is 2/9. Thus, the ratio of width to depth increases as the stream's discharge and abundance of the sediment discharge increases and as the size of bed material and channel slope (be proportional to the energy conversion length  $l_\varepsilon$ ) decreases.

For simplifying the expression of a channel cross-section and taking the advantage of Eq. (3-28), we suggest a cross-section indicator  $\eta$

$$\eta = \frac{B^{5/9}}{H} = \left( \frac{1}{l_d} \right)^{1/6} \left( \frac{1}{l_\varepsilon} \right)^{5/18} \quad (3-37)$$

The physical meaning of Eq. (3-37) is that a stream in equilibrium (graded, or in regime) is as one which has developed just the right cross-section shape to fit the two parameterization factors of sediment transport  $l_d$  delivered from watershed and the stream power conversion  $l_\varepsilon$ . This cross-section indicator  $\eta$  whose dimension is the

reciprocal of length power 4/9, is a function of the regime transportation length  $l_d$  and the energy conversion length  $l_e$  and not related to water discharge and more convenient for engineering practice.

#### 4. Hydraulic geometry of an alluvial channel

##### 4.1. The equilibrium state about bankfull characteristics

In a natural river, discharge supplied by runoff to a river channel fluctuates considerably over time and space, so does the sediment transportation. The key consequence of the elaboration of river morphodynamics over the past studies has been explicit recognition that river morphology is the consequence of sediment transport in the river (Church and Ferguson, 2015). The river organizes its bankfull characteristics toward an equilibrium state. And the bankfull variables of the river are considerable stable and imply the spatiotemporal equilibrium of bankfull channel characteristics. This means the bankfull characteristics of a channel presents a regime stream. In this equilibrium condition, the river is able to transport sediment at precisely the rate that is supplied to the reach without causing overall bed aggradation or degradation (Naito and Parker 2019). This physical implication of bankfull characteristics should adhere to the regime equation of Eq. (3-10).

Let  $B_{bf}$ ,  $H_{bf}$  and  $Q_{bf}$  are bankfull width, depth and discharge respectively, therefore, the bankfull relation of a stream can read according to Eq. (3-10)

$$B_{bf} H_{bf}^{1.8} = l_d^{0.3} \frac{Q_{bf}}{\sqrt{g}} \quad (4-1)$$

where  $B_{bf}$ ,  $H_{bf}$  and  $Q_{bf}$  is the bankfull width, depth and water discharge of the stream.

If an alluvial channel is graded, or in regime conditions, the rate of sediment transported by the channel is equal to the rate of sediment eroded from the drainage

area. Therefore, the term  $\frac{\gamma_s Q}{G_B}$  of Eq. (3-9) is also equal to the annual volume ratio

of the water to sediment charge. Thus

$$l_d = \left( \frac{\gamma_s Q}{G_B} \right)^{5/3} d = \left( \frac{T_{vw}}{T_{vs}} \right)^{5/3} d_{50T} = \frac{d_{50T}}{S_{vm}^{5/3}} \quad (4-2)$$

where,  $T_{VW}$  is the annual volume of water charge;  $T_{VS}$  is the annual volume of gross sediment charge;  $d_{50T}$  is the medium diameter of the total sediment charge.  $S_{Vm}$  is the mean concentration of the gross sediment to the water charge.

The reciprocal of the symbol  $\frac{T_{VW}}{T_{VS}}$  in Eq. (4-2) also indicates the annual sediment concentration  $S_{Vm}$ . Using Eq. (4-2) to calculate the regime transportation length  $l_d$  of Eq. (4-1), thus, the sediment charge should be the gross sediment supplied from upstream, no matter whether the sediment transportation is suspended load material and/or bed load material. Eq. (4-1) is the regime equation of alluvial channels at the bankfull stage, which are set the particular values of bankfull discharge and corresponding bankfull channel geometry.

#### 4.2. Cross-sectional bankfull geometry and relations

Bankfull geometry refers to the channel width and depth at that discharge, as well as down-channel slope. Because bankfull discharge and bankfull channel geometry describe fundamental features of a river, a tool for predicting the change in bankfull characteristics (i.e., bankfull discharge and bankfull geometry) has a wide range of uses in engineering practice and river restoration.

Of the four variables (the slope  $J$ , width  $B$ , depth  $H$  and velocity  $U$ ), only three are independent. Consequently, three independent equations are necessary to describe the uniform (or in regime) flow in an erodible channel. The three equations can be expressed in various forms. The simplest ones, perhaps, are the cross-sectional variables of bankfull stage which are set up by Leopold, L. B., and Maddock, T., Jr. (1953), where the stream width  $B$ , water depth  $H$  and flow velocity  $U$  of a stream are expressed as a function of water discharge  $Q$  at the bankfull level

$$\begin{cases} B_{bf} = \alpha_1 Q_{bf}^{\beta_1} \\ H_{bf} = \alpha_2 Q_{bf}^{\beta_2} \\ U_{bf} = \alpha_3 Q_{bf}^{\beta_3} \end{cases} \quad (4-3)$$

where  $\alpha_1$ ,  $\alpha_2$  and  $\alpha_3$  are coefficients;  $\beta_1$ ,  $\beta_2$  and  $\beta_3$  are exponents;  $U_{bf}$  is the bankfull velocity of the water flow.

The first equation of the three is Eq. (3-14) rewritten at graded condition. Thus, Eq. (3-30) reads



$$B_{bf} = \left( \frac{1}{l_\varepsilon} \right)^{1/4} \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{1/2} \quad (4-4)$$

510 In fluvial processes, Eq. (4-4) states that the stream width at the bankfull level is  
 511 inversely proportional to the energy conversion length  $l_\varepsilon$  and directly proportional  
 512 to the water discharge  $Q_{bf}$ , but irrelevant to sediment discharge.

513 In accordance with Eq. (3-32), Eq. (3-34), Eq. (3-35), Eq. (3-36) and Eq. (3-37),  
 514 the other bankfull variables read

$$H_{bf} = l_d^{1/6} l_\varepsilon^{5/36} \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{5/18} \quad (4-5)$$

$$A_{bf} = \frac{l_d^{1/6}}{l_\varepsilon^{1/9}} \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{7/9} \quad (4-6)$$

$$U_{bf} = \frac{l_\varepsilon^{1/9}}{l_d^{1/6}} \sqrt{g} \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{2/9} \quad (4-7)$$

$$\frac{B_{bf}}{H_{bf}} = \left( \frac{1}{l_d} \right)^{1/6} \left( \frac{1}{l_\varepsilon} \right)^{7/18} \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{2/9} \quad (4-8)$$

$$\eta = \frac{B_{bf}^{5/9}}{H_{bf}} = \left( \frac{1}{l_d} \right)^{1/6} \left( \frac{1}{l_\varepsilon} \right)^{5/18} \quad (4-9)$$

515 Eq. (4-9) that determines the cross-section shape is the only morphodynamic  
 516 relation which is not related to the water discharge in the symbol  $\frac{Q}{\sqrt{g}}$  evidently.

517 Except Eq. (4-4) and the cross-section indicator  $\eta$  Eq. (4-9), the other bankfull  
 518 variables are exclusively determined by the three parameters that are the energy  
 519 conversion length  $l_\varepsilon$ , the regime transportation length  $l_d$  and the water discharge in

520 the symbol of  $\frac{Q}{\sqrt{g}}$ .

### 4.3. Tentative testing by observed data

#### 4.3.1. The fractal relation

All hydraulic variables fore-derived are based on the equilibrium of sediment transport and stream power conversion or the fractal features of streams. The equilibrium conditions of sediment transportation are presented by Eq. (4-1) that shows the cross-section dimension of a bankfull channel. And energy conversion relation Eq. (4-4) implies the fractal relation of channels which is derivative from the original fractal Eq. (3-29). Therefore, the two equations that is relevant to the regime transportation length  $l_d$  and the energy conversion length  $l_e$  respectively should be verified by observed data at least.

As limited by the data we obtained, only tentative tests can be made. The data set of gravel-bed rivers in Colorado (E. D. Andrews, 1984) and gravel-bedded reaches in the northern Rocky Mountains of USA are presented by E. R. Mueller and J. Pitlick (2014). The second data set is a large gravel bed river of USA reported by J. Pitlick and R. Cress (2002), a nearly contiguous alluvial segment of the Colorado River between approximately Rulison, Colorado, and Moab, Utah. The third data set (Table 1) is sand-bedded reaches of the Songhua River Basin located in the black soil area of Northeast China.

**Table 1** *Bankfull values of the main and tributaries of the Songhua River Basin*

River	Station	$Q_{bf}$ (m <sup>3</sup> /s)	$A_{bf}$ (m <sup>2</sup> )	$B_{bf}$ (m)	$H_{bf}$ (m)	$d_{50bs}^a$ (mm)	$J$ $\times 10^{-4}$	Note
Nenjiang	Jiangqiao	2049	1194	224	5.32	1.25	0.3	Main
Nenjiang	Dalai	1624	935	169	5.53	2.5	0.2	Main
Songhua River	Xiadaiji	2998	1699	272	6.24	1.1	0.14	Main
Songhua River	Haerb	3614	2215	427	5.18	0.25	0.5	Main
Songhua No.2	Fuyu	601	436	175	2.49	0.4	0.2	Tributary

Lalinhe	Caijiagou	516	361	148	2.44	0.7	0.3	Tributary
Yinmahe	Simajia	176	111	32	3.45	0.8	2	Tributary

$a$   $d_{50bs}$  is the medium size of debris on bed surface.

Utilizing E. R. Mueller and J. Pitlick's data to checkout Eq. (4-4), only the data of single-thread channels is selected. Fig.1 shows that Eq. (4-4) fits the three data sets forementioned when the energy conversion length is 0.244mm. The abscissa presents

the symbol  $\left(\frac{Q_{bf}}{\sqrt{g}}\right)^{1/2}$  and the ordinate the bankfull width  $B_{bf}$ , i.e., x- and y-axis are

$\left(\frac{Q_{bf}}{\sqrt{g}}\right)^{1/2}$  and  $B_{bf}$  respectively, where all variables are in meter and second. The

equation of the straight line fitted the three data sets is

$$B_{bf} = 8 \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{1/2} \quad (4-10)$$

Therefore, the average value of the energy conversion length is

$$l_\varepsilon = \left( \frac{1}{8} \right)^4 = 2.44 \times 10^{-4} \text{ m} \quad (4-11)$$

This value of the energy conversion length has an amazing coincidence with the size of microeddies (Kolmogorov's microscale, the resolved length scale). The size values of microeddies in a compound channel are varied within the ranges of 0.08 to 0.48 mm, which are observed by Adam Koziol (2015).

According to theoretical and experimental investigations (Batchelor,1959; Jong et al. 2009; Buschmann and Gad-el-Hak 2010; Ahmad and Huang, 2014; Krieger, Sinai and Nowak 2020) about Kolmogorov's microscale, the cascade proceeds to smaller and smaller scales until the Reynolds number is small enough for dissipation to be effective. Noting the fact that the Kolmogorov Reynolds number of small eddies is 1, it is estimated that the minimum value of the energy conversion length should be

$$l_\varepsilon > 5.0 \times 10^{-6} \text{ m}.$$

560 The fitted line of the three data sets, however, is close to Lacey's (1929) formula  
 561 in meter and second, viz

$$B_{bf} = 8.56 \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{1/2} \quad (4-12)$$

$$l_\varepsilon = \left( \frac{1}{8.56} \right)^4 = 1.86 \times 10^{-4} \text{ m}$$


562 Mueller and Pitlick (2013) also gives the same exponent for single-thread gravel  
 563 bed streams and rivers as flowing

$$B_{bf} = 12.22 \left( \frac{Q_{bf}}{\sqrt{g}} \right)^{1/2} \quad (4-13)$$

$$l_\varepsilon = \left( \frac{1}{12.22} \right)^4 = 4.49 \times 10^{-5} \text{ m}$$

564 The testing about Eq. (4-4), although tentatively, confirms that the exponent of  
 565 the fractal Eq. (3-14) is 1/2, and shows that the energy conversion length of Eq. (3-30)  
 566 is not a constant which needs further investigation how it is relevant to the  
 567 Kolmogorov's microeddies in the field of channel turbulence.

568



569

Fig.1 Reverse seeking the average value of the energy conversion length

#### 4.3.2. Equilibrium sediment transportation and bankfull cross-section dimension

Although differences in sediment supply between single-thread and braided channel types provide a long-recognized pattern discrimination (Mueller and Pitlick, 2014), all channel types should consistent with the sediment transportation principle

of Eq. (4-1) because of  $\frac{1}{\sqrt{g}} \sum_{i=1}^n l_{di}^{0.3} Q_{bfi} = \sum_{i=1}^n B_{bfi} H_{bfi}^{1.8} = \bar{H}_{bf}^{1.8} \sum_{i=1}^n B_{bfi}$  and

$\frac{1}{\sqrt{g}} \sum_{i=1}^n l_{di}^{0.3} Q_{bfi} = \frac{\bar{l}_d^{0.3}}{\sqrt{g}} \sum_{i=1}^n Q_{bfi} = \bar{l}_d^{0.3} \frac{Q_{bf}}{\sqrt{g}}$ , where  $\bar{H}_{bf}$  is the mean bankfull depth of the

braided reach and  $\bar{l}_d$  is the mean value of the streams; the width term  $\sum_{i=1}^n B_{bfi}$  refers

to the entire braid plain for the braided reach;  $n$  is the stream numbers of the braided reach, viz


$$\bar{H}_{bf}^{1.8} \sum_{i=1}^n B_{bfi} = \bar{l}_d^{0.3} \frac{Q_{bf}}{\sqrt{g}} \quad (4-14)$$

This expression of Eq. (4-1) for all channel types is demonstrated by the data set of E. R. Mueller and J. Pitlick (2014) and E. D. Andrews (1984) as shown in Fig.1.

The x-axis is  $\bar{H}_{bf}^{1.8} \sum_{i=1}^n B_{bfi}$  for multi-channels or  $B_{bf} H_{bf}^{1.8}$  for single-thread, and

y-axis  $\frac{Q_{bf}}{\sqrt{g}}$ . The mean value  $\bar{l}_d$  of the streams in the northern Rocky Mountains is

$\bar{l}_d = 1.0\text{m}$ .



**Figure 2.** The cross-section dimension and discharge of bankfull stage

Fig.2 presents the data sets of the Colorado streams and the Songhua River Basin, too. With an annual runoff of 734.7 billion cubic meters and a drainage area of 565,800 square kilometers, the Songhua River Basin has 16 tributaries whose drainage area are exceeding 10,000 square kilometers. The summary information for the main and three tributaries of the Songhua River is presented in Table 2. Unlike the energy conversion length that can be obtained by reverse seeking, the regime transportation length  $l_d$  can be calculated according observed data by Eq. (4-2). The calculating outcomes are listed in Table 2, where the mean value of the length  $l_d$  of the Songhua River basin is 726m shown in Fig.2.

**Table 2** Summary information for the main and tributaries of the Songhua River

River	Station	Drainage Area, km <sup>2</sup>	Mean Annual Discharge, m <sup>3</sup> /s	Annual Sediment Load, t/yr	$S_{vm}$ $\times 10^{-5}$	$d_{50T}$ (mm)	$l_d^b$ (m)
Nenjiang	Jiangqiao	162,569	347	$329 \times 10^4$	11.34	0.048	181
Nenjiang	Dalai	221,715	642	$268 \times 10^4$	4.98	0.046	682
Songhua River	Xiadaiji	363,923	1151	$339 \times 10^4$	3.52	0.038	1005

Songhua River	Haerb	389,769	1395	$634 \times 10^4$	5.44	0.037	474
Songhua No.2	Fuyu	71,783	528	$111 \times 10^4$	2.52	0.034	1565
Lalinhe	Caijiagou	18,339	99.70	$28 \times 10^4$	3.38	0.041	1160
Yinmahe	Simajia	7,573	19.63	$71.5 \times 10^4$	43.59	0.035	14

b  $l_d$  is calculated according to Eq. (4-2).

The testing of Fig.2 about Eq. (4-1) indicates that the bankfull relation between the dimension of channel cross-section and the water discharge are the outcomes of the fluvial processes in the equilibrium of sediment transport.

## 5. Discussion

A stream of bankfull stage should adhere to the mechanical principle of Eq. (3-8).

Therefore, the term  $\frac{\gamma_s Q}{G_B} d^{0.6}$  in Eq. (3-8) can be written as

$$l_d = \frac{\gamma_s Q}{G_B} d^{0.6} = \frac{d_{50bf}^{0.6}}{S_{Vbf}} \quad (6-1)$$

where  $S_{Vbf}$  is the volume concentration of the total sediment transportation at the bankfull lever;  $d_{50bf}$  is the medium diameter of the total sediment.

Because the bankfull characteristics of a channel presents a regime stream, Eq. (4-10) should include condition of Eq. (6-1), thus

$$l_d = \frac{d_{50T}^{5/3}}{S_{Vm}} = \frac{d_{50bf}^{5/3}}{S_{Vbf}} \quad (6-2)$$

Thus, a dynamic expression is obtained

$$\frac{d_{50bf}}{d_{50T}} = \left( \frac{S_{Vbf}}{S_{Vm}} \right)^{5/3} \quad (6-3)$$

Because the alluvial channel patterns are determined by sediment transportation, it may make sense to introduce an indicator related channel patterns according to Eq. (6-3)

$$I_{cp} \propto \left( \frac{S_{vbf}}{S_{vm}} \right)^{5/3} = \frac{d_{50bf}}{d_{50T}} \quad (6-4)$$

615 where  $I_{cp}$  is the indicator of channel patterns.

616 For the convenience of engineering practice, we suggest the indicator in the  
617 following form

$$I_{cp} = \frac{d_{50bs}}{d_{50fp}} \quad (6-5)$$

618 where  $d_{50bs}$  is the median grain size of bed surface;  $d_{50fp}$  is the median diameter of  
619 floodplain material.

620 In future study, therefore, we are going to utilize this indicator to deal with the  
621 patterns (single-thread, meandering and braided) of channels and to research the  
622 energy conversion length with Kolmogorov's microeddies theory, how the patterns  
623 are relevant to stream power expenditure and channel slope.

## 624 **6. Conclusion**

625 The two governing equations of fluvial processes are Eq. (3-10) and Eq. (3-30),  
626 which state the equilibrium of sediment transportation and stream power conversion.

627 The regime equation Eq. (3-10) unveils the mechanical relation between the  
628 water discharge  $Q$  and the cross-section dimension  $BH^{1.8}$  of the alluvial channel  
629 flow at the bankfull level.

630 The fractal features of Eq. (3-28) and Eq. (3-29) are the outcomes of the alluvial  
631 evolution that is consistent with the mechanism of sediment transportation and stream  
632 power conversion.

633 The tentative tests demonstrate three aspects: 1) the exponent 1/2 of the energy  
634 conversion equation Eq. (3-30) is suitable to the bankfull condition Eq. (4-4) and is  
635 also in general agreement with the observations (Fig.1); 2) Eq. (3-10) of the  
636 equilibrium sediment transporting does reflect the dynamic relation between the  
637 cross-section dimension of a channel and the water discharge at the channel bankfull  
638 level Eq. (4-1); 3) the bankfull stage of the channel implies such an equilibrium  
639 condition that the annual value of the transportation length (Fig.2) fits its  
640 cross-section variables (channel width, depth and discharge).



## Acknowledgment

Financial supported from the National Key Research and Development Program of China (Project No. 2018YFC0407303), and the provision of the lecture books about river basin erosion by Dr. Wen-hong Cao (China Institute of Water Resources and Hydropower Research) is gratefully acknowledged.

Datasets for this research are available in this in-text data citation reference: Bao-shan FAN et al., figshare (2020).

[doi.org/10.6084/m9.figshare.11782206](https://doi.org/10.6084/m9.figshare.11782206).

Or [https://figshare.com/articles/Songhua\\_River\\_Regime/11782206](https://figshare.com/articles/Songhua_River_Regime/11782206)

## References

Ackers P., W. R. White (1973). Sediment transport: new approach and analysis. *Journal of Hydraulic Division, American Society of Civil Engineers*, 99(11):2041- 2060.

Ackers P. (1992). Canal and river regime in theory and practice. 1929 to 1992. 1992 Gerald Lacey memorial lecture, British Section, *Ice Proceedings Water Maritime & Energy*, 96, 167– 178, London, UK.

Adam Koziol (2015 ). Scales of Turbulent Eddies in a Compound Channel, *Acta Geophysica*, 63(2), 514-532. DOI: 10.2478/S11600-014-0247-0

Ahmad I.,Y. Huang, Z., Lu (2014). Detrended analysis of Reynolds stress in a decaying turbulent flow in a wind tunnel with active grids, *Journal of Hydrodynamics*. 26(1),122-128.DOI: 10.1016/S1001-6058(14)60014-7

Andrews, E. D. (1984) Bed-material entrainment and hydraulic geometry of gravel-bed rivers in Colorado, *Geological Society of America Bulletin* , Vol. 95, 371-378.

Bagnold, R. A. (1966), An approach to the sediment transport problem from general physics. US Geological Survey Professional Paper, No. 422-1, Washington, D. C.

Bagnold R. A. (1977). Bedload transport by natural rivers. *Water Resources Research*, 13(2): 303 - 312.

- Batchelor, G. K. (1959). Small-scale variation of convected quantities like temperature in turbulent fluid part 1. general discussion and the case of small conductivity. *Journal of Fluid Mechanics*, 5, 113-133 .
- Buschmann M.H., M. Gad-el-Hak (2010). Kolmogorov scaling of turbulent flow in the vicinity of the wall. *Physica D*, 239:1288 – 1295.
- Carbonneau, P., S. Lane, and N. E. Bergeron (2004). Catchment - scale mapping of surface grain size in gravel bed rivers using airborne digital imagery. *Water Resources Research*, 40. W07202. <https://doi:10.1029/2003WR002759>
- Carling P.A., Cao Z., Holland M. J., Ervie D.A. and Babayan Koopaei K. ( 2002) Turbulent flow across a natural compound channel. *Water Resources Research*, AGU. 38, 6-1- 6-11.
- Carson, M. A. (1984). The meandering - braided river threshold: A reappraisal. *Journal of Hydrology*, 73, 315–334.
- Chang, H. H. (1979). Minimum Stream Power and River Channel Patterns. *Journal of Hydrology*, 41, 303–327.
- Cheng, N. S. (1997). A simplified settling velocity formula for sediment particle. *Journal of Hydraulic Engineering*, 123: 149–152.
- Church, M., M. A. Hassan, and J. F. Wolcott (1998). Stabilizing self-organized structures in gravel-bed stream channels: Field and experimental observations. *Water Resources Research*, 34, 3169–3179.
- Church, M. (2006). Bed material transport and the morphology of alluvial river channels. *Annual Review of Earth and Planetary Sciences*, 34, 325–354.
- Church M, and R. I. Ferguson (2015). Morphodynamics: Rivers beyond steady state. *Water Resources Research*, 51(4), 1883–1897.
- Coulthard, T. J. (2005). Effect of vegetation on braided stream pattern and dynamics. *Water Resources Research*, 41, W04003. <https://doi:10.1029/2004/WR003201>
- Dade, W. B., and P. F. Friend (1998). Grain-size, sediment-transport regime, and channel slope in alluvial rivers. *Journal of Geology*, 106, 661–675.
- Davis T. R. H., and Sutherland A. J. (1983). Extremal hypotheses for river behavior. *Water Resources Research*, 19(1), 141–148.

700 Dietrich, W. E., and J. D. Smith (1984). Bed load transport in a river meander. *Water*  
701 *Resources Research*, 20, 1355–1380.

702 Di Silvio, G., and M. Nones (2014). Morphodynamic reaction of a schematic river to  
703 sediment input changes: Analytical approaches. *Geomorphology*, 215, 74–82.

704 Dodov B, Foufoula-Georgiou E (2005) Fluvial processes and stream flow variability:  
705 interplay in the scale-frequency continuum and implications for scaling. *Water*  
706 *Resources Research* 41(5): W05005

707 Dou, G. (1964). Channel bed evolution of alluvial rivers and tidal estuaries in plain.  
708 *Journal of Hydraulic Engineering*, (2), 1–13 (In Chinese).

709 Eaton, B. C., & Church, M. (2011). A rational sediment transport scaling relation  
710 based on dimensionless stream power. *Earth Surface Processes and Landforms*,  
711 36(7), 901–910. <https://doi.org/10.1002/esp.2120>

712 Einstein, H. A. (1950). The bed-load function for sediment transportation in open  
713 channel flows, USDA Tech. Bull. 1026. Washington D.C.

714 Engelund, F., and J. Fredsoe (1976), A sediment transport model for straight alluvial  
715 channels, *Nordic Hydrology*, 7, 293–306.

716 Fan, B. (1992). A Theoretical Study on Sediment Transport, 5th International  
717 Symposium on River Sedimentation, KARLSRUHE, FRG, 4.

718 Fan, B. (1995). Kinematic study on fluvial sediment. *Journal of Sediment Research*,  
719 (3), 72–78 (In Chinese).

720 Fan, B., et al. (2017). Theory and application of sediment transport and ice load in  
721 open channel flow (In Chinese). *China Water & Power Press (CWPP)*, Beijing,  
722 5.

723 Ferguson, R., and M. Church (2009). A critical perspective on 1 - D modeling of river  
724 processes: Gravel load and aggradation in lower Fraser River. *Water Resources*  
725 *Research*, 45, W11424. <https://doi:10.1029/2009WR007740>

726 Fiorentino M., et al. (1993). An entropy-based morphological analysis of river basin  
727 networks. *Water Resources Research*, 29(4), 1215–1224.

728 Gran, K., and C. Paola (2001). Riparian vegetation controls on braided stream  
729 dynamics. *Water Resources Research*, 37, 3275–3283.

730 Jähmlich S., L. C. Lund-Hansen, T. Leipe (2002). Enhanced settling velocities and  
731 vertical transport of particulate matter by aggregation in the benthic boundary  
732 layer. *Geografisk Tidsskrift, Danish Journal of Geography* 102, 37–49.

733 Jeremy G. V., N. Domarad, M. Church, C. D. Rennie (2015). The gravel-sand  
734 transition: Sediment dynamics in a diffuse extension. *Journal of Geophysical*  
735 *Research: Earth Surface*, 10.1002/2014JF003328, 120, 6, 943-963.

736 Jong, J.D., . Cao, S. H. Woodward, J. P. L. C. Salazar, L. R. Collins and H. Meng.  
737 (2009) Dissipation Rate Estimation from PIV in Zero-Mean Isotropic Turbulence.  
738 *Experiments in Fluids*, 46, 499-515.

739 Habersack, H. M., and J. B. Laronne (2001). Bed load texture in an alpine gravel bed  
740 river. *Water Resources Research*, 37, 3359–3370.

741 Harvey, A. M. (2002). Effective time scales of coupling within fluvial systems.  
742 *Geomorphology*, 44, 175–201.

743 Howard, A. D. (1967). Drainage analysis in geological interpretation, A summation.  
744 *American Association of Petroleum Geologists Bulletin*, 51, 2246–2259.

745 Huang W. (1981). The law of maximum rate the energy dissipation on continuum  
746 dynamics. *Journal of Tsinghua University*, (1): 87–96 (In Chinese).

747 Kieran B. J. Dunne, Douglas J. Jerolmack. (2018). Evidence of, and a proposed  
748 explanation for, bimodal transport states in alluvial rivers. *Earth Surface*  
749 *Dynamics* 6:3, 583-594, <https://doi.org/10.5194/esurf-6-583-2018>

750 Kleinhans, M. G., H. R. A. Jagers, E. Mosselman, and C. J. Sloff (2008). Bifurcation  
751 dynamics and avulsion duration in meandering rivers by one - dimensional and  
752 three - dimensional models. *Water Resources Research*, 44, W08454.  
753 <https://doi:10.1029/2007WR005912>

754 Krieger, M.S., Sinai, S. and, M.A.Nowak (2020). Turbulent coherent structures and  
755 early life below the Kolmogorov scale. *Nature Communications* 11, 2192 .  
756 <https://doi.org/10.1038/s41467-020-15780-1>

757 Lacey, G. (1929). Stable channels in alluvium. *Proceedings of the Institute of Civil*  
758 *Engineers*, London, 229: 259-292.

759 Langbein, W. B. (1964). Geometry of river channels. *Journal of the Hydraulic*  
760 *Division, American Society of Civil Engineers*, 90(HY2), 301–312.

- Leopold, L.B. and T. Maddock (1953). The hydraulic geometry of stream channels and some physiographic implications. *United States Geological Survey Professional Paper*, 252. [Google Scholar](#)
- Leopold, L. B., M. G. Wolman and J. P. Miller (1964). Fluvial Processes in Geomorphology. W. M. Freeman and Co., 522 pages.
- Li, R., D. D. Simons, and M. A. Stevens (1976). Morphology of cobble streams in small watersheds. *Journal of the Hydraulic Division, American Society of Civil Engineers*, 102(8), 1101–1118.
- LI Y., J. DENG, and Z. SUN (2003). A study on river bed erosion downstream from the Tree Gorges Reservoir, *Journal of Basic Science and Engineering*, 11(3): 283-295.
- Lom, A., J. S. Ribberink, and G. Parker (2008). Vertical sorting and the morphodynamics of bed form-dominated rivers: A sorting evolution model. *Journal of Geophysical Research*, 113, F01019. <https://doi:10.1029/2006JF000618>
- Mandelbrot, B. B. (1983). The Fractal Geometry of Nature. San Francisco: Freeman, 156-163.
- Meyer-Peter, E., and R. Mueller (1948), Formulas for bed-load transport, paper presented at 2nd Meeting, Int. Assoc. of Hydraul. Eng. and Res., Stockholm.
- Millar, R. G. (2000). Influences of bank vegetation on alluvial channel patterns. *Water Resources Research*, 36, 1109–1118.
- Mueller, E.R., and J. Pitlick. (2013). Sediment supply and channel morphology in mountain river systems: 1. Relative importance of lithology, topography, and climate . *Journal of Geophysical Research: Earth Surface*, 118, 2325-2342. doi:10.1002/2013JF002843
- Mueller, E.R. and J. Pitlick. (2014). Sediment supply and channel morphology in mountain river systems: 2. Single thread to braided transitions. *Journal of Geophysical Research: Earth Surface*, 119, 7, 1516-1541, doi:10.1002/2013JF002843.
- Naito, K., & Parker, G. (2019). Can bankfull discharge and bankfull channel characteristics of an alluvial meandering river be cospecified from a flow duration curve?. *Journal of Geophysical Research: Earth Surface*, 124, 10, 2381-2401, <https://doi.org/10.1029/2018JF004971>.

794 Parker, G. (1978). Self-formed straight rivers with equilibrium banks and mobile bed:  
795 Part 2, The gravel rivers. *Fluid Mechanics*, 89(1), 127 – 146.

796 Pitlick J. and R. Cress (2002), Downstream changes in the channel geometry of a  
797 large gravel bed river. *Water Resources Research*, 38(10): 34-1-34-11.  
798 <https://doi.org/10.1029/2001WR000898>

799 Shi, C. and Zhang, D. (2003), Processes and mechanisms of dynamic channel  
800 adjustment to delta progradation: the case of the mouth channel of the Yellow  
801 River, China. *Earth Surface Processes and Landforms*, 28, 609-624.

802 Schumm, S. A. (1960). The shape of alluvial channels in relation to sediment type,  
803 US Geological Survey Professional Paper, 352B.

804 Shvidchenko A. B, G. Pender (2000). Flume study of the effect of relative depth on  
805 the incipient motion of coarse uniform sediments. *Water Resources Research*,  
806 36(2): 619 - 628.

807 Slingerland, R., and N. D. Smith (2004). River avulsions and their deposits, *Annual*  
808 *Review of Earth and Planetary Sciences*, 32, 257– 285.

809 Whipple, K. X., and Tucker, G. E. (1999). Dynamics of the stream - power river  
810 incision model: Implications for height limits of mountain ranges, landscape  
811 response timescales, and research needs. *Journal of Geophysical Research*,  
812 104(B8), 17,661– 17,674.

813 Wilcock, P. R., and J. C. Crowe (2003). Surface-based transport model for mixed-size  
814 sediment. *Journal of Hydraulic Engineering*, 129, 120 – 128.

815 White, W. R., Bettis R., and Paris E. (1982). Analytical approach to river regime.  
816 *Journal of the Hydraulic Division, American Society of Civil Engineers*,  
817 108(HY10), 1179 –1193.

818 Yager, E. M., J. W. Kirchner, and W. E. Dietrich (2007). Calculating bed load  
819 transport in steep boulder bed channels. *Water Resources Research*, 43(7),  
820 W07418. <https://doi.org/10.1029/2006WR005432>

821 Yen, B.C., (1992). Dimensionally homogeneous Manning' s formula. *Journal of*  
822 *Hydraulic Engineering*, 118 (9), 1326-1332.

823 Yang, C.T. (1971). Potential Energy and Stream Morphology. *Water Resources*  
824 *Research*, 7(2), 312–322.

825 Zhang G., et al. (2016). Incipient velocity formula of non-cohesive uniform sediment  
826 based on relative exposure degree (In Chinese). *Journal of basic science and*  
827 *Engineering*. 24(4), 687-697.

828 Zhang R., et al. (1961). The dynamics of river (In Chinese). *China Industry Press,*  
829 *Beijing*.

830