

Impact of ice aggregate parameters on microwave and sub-millimetre scattering properties

Robin Ekelund and Patrick Eriksson

Chalmers University of Technology, Gothenburg, Sweden
robin.ekelund@chalmers.se, patrick.eriksson@chalmers.se



Introduction

Understanding electromagnetic scattering by ice particles is important for microwave radiative transfer and remote sensing. Ice aggregates have complex shapes, but are generally simplified in models. Improving the representation of aggregates could lead to better weather prediction through data assimilation, for instance.

This study investigates the impact of aggregate characteristics on single and bulk scattering properties. The total modelling system consists of two parts. 1) Generating particle model data, and 2) Calculating the scattering properties of generated particles.

This poster is based on the study presented in [1].

Particle model data

Aggregate particles were generated in a stochastic fashion, explicitly simulating the aggregation of hexagonal crystals.

Several simulation runs were performed, assuming different crystal axis ratio r_{cryst} , ranging from 1/15 to 15. r_{cryst} is here defined as $r_{\text{cryst}} = h/(2a)$, where h is the height and a the side base length of the crystal.



Fig. 1: Example aggregates composed of columns, blocks and plates ($r_{\text{cryst}} = 15, 1$ and $1/15$, respectively.)

The particles are here mainly characterized using the aerodynamic area ratio A_r :

$$A_r = \frac{4A_{\text{aer}}}{\pi D_{\text{veq}}^2},$$

where A_{aer} is the aerodynamic area and D_{veq} is the volume-equivalent diameter of the particle.

Scattering calculations

Electromagnetic scattering by the aggregates was calculated using the Discrete Dipole Approximation (DDA) method, which treats arbitrarily shaped particles. The Amsterdam DDA implementation was used.

Incident radiation travels along the nadir or zenith direction, and particles are aligned with their maximum moment of inertia axes normal to the horizontal plane.

Results: single scattering

Single scattering properties are shown in terms of extinction efficiency Q_e at common passive microwave frequencies 183.31, 325.15 and 664.00 GHz, and back-scattering efficiency Q_b at radar frequencies 13.4, 35.6 and 94.1 GHz.

Only particles with $D_{\text{veq}} \approx 2$ mm are shown here.




Fig. 2: Left: A_r as a function of r_{cryst} . Middle: Back-scattering as a function of A_r . Right: Extinction as a function of A_r . Points represent individual particles, while the full lines are 3-degree polynomial fits and dashed lines are the associated prediction bounds. R-squared values (R^2) are reported for each fit in the legends.

Results: bulk scattering

Bulk scattering quantities (i.e. scattering from a whole volume element) such as the extinction coefficient γ_e , are calculated for particle ensembles assuming an exponential size distribution, i.e. $N(D_{\text{veq}}) = N_0 e^{-\Lambda D_{\text{veq}}}$.

Bulk back-scattering is shown in terms of radar triple frequency signatures, defined as pairs of dual wavelength ratios (DWR), i.e. ratios of radar reflectivities (in log-space) at three selected radar frequencies.




Fig. 3: Bulk scattering properties, divided into lines of r_{cryst} . Legends are common to all panels. Left: Bulk extinction as a function of ice water content (IWC) at 183.31 GHz and 664.00 GHz. Middle: As left, but with snowfall rate R_{leq} on the x-axis. Right: Triple frequency signatures, at frequencies: 13.4, 25.6 and 94.1 GHz (K_u , K_a and W-band, respectively).

Conclusions

A clear impact of crystal axis ratio (r_{cryst}) on resulting simulated aggregates characteristics, e.g. aerodynamic area ratio (A_r), can be observed.

Moreover, A_r shows a clear impact on investigated single scattering properties, i.e. extinction efficiency and back-scattering.

Bulk extinction (γ_e) shows less sensitivity to r_{cryst} at 664 GHz than at 183 GHz. Also, retrieval of snowfall rate is potentially more accurate than for ice water content.

Outlook

Ongoing efforts focus on the impact on radiative transfer simulations.




Fig. 4: Occurrence frequencies of simulated brightness temperatures, assuming different particle models taken from [2]. Simulations mimic GPM Global Imager (GMI) measurements over the tropical pacific ocean. Synthetic scenes based on the v2.1.1 DARDAR product were used as input.

Acknowledgements/References

The ADDA calculations were performed mainly at the central Chalmers cluster C3SE, and this study was financially supported by the Swedish National Space Agency (SNSA) under Grant 150/44.



- [1] Robin Ekelund and Patrick Eriksson. Impact of ice aggregate parameters on microwave and sub-millimetre scattering properties. *J. Quant. Spectrosc. Radiat. Transf.*, 224:233–246, feb 2019.
- [2] P. Eriksson, R. Ekelund, J. Mendrok, M. Brath, O. Lemke, and S. A. Buehler. A general database of hydrometeor single scattering properties at microwave and sub-millimetre wavelengths. *Earth System Science Data*, 10(3):1301–1326, 2018.