

Characterization of Canopy Anisotropies over a Forested Area using a Multispectral Imager Integrated into an Unmanned Aerial System: the Droniometer Experiment


Sergio Bernardes & Marguerite Madden

Center for Geospatial Research (CGR), Department of Geography, The University of Georgia
(sbernard@uga.edu, www.cgr.uga.edu)

BACKGROUND

Challenges in remote sensing, including remote sensing of vegetation, include the spectral characterization of objects over space and time. One key aspect for this characterization involves the geometry of data acquisition and positional relationships between light source, the target and the remote sensor. Several configurations of goniometers have been used to acquire spectral data as a function of this geometry and this strategy has been particularly successful when applied to the study of short canopies (e.g., grasses). Tall canopies present logistical challenges when conducting proximal multi-angle remote sensing analyses, which can be resolved by replacing physical structures (rails) with flying systems capable to conform to different canopy geometries and data acquisition requirements.

Proximal multi-angle remote sensing solutions



Data acquisition geometry



Spectra Vista Corporation

Proximal multi-angle remote sensing solution for short canopies

Droniometer (aerial goniometer)

This work (the Droniometer Experiment) investigates anisotropies of a forested area using radiometrically calibrated images from a multispectral camera (MicaSense RedEdge) mounted on a rotary-wing unmanned aerial system programmed to follow a planned flight that simulates data acquisition by a goniometer assembled over a tall canopy.

The experiment uses multiple planned flights, conducted to represent changes in illumination, considering sun azimuth and elevation (multiple flights per day and over the course of months).

Multi-angle data acquisition is addressed by controlling aircraft position and camera pitch at regular intervals.

Matrice 600 Pro

- Ronin-MX gimbal
- Multisensor integration
- 25+ min. flight





Phantom 4 Pro

- camera: RGB, 20 MP
- 1 inch CMOS sensor
- ~30 min. flight/battery
- Augmented with multispectral system



Field site and target characteristics

Athens, Georgia





Stand of loblolly pine (*Pinus taeda*)

Area: ~57 acres

Challenges for proximal multi-angle remote sensing

- can reach 30–35 m (98–115 ft). Exceptional specimens may reach 50 m (160 ft).
- variations in the geometry of illumination.

Addressing variations in geometry of illumination over time



Changes in solar elevation and azimuth for a year over the field site.


Droniometer (aerial goniometer)

Platforms and sensor



MicaSense RedEdge

- multispectral (RGB, NIR, red edge)
- 3.6 MP, Global Shutter
- downwelling radiation sensor
- GPS
- calibration Panel




Software and hardware received different degrees of augmentation and in-house customizations.

Modes of data acquisition:

- Multi-angle view controlled by gimbal (changes in sensor pitch)
Flight mode: multiple orbit with common center of orbit lock
Decreasing orbit radius with increase in flight height
UAV looks inwards
- Multi-angle view controlled by gimbal (changes in sensor pitch)
Flight mode: UAV rotates around its vertical axis (pivot mode)
UAV looks outwards
- Multi-angle view with reduced gimbal control
Pixel selection from frame
Decreasing orbit radius with increase in flight height

Design for data acquisition:

- one acquisition per month over 12 months
- times of acquisition: 9:00 am, 12:00 pm and 3:00 pm
- angles of acquisition (20-degree step): 0°, 20°, 40°, 60°, 80°
- flight height: 80 m (262.5 feet) above canopy (5.45 cm GSD)
- image collection from calibration panel before and after flight
- use of downwelling radiation sensor



Data acquisition design options, showing concentric paths for orbit flights (including changes in camera pitch) and configuration for data collection including multiple azimuth angles.

Processing:

- account for dark pixel offset (unbias images)
- compensate for imager-level effects
- compensate for optical chain effects (vignette)
- normalize images by exposure and gain settings
- convert to radiance
- convert to reflectance

Challenges

- mission planning and system setup for consistent data acquisition over time
- stability of footprint dimension
- stability of sampling location
- limitations in maximum flight height and largest possible sampling area

Complementary efforts

Multi-component system integrated for data acquisition and target characterization, including a high-resolution RGB camera, a LiDAR sensor and a thermal camera.

Radiative transfer modelling of canopy anisotropies, including multispectral band simulation, and comparative analyses.

OUTLOOK

This work presents the integration of an aerial goniometer (the droniometer) system, including platform and sensor requirements and control, data acquisition and processing for target/vegetation characterization and to support multi-angle remote sensing and information extraction. Further system interactions include radiative transfer models used for comparative analysis and to further describe anisotropies in spectral responses of tall canopies.

ACKNOWLEDGMENTS

This project is being supported by the Center for Teaching and Learning at the University of Georgia-Athens, through multiple Learning Technology Grants.