

## **Estimated Energy Requirements for Pumping Pacific Ocean Water to Great Salt Lake**

**Robert B. Sowby<sup>1</sup>, Gustavious P. Williams<sup>1</sup>, and Andrew J. South<sup>1</sup>**

<sup>1</sup>Department of Civil and Construction Engineering, Brigham Young University, 430 EB, Provo, UT 84602, USA

Corresponding author: Robert B. Sowby ([rsowby@byu.edu](mailto:rsowby@byu.edu))

### **Key Points:**

- To augment Utah's declining Great Salt Lake, a pipeline to pump seawater from the Pacific Ocean has been proposed.
- With some simple assumptions, we estimate that the pumping would require at least 400 megawatts during operation.
- The significant ongoing energy use and costs are just one element of a complex project that needs careful evaluation before proceeding.

## Abstract

Great Salt Lake has receded in recent years. Among many options proposed to augment inflows is a pipeline from the Pacific Ocean. To inform discussion, we estimate a lower bound for the ongoing energy requirements, assuming one-third of the recommended additional inflow will be pumped through a single, smooth, large-diameter pipeline along a fictitious, shortest route without mountains. Accordingly, pumping would require at least 400 megawatts of electricity during operation, an amount equivalent to a large power plant, or 11% of Utah's annual electricity demand. Given current energy prices and fuel mixes, the electricity would cost over \$300,000,000 annually and emit nearly 1,000,000 metric tons of carbon dioxide annually, equivalent to 200,000 passenger vehicles. The figures could easily triple with longer routes, mountainous terrain, higher flows, smaller diameters, multiple pipelines, less-efficient pumps, and any required treatment. We present this estimate trusting that feasibility studies will include complete details.

## 1 Introduction

Great Salt Lake, located in northern Utah, USA, is a keystone ecosystem and economic resource in the western hemisphere. The lake has endured several wet and dry cycles over its recorded history, but in late 2022, water levels hit record lows and salinity hit record highs (USGS 2023). As summarized by Abbott et al. (2023), in recent years Great Salt Lake has receded as a result of excessive water use and drought. The lower lake levels significantly affect the regional ecology and have potential negative environmental, health, and economic impacts.

Among many options proposed to augment inflows to Great Salt Lake is a pipeline from the Pacific Ocean (Maffly 2022), pumping water some 1,000 km inland and 1,280 m above sea level—not counting major mountain ranges in between. While the idea sounds extreme, so are the circumstances, some argue, and all options should be kept open. First proposed in May 2022, the project is still being considered by Utah lawmakers and is an ongoing subject of public discourse.

We present a lower-bound estimate on the energy requirements of such a pipeline. We do not consider any planning, land acquisition, design, construction, permitting, finance, or other operation and maintenance costs, and we do not give an opinion on the necessity or feasibility of the project. Rather, we provide a minimal hydraulic and energy demands analysis early in the process in order to inform Great Salt Lake stakeholders, decision makers, and the public on one aspect of the project.

## 2 Analysis

To estimate the energy use, we employ fundamental equations of hydraulics: the energy equation between two points, the Hazen–Williams equation for head loss, and the pump equation for power demand. In simple terms, we compute the energy to lift water from sea level to lake level, along with friction loss and pump inefficiency. We then present the estimated energy

requirements in the context of power plant size, Utah's annual electricity use, electricity costs, and carbon dioxide equivalent (CO<sub>2</sub>e) emissions. We describe the steps below.

Researchers have recommended that the lake needs an additional  $1.5 \times 10^9$  m<sup>3</sup>/yr to recover (Abbott et al. 2023). We assume one-third of that flow ( $0.5 \times 10^9$  m<sup>3</sup>/yr) could come by pumping water from the Pacific Ocean and the remainder could come from within the watershed. We assume a route that is the shortest straight-line distance between the ocean and the lake, about 880 km. We ignore any other elevation changes due to mountains or construction issues along the route. The exercise is only to provide a minimum estimate of the energy use associated with pumping. Any actual energy use will be higher.

We analyze lifting water from the Pacific Ocean (point 1) to Great Salt Lake (point 2) with the following general equation (Mott and Untener 2015):

$$\frac{P_1}{\gamma} + z_1 + \frac{v_1^2}{2g} + h_A = \frac{P_2}{\gamma} + z_2 + \frac{v_2^2}{2g} + h_L \quad (1)$$

Because the project would move water between two open water bodies, we may eliminate the pressure terms (atmospheric assumption) and the velocity terms (large reservoir assumption) on each side:

$$z_1 + h_A = z_2 + h_L \quad (2)$$

Rearranging, the expression becomes:

$$h_A = (z_2 - z_1) + h_L \quad (3)$$

where  $h_A$  is the total head added by pumping,  $h_L$  is the total head loss due to friction, and  $z_1$  and  $z_2$  are the elevations of the Pacific Ocean and Great Salt Lake, respectively. The expression says that the head added by pumping must equal the difference in elevation between the Pacific Ocean and Great Salt Lake plus the head loss that occurs in the pipeline.

The first part of  $h_A$  is the elevation difference between Great Salt Lake and sea level (the datum), or 1,280 m. We compute the second part, head loss, using the empirical Hazen–Williams formula (Mott and Untener 2015):

$$h_L = \frac{10.67LQ^{1.85}}{C^{1.85}D^{4.87}} \quad (4)$$

where  $Q$  is the flow rate ( $0.5 \times 10^9$  m<sup>3</sup>/yr or 15.9 m<sup>3</sup>/s),  $L$  is pipe length (800,000 m),  $C$  is the roughness factor, and  $D$  is the pipe diameter. We assume a smooth pipe with a roughness value  $C$  of 140 (Mott and Untener 2015). We assume a 3.0 m diameter pipe, which is about the practical limit of large-diameter pipelines and a reasonable size for conveying the assumed flow without excessive head loss due to velocity (about 2.2 m/s for our assumptions). We ignore any minor friction losses from pipe fittings. These assumptions result in a head loss of 795 m:

$$h_L = \frac{10.67(880,000)(15.9)^{1.85}}{140^{1.85}3.0^{4.87}} = 795 \text{ m} \quad (5)$$

We now calculate the total head required (Equation 3) as the elevation difference, 1,280 m, plus the head loss of 795 m, to estimate the total head as 2,075 m.

Next we estimate the power required to increase the head of water by 2,075 m. We use the equation for pump power  $P_p$  (Mott and Untener 2015):

$$P_p = \frac{Q h_A \gamma}{\eta} \quad (6)$$

where  $\gamma$  is the specific weight of water and  $\eta$  is the efficiency of the pumping system. We assume water specific weight of  $\gamma$  equal to  $9.81 \text{ kN/m}^3$  and a rather high-efficiency pumping system where  $\eta$  is 0.80. Then

$$P_p = \frac{\left(15.9 \frac{\text{m}^3}{\text{s}}\right) (2,075 \text{ m}) \left(9.81 \frac{\text{kN}}{\text{m}^3}\right)}{0.80} \approx 400,000 \frac{\text{kN} \cdot \text{m}}{\text{s}} = 400,000 \text{ kW} = 400 \text{ MW} \quad (7)$$

This value, based on ideal conditions, represents a lower bound on the energy requirement only for raising the water over a fictitious, straight-line route that does not consider local terrain such as mountains. This does not include any other energy required for the system.

Even as a lower bound, 400 MW is a significant power requirement. It is equivalent to the output of a large power plant. (For comparison, the gas-fired Currant Creek Generating Station near Mona, Utah, has a 500 MW capacity.) The 400 MW power requirement is equivalent to 11% of Utah's 2021 electricity use of 32,768,000 MWh, based on 2021 data from the U.S. Energy Information Administration (EIA 2023a). At 2021 prices for industrial electricity in western states—about \$0.06/kWh to \$0.15/kWh (EIA 2023b)—purchasing a constant demand of 400 MW would likely cost over \$300,000,000/yr. According to the U.S. Environmental Protection Agency's Emissions & Generation Resource Integrated Database (eGRID) (EPA 2023), the 2020 fuel mix in western states (the NWPP subregion) produced about 274 kgCO<sub>2</sub>e/MWh, so a constant demand of 400 MW would emit 960,000 tCO<sub>2</sub>e/yr. The emissions would be equivalent to more than 200,000 passenger vehicles, which each emit about 4.6 tCO<sub>2</sub>e/yr on average (EPA 2022). For 2021, Utah had about 1,200,000 registered passenger vehicles, so 200,000 is approximately 17% (Utah State Tax Commission 2021). While 400 MW is a lower bound for the energy required to lift the water, actual energy requirements, again only for moving the water, could easily be three times higher because of longer routes, mountainous terrain, higher flow rates, smaller pipe diameters, multiple pipelines, less-efficient pumps, and any required treatment such as filters.

This estimate is limited by the assumptions we made. We assumed a flow of  $1.5 \times 10^9 \text{ m}^3/\text{yr}$ ; however, an actual project may assume a lower or higher flow, depending on actual needs. A smaller flow would require less water be lifted but may not sufficiently augment the lake. It may also result in a smaller pipe diameter being selected which could increase the friction losses. Higher flows would require additional energy to lift the water and would also result in higher friction losses unless a larger diameter pipe were selected. Any actual pipeline would need to

cross mountains and would require additional energy to lift the water. While some energy may be recovered through turbines on the downhill runs, the net lift of 1,280 m cannot be avoided and any mountain crossing would increase the energy requirements. To estimate the amount of carbon potentially emitted by the project, we assumed the current energy mix in Utah and other western states in the NWPP subregion. The project could be powered by cleaner energy, but 400 MW is a considerable demand for current renewable technologies, especially if the operation is to be constant. We assumed the route would be the shortest distance between the ocean and the lake, which is not feasible. Any actual route would be longer and include mountains and other terrain features, which would increase energy demands. We mention these details to provide context for our estimate. It is only meant to start the discussion, to provide managers and policymakers with an estimate of potential effort.

We provide the estimate to guide these and other similar discussions. We feel that issues such as water shortages and associated mitigation strategies should focus on efforts that are feasible and attainable, especially in the short term. Often, discussions seem to focus on solutions that later prove to be unworkable. These solutions, while important to initially consider, should be evaluated to determine if they are feasible; if not, then efforts should focus on more realistic alternatives.

In this short paper, we estimated a lower bound for energy requirements to pump water from the Pacific Ocean to Great Salt Lake. We have deliberately restricted our analysis to just one operational element of a potential major project. Any feasibility study will require conceptualization and analysis of the full system. We trust that the ultimate decision on proceeding with the pipeline will realistically consider all such elements, as well as the many alternative solutions already proposed within the Great Salt Lake watershed itself.

### **3 Conclusions**

We estimate the lower bound for energy costs to pipe water from the Pacific Ocean to Great Salt Lake is at least 400 MW of electricity. The amount is equivalent to the full output of a large power plant or 11% of Utah's annual electricity demand. At current rates, the electricity required to lift the water and overcome friction losses would cost over \$300,000,000/yr and emit nearly 1,000,000 tCO<sub>2</sub>e/yr, the same as 200,000 passenger vehicles, which is 17% of the number of vehicles registered in Utah. We present these figures as lower bounds on energy demands for discussion purposes, recognizing that they could quickly escalate with choices of route, equipment, and flow rate that differ from the unrealistic ideal conditions we assumed. We provide this analysis not as an opinion on the necessity or feasibility of the pipeline but as technical information to inform discussion alongside other alternatives, including ones proposed from within the Great Salt Lake watershed. We hope this work can help focus analysis on feasible solutions as well as provide a guide for similar situations in other locations.

### **Acknowledgments**

This work received no specific funding. Thanks to Easton Hopkins for verifying the calculations.

## Open Research

The foregoing analysis did not collect or produce any data or software. The analysis is fully documented here.

## References

Abbott, B. W., Baxter, B. K., Busche, K., de Freitas, L., Frei, R., Gomez, T., Karren, M. A., et al. (2023), Emergency measures needed to rescue Great Salt Lake from ongoing collapse.

<https://gsl.byu.edu/>

EIA (U.S. Energy Information Administration) (2023a), Retail sales of electricity: All sectors 2021. Electricity Data Browser, accessed Jan. 26.

<https://www.eia.gov/electricity/data/browser/#/topic/5?agg=0,1&geo=g&endsec=v&freq=A&start=2020&end=2021&ctype=map&ltype=pin&rtype=s&maptype=0&rse=0&pin=>

EIA (U.S. Energy Information Administration) (2023b), Average retail price of electricity: Industrial 2021. Electricity Data Browser. Accessed Jan. 26.

<https://www.eia.gov/electricity/data/browser/#/topic/7?agg=0,1&geo=g&endsec=v&linechart=ELEC.PRICE.US-ALL.A~ELEC.PRICE.US-RES.A~ELEC.PRICE.US-COM.A~ELEC.PRICE.US-IND.A&columnchart=ELEC.PRICE.US-ALL.A~ELEC.PRICE.US-RES.A~ELEC.PRICE.US-COM.A~ELEC.PRICE.US-IND.A&map=ELEC.PRICE.US-IND.A&freq=A&start=2020&end=2021&ctype=map&ltype=pin&rtype=s&pin=&rse=0&maptype=0>

EPA (U.S. Environmental Protection Agency) (2023), CO<sub>2</sub> equivalent total output emission rate (lb/MWh) by eGRID subregion, 2020. eGRID Data Explorer, last updated Jan. 11, accessed Jan. 25. <https://www.epa.gov/egrid/data-explorer>

EPA (U.S. Environmental Protection Agency) (2022), Greenhouse gas emissions from a typical passenger vehicle. Green Vehicle Guide, last updated June 30, accessed Jan. 26, 2023.

<https://www.epa.gov/greenvehicles/greenhouse-gas-emissions-typical-passenger-vehicle>

Maffly, B. (2022), Rescue Great Salt Lake with seawater from the Pacific? Utah lawmakers consider it. *Salt Lake Tribune*, May 19, accessed Jan. 25, 2023.

<https://www.sltrib.com/news/environment/2022/05/19/utah-legislature-consider/>

Mott, R. L., & Untener, J. A. (2015), *Applied Fluid Mechanics*, 7th ed., Boston: Pearson.

USGS (U.S. Geological Survey) (2023), Great Salt Lake hydro mapper. Utah Water Science Center, accessed Jan. 25. <https://webapps.usgs.gov/gsl/>

Utah State Tax Commission (2021), Utah current registrations 2021. Vehicle Registrations – Recent Data, accessed Jan. 31, 2023. <https://tax.utah.gov/econstats/mv/registrations>